

**Cauthen**

**& ASSOCIATES**

www.cauthenandassoc.com

Architects • Planners

# PROJECT MANUAL

---

PROJECT

## HVAC Replacement at Development 06-003 – Phase 2

OWNER

Housing Authority of Paducah  
2330 Ohio Street  
Paducah, Kentucky 42003

C&A Job No: 2898-01-03  
Issue Date: August 18, 2021  
Bid Date: **September 21, 2021**

Set No:

---

2908 Elm Hill Pike • Nashville TN • 37214  
9047 Executive Park Drive • Suite 221 • Knoxville TN • 37923


Ph. 615.645.5929 • fax: 615.712.8185  
Ph. 865.693.8091 • fax: 865.693.5156




SECTION 00 01 05 – CERTIFICATIONS PAGE



ARCHITECT  
Cauthen & Associates, LLC



MECHANICAL ENGINEER  
Marcum Engineering, LLC



ELECTRICAL ENGINEER  
Marcum Engineering, LLC



**SECTION 00 01 10 - TABLE OF CONTENTS**

<b>DIVISION 00 - PROCUREMENT AND CONTRACTING REQUIREMENTS</b>		<b>PAGES</b>
00 01 15	List of Drawing Sheets .....	1
 <b>DIVISION 01 - GENERAL REQUIREMENTS</b>		
01 11 00	Summary of Work.....	3
01 26 00	Contract Modification Procedures (including Architect's Supplemental Instructions, Owner-Initiated Proposal Request, Contractor's Cost Proposal, Contractor-Initiated Proposal Request and Change Order Forms) .....	7
01 29 00	Payment Procedures.....	2
01 30 00	Project Management and Coordination + Request for Information form .....	4
01 32 00	Construction Progress Documentation .....	2
01 33 00	Submittal Procedures (including Submittal Transmittal Form).....	7
01 40 00	Quality Requirements.....	5
01 45 00	Quality Control Procedures .....	5
01 50 00	Temporary Facilities and Controls .....	5
01 60 00	Product Requirements (including Substitution Request form) .....	8
01 73 00	Execution .....	7
01 73 29	Cutting and Patching .....	3
01 77 19	Closeout Procedures.....	6
 <b>DIVISION 02 – EXISTING CONDITIONS</b>		
02 41 00	Selective Demolition.....	8
 <b>DIVISION 03 – CONCRETE</b>		
03 30 00	Cast-in-Place Concrete .....	7
 <b>DIVISION 23 – HEATING, VENTILATING, AND AIR CONDITIONING (HVAC)</b>		
23 00 00	General Provisions for Mechanical.....	12
23 05 00	Common Work results for Mechanical .....	3
23 07 00	Mechanical Insulation.....	12
23 23 00	Refrigerant Piping.....	9
23 54 00	Furnaces and Condensing Units .....	6
 <b>DIVISION 26 – ELECTRICAL</b>		
26 00 00	General Provisions for Electrical.....	13
26 05 00	Common Work results for Electrical .....	3
26 05 19	Low-Voltage Electrical Power Conductors and Cables .....	3
26 05 26	Grounding and Bonding for Electrical Systems.....	2
26 05 33	Raceways and Boxes for Electrical Systems.....	3
26 28 16	Enclosed Switches and Circuit Breakers .....	3
 <b>DIVISION 31 – EARTHWORK</b>		
31 10 00	Site Clearing.....	3

**DIVISION 32 – EXTERIOR IMPROVEMENTS**

32 31 19 Chain Link Fences ..... 5

END OF SECTION 00 01 10

**SECTION 00 01 15 – LIST OF DRAWING SHEETS**

<b><u>No.</u></b>	<b><u>Description</u></b>
	Cover
C1.1	Site Plan – Dev. 06-003
A1.1	Typical Building Plan
ME0.1	Mech. & Elec. Notes, Schedules & Legend
ME0.2	Apartment Schedule
ME1.1	Mechanical/Electrical Floor Plans
ME1.2	Mechanical/Electrical Floor Plans
ME1.3	Mechanical Electrical Floor Plans
ME1.4	Overall Building 'A' Floor Plan
ME1.5	Overall Building 'B' Floor Plan
ME1.6	Overall Building 'C' Floor Plan
ME1.7	Building Elevations & Details
ME1.8	Building Elevations & Details
ME4.1	Mechanical/Electrical Details

END OF SECTION 00 01 15





## SECTION 01 11 00 - SUMMARY OF WORK

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. The owner is: The Housing Authority of Paducah, 2330 Ohio Street, Paducah, Kentucky 42003, as represented by Mr. Tommy Hollimon, Executive Director.
  - 1. Owners Representative: Tara Elder, Procurement Specialist & Special Events Coordinator.
- B. Construct the work under a Unit Price bid contract.

#### 1.02 PROJECT DESCRIPTION

- A. The project is divided into two parts:
  - 1. Replace existing HVAC systems in 11 buildings - 99 apartments.
  - 2. Provide new control wiring in conduit at the 14 buildings where the HVAC systems were replaced in Phase 1.
- B. The dwelling units will be occupied during the entire construction period.

#### 1.03 REGULATORY REQUIREMENTS

- A. Submit copies of all permits, licenses, and similar permissions obtained, and receipts for fees paid, to the owner directly.
  - 1. The contractor shall be responsible for all plan review fees and building permit fees.

#### 1.04 ACCESS TO THE SITE AND USE OF THE PREMISES

- A. Space will be available at selected locations for the contractor's storage trailer.
- B. Signs: Provide signs adequate to direct visitors. Do not install, or allow to be installed, signs other than specified sign(s) and signs identifying the principal entities involved in the project.
- C. The Contractor shall not disrupt any services to adjacent buildings without prior notification to, and approval by, the Owner.

### PART 2 - PRODUCTS (NOT USED)

### PART 3 - EXECUTION

#### 3.01 PRECONSTRUCTION MEETING

- A. A preconstruction meeting will be held at a time and place designated by the A/E, for the purpose of identifying responsibilities of the owner's and the A/E's personnel, explaining administrative procedures and signing contract documents.

- B. The contractor shall also use this meeting for the following minimum agenda:
  - 1. Construction schedule.
  - 2. Use of areas of the site.
  - 3. Delivery and storage.
  - 4. Safety.
  - 5. Security.
  - 6. Cleaning up.
  - 7. Subcontractor procedures relating to:
    - a. Submittals and change orders.
    - b. Applications for payment.
    - c. Record documents.
  
- C. Attendees shall include:
  - 1. The owner.
  - 2. The A/E.
  - 3. The contractor and its superintendent.
  - 4. Subcontractors.
  - 5. Others interested in the work.

### 3.02 SECURITY PROCEDURES

- A. Limit access to the site to persons involved in the work.
- B. Provide secure storage for materials for which the owner has made payment and which are stored on site.
- C. Secure completed work as required to prevent loss.

### 3.03 COORDINATION

- A. If necessary, inform each party involved, in writing, of procedures required for coordination; include requirements for giving notice, submitting reports, and attending meetings. Inform the owner when coordination of work is required.
- B. See other requirements in other portions of the contract documents.

### 3.04 TIMING OF THE WORK

- A. Work Areas
  - 1. The work under this contract involves multiple work areas: Prior to commencement of the work, the Contractor will submit his proposed work schedule to the Owner for review and approval.

- B. Work Schedule
  - 1. All submittals should be processed and materials ordered within the initial 30 day period.
  - 2. Contractor shall work the same work schedule as the Housing Authority which is Monday through Friday 8:00 am to 5:00 pm.
  - 3. Contractor shall not work any additional hours, weekends or holidays without prior written approval of the Housing Authority.
  - 4. Total contract time will be **150 calendar days** beginning with the Notice to Proceed date.
  
- C. Liquidated damages will be assessed based on the Contractor not meeting the schedule outlined above. Damages will be assessed at a rate of \$250.00 for each day where the schedule is not met.
  
- D. **In the event it is necessary to apply deductive alternates, the contract time may be adjusted accordingly.**

END OF SECTION 01 11 00



## SECTION 01 26 00 - CONTRACT MODIFICATION PROCEDURES

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section specifies administrative and procedural requirements for handling and processing Contract modifications.

#### 1.02 MINOR CHANGES IN THE WORK

- A. Architect will issue supplemental instructions authorizing Minor Changes in the Work, not involving adjustment to the Contract Sum or the Contract Time, on the attached form at the end of this Section.

#### 1.03 PROPOSAL REQUESTS

- A. Owner-Initiated Proposal Requests: Architect will issue a detailed description of proposed changes in the Work that may require adjustment to the Contract Sum or the Contract Time. If necessary, the description will include supplemental or revised Drawings and Specifications.
  - 1. Proposal Requests issued by Architect are for information only. Do not consider them instructions either to stop work in progress or to execute the proposed change.
  - 2. Within time specified in Proposal Request after receipt of Proposal Request, submit a quotation estimating cost adjustments to the Contract Sum and the Contract Time necessary to execute the change.
    - a. Include a list of quantities of products required or eliminated and unit costs, with total amount of purchases and credits to be made. If requested, furnish survey data to substantiate quantities.
    - b. Indicate applicable taxes, delivery charges, equipment rental, and amounts of trade discounts.
    - c. Include an updated Contractor's Construction Schedule that indicates the effect of the change, including, but not limited to, changes in activity duration, start and finish times, and activity relationship. Use available total float before requesting an extension of the Contract Time.
- B. Contractor-Initiated Proposals: If latent or unforeseen conditions require modifications to the Contract, Contractor may propose changes by submitting a request for a change.
  - 1. Include a statement outlining reasons for the change and the effect of the change on the Work. Provide a complete description of the proposed change. Indicate the effect of the proposed change on the Contract Sum and the Contract Time.
  - 2. Include a list of quantities of products required or eliminated and unit costs, with total amount of purchases and credits to be made. If requested, furnish survey data to substantiate quantities.

3. Indicate applicable taxes, delivery charges, equipment rental, and amounts of trade discounts.
  4. Include an updated Contractor's Construction Schedule that indicates the effect of the change, including, but not limited to, changes in activity duration, start and finish times, and activity relationship. Use available total float before requesting an extension of the Contract Time.
  5. Comply with requirements in Division 01 Section "Product Requirements" if the proposed change requires substitution of one product or system for product or system specified.
- C. Owner-Initiated Proposal Request Form: Use the attached form at the end of this Section. Contractor shall reply to all Proposal Requests using the Contractor's Cost Proposal form that is also attached at the end of this Section.
- D. Contractor-Initiated Proposal Form: Use the attached form at the end of this Section.

#### 1.04 CHANGE ORDER PROCEDURES

- A. On Owner's approval of a Proposal Request, Architect will issue a Change Order for signatures of Owner and Contractor on the attached form at the end of this Section.

#### **PART 2 - PRODUCTS (Not Used)**

#### **PART 3 - EXECUTION (Not Used)**

END OF SECTION 01 26 00

# ARCHITECT'S SUPPLEMENTAL INSTRUCTIONS

---

PROJECT: ARCHITECT'S SUPPLEMENTAL INSTRUCTIONS NO:

OWNER: DATE OF ISSUANCE:

ARCHITECT'S PROJECT NO.:

ARCHITECT:

---

The work shall be carried out in accordance with the following supplemental instruction in accordance with the Contract Documents without change in Contract Sum or Contract Time. Prior to proceeding in accordance with these instructions, indicate your acceptance of these instructions for minor changes to the Work as consistent with the Contract Documents and return a copy to the Architect's Representative.

Description:

Attachments:

---

ISSUED:

ACCEPTED:

BY: \_\_\_\_\_  
Architect

BY: \_\_\_\_\_  
Contractor

DATE: \_\_\_\_\_

DATE: \_\_\_\_\_





# OWNER INITIATED PROPOSAL REQUEST

---

PROJECT:

PROPOSAL REQUEST NO.:

DATE OF ISSUANCE:

OWNER:

CONTRACT DATED:

ARCHITECT:

---

Please submit an itemized proposal for changes in the Contract Sum and Contract Time for proposed modifications to the Contract Documents described herein. Submit proposal within \_\_\_\_\_ days, or notify the Architect in writing of the date on which you anticipate submitting your proposal.

THIS IS NOT A CHANGE ORDER, A CONSTRUCTION CHANGE DIRECTIVE OR A DIRECTION TO PROCEED WITH THE WORK DESCRIBED IN PROPOSED MODIFICATIONS.

---

Description:

Attachments:

---

REQUESTED BY:

ACCEPTED:

---

(Signature)

---

(Printed name and title)











# CHANGE ORDER

PROJECT:

CHANGE ORDER NO.

DATE:

ARCHITECT'S PROJECT NO.:

CONTRACT DATE:

TO CONTRACTOR:

The Contract is changed as follows:

---

**Not valid until signed by the Owner, Architect and Contractor**

---

The original Contract Sum was: \_\_\_\_\_

Net Change by previously authorized Change Orders: \_\_\_\_\_

The Contract Sum prior to this Change Order was: \_\_\_\_\_

The Contract Sum will be (increased) (decreased) (unchanged) by this Change Order  
in the amount of: \_\_\_\_\_

The new Contract Sum including this Change Order will be: \_\_\_\_\_

The contract time will be (increased) (decreased) (unchanged) by ( ) days.

The date of Substantial Completion as of the date of this Change Order therefore is: \_\_\_\_\_

NOTE: This summary does not reflect changes in the Contract Sum or Contract Time which have been authorized by Construction Change Directive.

\_\_\_\_\_  
ARCHITECT'S REPRESENTATIVE                      CONTRACTOR                      OWNER

\_\_\_\_\_  
ADDRESS                      ADDRESS                      ADDRESS

BY: \_\_\_\_\_                      BY: \_\_\_\_\_                      BY: \_\_\_\_\_

Date: \_\_\_\_\_                      Date: \_\_\_\_\_                      Date: \_\_\_\_\_





## SECTION 01 29 00 - PAYMENT PROCEDURES

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section specifies administrative and procedural requirements necessary to prepare and process Applications for Payment.

#### 1.02 SCHEDULE OF VALUES

- A. The Schedule of Amounts for Contract Payments shall be the same outline as found on the Bid Form – Section 00 41 43.

#### 1.03 APPLICATIONS FOR PAYMENT

- A. Each Application for Payment shall be consistent with previous applications and payments as certified by Architect and paid for by Owner.
  - 1. Initial Application for Payment, Application for Payment at time of Substantial Completion, and final Application for Payment involve additional requirements.
- B. Payment Application Forms: HUD 51001-Periodic Estimate for Partial Payment (Section 00 62 76), Certificate of Progress Payment (Section 00 62 76.01), HUD 51003-Schedule of Materials Stored (Section 00 62 79.01), and HUD 51004-Summary of Materials Stored (Section 00 62 79.02) as forms for Applications for Payment. Contractor shall also submit AIA Documents G702 and G703 (Application and Certificate for Payment and Continuation Sheet) or a Contractor-generated form of similar style. Copies of landfill receipts shall be included with each application for payment.
- C. Application Preparation: Complete every entry on form. Notarize and execute by a person authorized to sign legal documents on behalf of Contractor. Architect will return incomplete applications without action.
  - 1. Entries shall match data on the Schedule of Values and Contractor's Construction Schedule. Use updated schedules if revisions were made.
  - 2. Include amounts of Change Orders and Construction Change Directives issued before last day of construction period covered by application.
- D. Transmittal: Submit 4 signed and notarized original copies of each Application for Payment to Architect. One copy shall include waivers of lien and similar attachments if required.
  - 1. Transmit each copy with a transmittal form listing attachments and recording appropriate information about application.
- E. Waivers of Mechanic's Lien: With the Final Application for Payment, submit waivers of mechanic's lien from every entity who is lawfully entitled to file a mechanic's lien arising out of the Contract and related to the Work covered by the payment.

- F. Initial Application for Payment: Administrative actions and submittals that must precede or coincide with submittal of first Application for Payment include the following:
1. List of subcontractors.
  2. Schedule of Values.
  3. Contractor's Construction Schedule (preliminary if not final).
  4. All Product Submittals
  5. List of Contractor's staff assignments.
  6. Copies of building permits, if required by local authority having jurisdiction.
  7. Copies of authorizations and licenses from authorities having jurisdiction for performance of the Work.
  8. Certificates of insurance and insurance policies.
  9. Performance and payment bonds.
  10. Data needed to acquire Owner's insurance.
- G. Final Payment Application: Submit final Application for Payment with releases and supporting documentation not previously submitted and accepted, including, but not limited, to the following:
1. Evidence of completion of Project closeout requirements.
  2. Insurance certificates for products and completed operations where required and proof that taxes, fees, and similar obligations were paid.
  3. Updated final statement, accounting for final changes to the Contract Sum.
  4. AIA Document G706, "Contractor's Affidavit of Payment of Debts and Claims."
  5. AIA Document G706A, "Contractor's Affidavit of Release of Liens."
  6. AIA Document G707, "Consent of Surety to Final Payment."
  7. Evidence that claims have been settled.
  8. Final meter readings for utilities, and similar data as of date of Substantial Completion or when Owner took possession of and assumed responsibility for corresponding elements of the Work.

**PART 2 - PRODUCTS (Not Used)**

**PART 3 - EXECUTION (Not Used)**

END OF SECTION 01 29 00

## SECTION 01 30 00 - PROJECT MANAGEMENT AND COORDINATION

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes administrative provisions for coordinating construction operations on Project including, but not limited to, the following:
  - 1. General Project coordination procedures.
  - 2. Project meetings.
- B. See Division 01 Section "Execution" for procedures for coordinating general installation and field-engineering services, including establishment of benchmarks and control points.

#### 1.02 COORDINATION

- A. Coordination: Coordinate construction operations included in various Sections of the Specifications to ensure efficient and orderly installation of each part of the Work. Coordinate construction operations, included in different Sections that depend on each other for proper installation, connection, and operation.
  - 1. Schedule construction operations in sequence required to obtain the best results where installation of one part of the Work depends on installation of other components, before or after its own installation.
  - 2. Coordinate installation of different components with other contractors to ensure maximum accessibility for required maintenance, service, and repair.
  - 3. Make adequate provisions to accommodate items scheduled for later installation.
- B. If necessary, prepare memoranda for distribution to each party involved, outlining special procedures required for coordination. Include such items as required notices, reports, and list of attendees at meetings.
  - 1. Prepare similar memoranda for Owner and separate contractors if coordination of their Work is required.
- C. Administrative Procedures: Coordinate scheduling and timing of required administrative procedures with other construction activities and activities of other contractors to avoid conflicts and to ensure orderly progress of the Work. Such administrative activities include, but are not limited to, the following:
  - 1. Preparation of Contractor's Construction Schedule.
  - 2. Preparation of the Schedule of Values.
  - 3. Installation and removal of temporary facilities and controls.
  - 4. Delivery and processing of submittals.
  - 5. Progress meetings.
  - 6. Project closeout activities.

### 1.03 PROJECT MEETINGS

- A. General: Architect will schedule and conduct meetings and conferences at Project site, unless otherwise indicated.
  - 1. Attendees: Architect will inform participants and others involved, and individuals whose presence is required, of date and time of each meeting. Architect will notify Contractor and Owner of scheduled meeting dates and times.
  - 2. Agenda: Architect will prepare the meeting agenda and distribute the agenda to all invited attendees.
  - 3. Minutes: Architect will record significant discussions and agreements achieved. Architect will distribute the meeting minutes to everyone concerned.
  
- B. Progress Meetings: Conduct progress meetings at monthly intervals. Coordinate dates of meetings with preparation of payment requests.
  - 1. Attendees: In addition to representatives of Owner and Architect, each contractor, subcontractor, supplier, and other entity concerned with current progress or involved in planning, coordination, or performance of future activities shall be represented at these meetings. All participants at the conference shall be familiar with Project and authorized to conclude matters relating to the Work.
  - 2. Agenda: Review items of significance that could affect progress. Include topics for discussion as appropriate to status of Project.
    - a. Contractor's Construction Schedule: Review progress since the last meeting. Determine whether each activity is on time, ahead of schedule, or behind schedule, in relation to Contractor's Construction Schedule. Determine how construction behind schedule will be expedited; secure commitments from parties involved to do so. Discuss whether schedule revisions are required to ensure that current and subsequent activities will be completed within the Contract Time.
    - b. Review present and future needs of each entity present, including the following:
      - 1) Interface requirements.
      - 2) Sequence of operations.
      - 3) Status of submittals.
      - 4) Deliveries.
      - 5) Off-site fabrication.
      - 6) Access.
      - 7) Site utilization.
      - 8) Temporary facilities and controls.
      - 9) Work hours.
      - 10) Hazards and risks.
      - 11) Progress cleaning.
      - 12) Quality and work standards.
      - 13) Change Orders.
      - 14) Documentation of information for payment requests.

3. Reporting: Distribute minutes of the meeting to each party present and to parties who should have been present. Include a brief summary, in narrative form, of progress since the previous meeting and report.
  - a. Schedule Updating: Revise Contractor's Construction Schedule after each progress meeting where revisions to the schedule have been made or recognized. Issue revised schedule concurrently with the report of each meeting.

**PART 2 - PRODUCTS (Not Used)**

**PART 3 - EXECUTION (Not Used)**

END OF SECTION 01 30 00



# REQUEST FOR INFORMATION

RFI NO.: \_\_\_\_\_

DATE: \_\_\_\_\_

PROJECT: \_\_\_\_\_

TO: \_\_\_\_\_

ATTN: \_\_\_\_\_

FROM: \_\_\_\_\_

PHONE: \_\_\_\_\_

REASON FOR REQUEST	ACTION REQUIRED	PROBABLE EFFECT
<input type="checkbox"/> Insufficient Information	<input type="checkbox"/> Clarification	<input type="checkbox"/> Increase Cost
<input type="checkbox"/> Engineering Conflict	<input type="checkbox"/> Direction	<input type="checkbox"/> Decrease Cost
<input type="checkbox"/> Alternate Proposal	<input type="checkbox"/> Approval	<input type="checkbox"/> Unknown Cost
		<input type="checkbox"/> Increase Time
		<input type="checkbox"/> Decrease Time
		<input type="checkbox"/> Unknown Time

REFERENCE:	DRAWING NO.:	DETAIL NO.:	SPEC SECTION:
------------	--------------	-------------	---------------

INFORMATION NEEDED:

RECOMMENDATION:

RESPONSE:	COPIES TO:
-----------	------------

\_\_\_\_\_  
Authorized Signature

\_\_\_\_\_  
Company

\_\_\_\_\_  
Date





## **SECTION 01 32 00 - CONSTRUCTION PROGRESS DOCUMENTATION**

### **PART 1 - GENERAL**

#### **1.01 SUMMARY**

- A. This Section includes administrative and procedural requirements for documenting the progress of construction during performance of the Work, including the following:
  1. Contractor's Construction Schedule.
  2. Field condition reports.

#### **1.02 SUBMITTALS**

- A. Field Condition Reports: Submit three copies at time of discovery of differing conditions.

#### **1.03 COORDINATION**

- A. Coordinate preparation and processing of schedules and reports with performance of construction activities and with scheduling and reporting of separate contractors.

### **PART 2 - PRODUCTS**

#### **2.01 CONTRACTOR'S CONSTRUCTION SCHEDULE**

- A. Use HUD-5372 Construction Progress Schedule (Section 00 62 83).
- B. Contract Modifications: For each proposed contract modification and concurrent with its submission, provide justification to demonstrate the effect of the proposed change on the overall project schedule.

#### **2.02 REPORTS**

- A. Field Condition Reports: Immediately on discovery of a difference between field conditions and the contract documents, prepare a detailed report. Submit report with a Request for Information on attached form at the end of this Section. Include a detailed description of the differing conditions, together with recommendations for changing the Contract Documents.

### **PART 3 - EXECUTION**

#### **3.01 CONTRACTOR'S CONSTRUCTION SCHEDULE**

- A. Contractor's Construction Schedule Updating: At monthly intervals, update schedule to reflect actual construction progress and activities.
  1. Revise schedule immediately after each meeting or other activity where revisions have been recognized or made. Issue updated schedule concurrently with the report of each such meeting.

2. Include a report with updated schedule that indicates every change.
  3. As the Work progresses, indicate Actual Completion percentage for each activity.
- B. Distribution: Distribute copies of approved schedule to Architect, Owner, separate contractors, testing and inspecting agencies, and other parties identified by Contractor with a need-to-know schedule responsibility.
1. When revisions are made, distribute updated schedules to the same parties. Delete parties from distribution when they have completed their assigned portion of the Work and are no longer involved in performance of construction activities.

END OF SECTION 01 32 00

## SECTION 01 33 00 - SUBMITTAL PROCEDURES

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes administrative and procedural requirements for submitting Shop Drawings, Product Data, Samples, and other miscellaneous submittals.
- B. See Division 01 Section "Construction Progress Documentation" for submitting schedules and reports, including Contractor's Construction Schedule and the Submittals Schedule
- C. See Division 01 Section "Quality Requirements" for submitting test and inspection reports, for Delegated-Design submittals and for erecting mockups.
- D. See Division 01 Section "Closeout Procedures" for submitting warranties Project Record Documents and operation and maintenance manuals.

#### 1.02 DEFINITIONS

- A. Action Submittals: Written and graphic information that requires Architect's responsive action.
- B. Informational Submittals: Written information that does not require Architect's approval. Submittals may be rejected for not complying with requirements.

#### 1.03 SUBMITTAL PROCEDURES

- A. Timing: All submittals must be received within 30 days of the Notice to Proceed.
- B. Processing Time: Allow enough time for submittal review, including time for resubmittals, as follows. Time for review shall commence on Architect's receipt of submittal.
  - 1. Initial Review: Allow 14 days for initial review of each submittal. Allow additional time if processing must be delayed to permit coordination with subsequent submittals.
  - 2. If intermediate submittal is necessary, process it in same manner as initial submittal.
  - 3. Allow 14 days for processing each resubmittal.
  - 4. No extension of the Contract Time will be authorized because of failure to transmit submittals enough in advance of the Work to permit processing.
  - 5. No submittals will be released until all submittals have been received, reviewed, and accepted with no exceptions taken.
- C. Identification: Place a permanent label or title block on each submittal for identification.
  - 1. Indicate name of firm or entity that prepared each submittal on label or title block.

2. Provide a space approximately 4 by 5 inches on label or beside title block to record Contractor's review and approval markings and action taken by Architect.
  3. Include the following information on label for processing and recording action taken:
    - a. Project name.
    - b. Date.
    - c. Name and address of Contractor.
    - d. Name and address of subcontractor.
    - e. Name and address of supplier.
    - f. Name of manufacturer.
    - g. Number and title of appropriate Specification Section.
    - h. Drawing number and detail references, as appropriate.
    - i. Other necessary identification.
- D. Deviations: Highlight, encircle, or otherwise identify deviations from the Contract Documents on submittals.
- E. Transmittal: Package each submittal individually and appropriately for transmittal and handling. Transmit each submittal using a transmittal form. Architect will discard submittals received from sources other than Contractor.
1. Include Contractor's certification stating that information submitted complies with requirements of the Contract Documents.
  2. Transmittal Form: Use sample form at end of Section.
- F. PDF Submittals: Prepare submittals as PDF package, incorporating complete information into each PDF file. Name PDF file with submittal number.
- G. Distribution: Furnish copies of final submittals to manufacturers, subcontractors, suppliers, fabricators, installers, authorities having jurisdiction, and others as necessary for performance of construction activities. Show distribution on transmittal forms.
- H. Use for Construction: Use only final submittals with mark indicating action taken by Architect in connection with construction.

## **PART 2 - PRODUCTS**

### **2.01 ACTION SUBMITTALS**

- A. General: Prepare and submit Action Submittals required by individual Specification Sections.
1. Number of Copies: Submit seven copies of each submittal, unless otherwise indicated. Architect will return three copies. Mark up and retain one returned copy as a Project Record Document.
- B. Product Data: Collect information into a single submittal for each element of construction and type of product or equipment.
1. If information must be specially prepared for submittal because standard printed data are not suitable for use, submit as Shop Drawings, not as Product Data.
  2. Mark each copy of each submittal to show which products and options are applicable.

3. Include the following information, as applicable:
  - a. Manufacturer's written recommendations.
  - b. Manufacturer's product specifications.
  - c. Manufacturer's installation instructions.
  - d. Manufacturer's catalog cuts.
  - e. Wiring diagrams showing factory-installed wiring.
  - f. Printed performance curves.
  - g. Operational range diagrams.
  - h. Compliance with recognized trade association standards.
  - i. Compliance with recognized testing agency standards.
  
- C. Shop Drawings: Prepare Project-specific information, drawn accurately to scale. Do not base Shop Drawings on reproductions of the Contract Documents or standard printed data.
  1. Preparation: Include the following information, as applicable:
    - a. Dimensions.
    - b. Identification of products.
    - c. Fabrication and installation drawings.
    - d. Roughing-in and setting diagrams.
    - e. Wiring diagrams showing field-installed wiring, including power, signal, and control wiring.
    - f. Shopwork manufacturing instructions.
    - g. Templates and patterns.
    - h. Schedules.
    - i. Notation of coordination requirements.
    - j. Notation of dimensions established by field measurement.
  2. Wiring Diagrams: Differentiate between manufacturer-installed and field-installed wiring.
  3. Sheet Size: Except for templates, patterns, and similar full-size drawings, submit Shop Drawings on sheets at least 8-1/2 by 11 inches but no larger than 24 by 36 inches.
  
- D. Samples: Prepare physical units of materials or products, including the following:
  1. Comply with requirements in Division 01 Section "Quality Requirements" for mockups.
  2. Samples for Initial Selection: Submit manufacturer's color charts consisting of units or sections of units showing the full range of colors, textures, and patterns available.
    - a. Submit one full set of available choices where color, pattern, texture, or similar characteristics are required to be selected from manufacturer's product line. Architect will return submittal with options selected.
  3. Preparation: Mount, display, or package Samples in manner specified to facilitate review of qualities indicated. Prepare Samples to match Architect's sample where so indicated. Attach label on unexposed side.
  4. Submit Samples for review of kind, color, pattern, and texture for a final check of these characteristics with other elements and for a comparison of these characteristics between final submittal and actual component as delivered and installed.
  5. Disposition: Maintain sets of approved Samples at Project site, available for quality-control comparisons throughout the course of construction activity.

Sample sets may be used to determine final acceptance of construction associated with each set.

- E. Delegate-Design Submittal: Comply with requirements in Division 01 Section "Quality Requirements".
- F. Application for Payment: Comply with requirements in Division 01 Section "Payment Procedures."
- G. Schedule of Values: Comply with requirements in Division 01 Section "Payment Procedures."
- H. Subcontract List: Prepare a written summary identifying individuals or firms proposed for each portion of the Work, including those who are to furnish products or equipment fabricated to a special design.

## 2.02 INFORMATIONAL SUBMITTALS

- A. General: Prepare and submit Informational Submittals required by other Specification Sections.
  - 1. Number of Copies: Submit seven copies of each submittal, unless otherwise indicated. Architect will not return copies.
  - 2. Certificates and Certifications: Provide a notarized statement that includes signature of entity responsible for preparing certification. Certificates and certifications shall be signed by an officer or other individual authorized to sign documents on behalf of that entity.
  - 3. Test and Inspection Reports: Comply with requirements in Division 01 Section "Quality Requirements."
- B. Contractor's Construction Schedule: Comply with requirements in Division 01 Section "Construction Progress Documentation."
- C. Qualification Data: Prepare written information that demonstrates capabilities and experience of firm or person. Include lists of completed projects with project names and addresses, names and addresses of architects and owners, and other information specified.
- D. Product Certificates: Prepare written statements on manufacturer's letterhead certifying that product complies with requirements.
- E. Welding Certificates: Prepare written certification that welding procedures and personnel comply with requirements. Submit record of Welding Procedure Specification (WPS) and Procedure Qualification Record (PQR) on AWS forms. Include names of firms and personnel certified.
- F. Installer Certificates: Prepare written statements on manufacturer's letterhead certifying that Installer complies with requirements and, where required, is authorized for this specific Project.

- G. **Manufacturer Certificates:** Prepare written statements on manufacturer's letterhead certifying that manufacturer complies with requirements. Include evidence of manufacturing experience where required.
- H. **Material Certificates:** Prepare written statements on manufacturer's letterhead certifying that material complies with requirements.
- I. **Material Test Reports:** Prepare reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting test results of material for compliance with requirements.
- J. **Compatibility Test Reports:** Prepare reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting results of compatibility tests performed before installation of product. Include written recommendations for primers and substrate preparation needed for adhesion.
- K. **Field Test Reports:** Prepare reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting results of field tests performed either during installation of product or after product is installed in its final location, for compliance with requirements.
- L. **Product Test Reports:** Prepare written reports indicating current product produced by manufacturer complies with requirements. Base reports on evaluation of tests performed by manufacturer and witnessed by a qualified testing agency, or on comprehensive tests performed by a qualified testing agency.
- M. **Research/Evaluation Reports:** Prepare written evidence, from a model code organization acceptable to authorities having jurisdiction, that product complies with building code in effect for Project.
- N. **Maintenance Data:** Prepare written and graphic instructions and procedures for operation and normal maintenance of products and equipment. Comply with requirements in Division 01 Section "Closeout Procedures."
- O. **Design Data:** Prepare written and graphic information, including, but not limited to, performance and design criteria, list of applicable codes and regulations, and calculations. Include list of assumptions and other performance and design criteria and a summary of loads. Include load diagrams if applicable. Provide name and version of software, if any, used for calculations. Include page numbers.
- P. **Manufacturer's Instructions:** Prepare written or published information that documents manufacturer's recommendations, guidelines, and procedures for installing or operating a product or equipment. Include name of product and name, address, and telephone number of manufacturer.
- Q. **Manufacturer's Field Reports:** Prepare written information documenting factory-authorized service representative's tests and inspections.

### **PART 3 - EXECUTION**

#### **3.01 CONTRACTOR'S REVIEW**

- A. Review each submittal and check for compliance with the Contract Documents. Note corrections and field dimensions.

#### **3.02 ARCHITECT'S ACTION**

- A. General: Architect will not review submittals that do not bear Contractor's approval stamp and will return them without action.
- B. Action Submittals: Architect will review each submittal, make marks to indicate corrections or modifications required, and return it.
  - 1. PDF Submittals: Architect will indicate, via markup on each submittal, the appropriate action.
- C. Informational Submittals: Architect will review each submittal and will not return it, or will reject and return it if it does not comply with requirements. Architect will forward each submittal to appropriate party.
- D. Submittals not required by the Contract Documents will not be reviewed and may be discarded.

END OF SECTION 01 33 00



**Submittal Transmittal No.** \_\_\_\_\_

Total Contract Days Elapsed: \_\_\_\_\_

Date of Transmittal: \_\_\_\_\_

Total Contract Days: \_\_\_\_\_

Spec Section No: \_\_\_\_\_ - \_\_\_\_\_ (submittal number; start with 01)

Description: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Subcontractor's Name: \_\_\_\_\_

Contractor's Name: \_\_\_\_\_

Address: \_\_\_\_\_

Address: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

Supplier's Name: \_\_\_\_\_

Manufacturer's Name: \_\_\_\_\_

Address: \_\_\_\_\_

Address: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

**CAUTHEN & ASSOCIATES, LLC**

**CONTRACTOR'S REVIEW**

- NO EXCEPTIONS TAKEN
- MAKE CORRECTIONS NOTED
- REVISE AND RESUBMIT
- REJECTED SEE REMARKS

Reviewed By: \_\_\_\_\_ Date: \_\_\_\_\_

Reviewed By: \_\_\_\_\_ Date: \_\_\_\_\_

Checking is only for general conformance with the design concept of the project and general compliance with the information given in the contract documents. Any action shown is subject to the requirements of the plans and specifications. Contractor is responsible for dimensions which shall be confirmed and correlated at the job site: fabrication processes and techniques of construction; coordination of his work with that of all other trades; and the satisfactory performance of his work.

**A/E COMMENTS:**

Copies shall bear the A/E and Contractor's stamp

**HOUSING AUTHORITY**

Reviewed By: \_\_\_\_\_ Date: \_\_\_\_\_



## SECTION 01 40 00 - QUALITY REQUIREMENTS

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes administrative and procedural requirements for quality assurance and quality control.
- B. Testing and inspecting services are required to verify compliance with requirements specified or indicated. These services do not relieve Contractor of responsibility for compliance with the Contract Document requirements.
  - 1. Specified tests, inspections, and related actions do not limit Contractor's quality-control procedures that facilitate compliance with the Contract Document requirements.
  - 2. Requirements for Contractor to provide quality-control services required by Architect, Owner, or authorities having jurisdiction are not limited by provisions of this Section.
- C. See Divisions 02 through 33 Sections for specific test and inspection requirements.

#### 1.02 DEFINITIONS

- A. Quality-Assurance Services: Activities, actions, and procedures performed before and during execution of the Work to guard against defects and deficiencies and ensure that proposed construction complies with requirements.
- B. Quality-Control Services: Tests, inspections, procedures, and related actions during and after execution of the Work to evaluate that completed construction complies with requirements. Services do not include contract enforcement activities performed by Architect.
- C. Mockups: Full-size, physical example assemblies to illustrate finishes and materials. Mockups are used to verify selections made under Sample submittals, to demonstrate aesthetic effects and, where indicated, qualities of materials and execution, and to review construction, coordination, testing, or operation; they are not Samples. Mockups establish the standard by which the Work will be judged.
- D. Testing Agency: An entity engaged to perform specific tests, inspections, or both. Testing laboratory shall mean the same as testing agency.

#### 1.03 DELEGATED DESIGN

- A. Performance and Design Criteria: Where professional design services or certifications by a design professional are specifically required of Contractor by the Contract Documents, provide products and systems complying with specific performance and design criteria indicated.
  - 1. If criteria indicated are not sufficient to perform services or certification required, submit a written request for additional information to Architect.

#### 1.04 SUBMITTALS

- A. Qualification Data: For testing agencies specified in "Quality Assurance" Article to demonstrate their capabilities and experience. Include proof of qualifications in the form of a recent report on the inspection of the testing agency by a recognized authority.
- B. Delegated-Design Submittal: In addition to Shop Drawings, Product Data, and other required submittals, submit a statement, signed and sealed by the responsible design professional, for each product and system specifically assigned to Contractor to be designed or certified by a design professional, indicating that the products and systems are in compliance with performance and design criteria indicated. Include list of codes, loads, and other factors used in performing these services.
- C. Reports: Prepare and submit certified written reports that include the following:
  - 1. Date of issue.
  - 2. Project title and number.
  - 3. Name, address, and telephone number of testing agency.
  - 4. Dates and locations of samples and tests or inspections.
  - 5. Names of individuals making tests and inspections.
  - 6. Description of the Work and test and inspection method.
  - 7. Identification of product and Specification Section.
  - 8. Complete test or inspection data.
  - 9. Test and inspection results and an interpretation of test results.
  - 10. Ambient conditions at time of sample taking and testing and inspecting.
  - 11. Comments or professional opinion on whether tested or inspected Work complies with the Contract Document requirements.
  - 12. Name and signature of laboratory inspector.
  - 13. Recommendations on retesting and reinspecting.
- D. Permits, Licenses, and Certificates: For Owner's records, submit copies of permits, licenses, certifications, inspection reports, releases, jurisdictional settlements, notices, receipts for fee payments, judgments, correspondence, records, and similar documents, established for compliance with standards and regulations bearing on performance of the Work.

#### 1.05 QUALITY ASSURANCE

- A. Fabricator Qualifications: A firm experienced in producing products similar to those indicated for this Project and with a record of successful in-service performance, as well as sufficient production capacity to produce required units.
- B. Factory-Authorized Service Representative Qualifications: An authorized representative of manufacturer who is trained and approved by manufacturer to inspect installation of manufacturer's products that are similar in material, design, and extent to those indicated for this Project.

- C. **Installer Qualifications:** A firm or individual experienced in installing, erecting, or assembling work similar in material, design, and extent to that indicated for this Project, whose work has resulted in construction with a record of successful in-service performance.
- D. **Manufacturer Qualifications:** A firm experienced in manufacturing products or systems similar to those indicated for this Project and with a record of successful in-service performance.
- E. **Professional Engineer Qualifications:** A professional engineer who is legally qualified to practice in jurisdiction where Project is located and who is experienced in providing engineering services of the kind indicated. Engineering services are defined as those performed for installations of the system, assembly, or product that are similar to those indicated for this Project in material, design, and extent.
- F. **Specialists:** Certain sections of the Specifications require that specific construction activities shall be performed by entities who are recognized experts in those operations. Specialists shall satisfy qualification requirements indicated and shall be engaged for the activities indicated.
  - 1. Requirement for specialists shall not supersede building codes and similar regulations governing the Work, nor interfere with local trade-union jurisdictional settlements and similar conventions.
- G. **Testing Agency Qualifications:** An agency with the experience and capability to conduct testing and inspecting indicated, as documented by ASTM E 548, and that specializes in types of tests and inspections to be performed.
- H. **Mockups:** Before installing portions of the Work requiring mockups, build mockups for each form of construction and finish required to comply with the following requirements, using materials indicated for the completed Work:
  - 1. Build mockups in location and of size indicated or, if not indicated, as directed by Architect.
  - 2. Notify Architect seven days in advance of dates and times when mockups will be constructed.
  - 3. Demonstrate the proposed range of aesthetic effects and workmanship.
  - 4. Obtain Architect's approval of mockups before starting work, fabrication, or construction.
  - 5. Maintain mockups during construction in an undisturbed condition as a standard for judging the completed Work.
  - 6. Demolish and remove mockups when directed, unless otherwise indicated.

#### 1.06 QUALITY CONTROL

- A. **Owner Responsibilities:** Where quality-control services are indicated as Owner's responsibility, Owner will engage a qualified testing agency to perform these services.
  - 1. Owner will furnish Contractor with names, addresses, and telephone numbers of testing agencies engaged and a description of the types of testing and inspecting they are engaged to perform.

2. Costs for retesting and re-inspecting construction that replaces or is necessitated by work that failed to comply with the Contract Documents will be charged to Contractor, and the Contract Sum will be adjusted by Change Order.
- B. Contractor Responsibilities: Unless otherwise indicated, provide quality-control services specified and required by authorities having jurisdiction.
1. Where services are indicated as Contractor's responsibility, engage a qualified testing agency to perform these quality-control services.
    - a. Contractor shall not employ the same entity engaged by Owner, unless agreed to in writing by Owner.
  2. Notify testing agencies at least 24 hours in advance of time when Work that requires testing or inspecting will be performed.
  3. Where quality-control services are indicated as Contractor's responsibility, submit a certified written report, in duplicate, of each quality-control service.
  4. Testing and inspecting requested by Contractor and not required by the Contract Documents are Contractor's responsibility.
  5. Submit additional copies of each written report directly to authorities having jurisdiction, when they so direct.
- C. Special Tests and Inspections: Owner will engage a testing agency to conduct special tests and inspections required by authorities having jurisdiction as the responsibility of Owner.
1. Testing agency will notify Architect and Contractor promptly of irregularities and deficiencies observed in the Work during performance of its services.
  2. Testing agency will submit a certified written report of each test, inspection, and similar quality-control service to Architect with copy to Contractor and to authorities having jurisdiction.
  3. Testing agency will submit a final report of special tests and inspections at Substantial Completion, which includes a list of unresolved deficiencies.
  4. Testing agency will interpret tests and inspections and state in each report whether tested and inspected work complies with or deviates from the Contract Documents.
  5. Testing agency will retest and reinspect corrected work.
- D. Manufacturer's Field Services: Where indicated, engage a factory-authorized service representative to inspect field-assembled components and equipment installation, including service connections. Report results in writing.
- E. Retesting/Reinspecting: Regardless of whether original tests or inspections were Contractor's responsibility, provide quality-control services, including retesting and reinspecting, for construction that revised or replaced Work that failed to comply with requirements established by the Contract Documents.
- F. Testing Agency Responsibilities: Cooperate with Architect and Contractor in performance of duties. Provide qualified personnel to perform required tests and inspections.
1. Notify Architect and Contractor promptly of irregularities or deficiencies observed in the Work during performance of its services.

2. Interpret tests and inspections and state in each report whether tested and inspected work complies with or deviates from requirements.
  3. Submit a certified written report, in duplicate, of each test, inspection, and similar quality-control service through Contractor.
  4. Do not release, revoke, alter, or increase requirements of the Contract Documents or approve or accept any portion of the Work.
  5. Do not perform any duties of Contractor.
- G. Associated Services: Cooperate with agencies performing required tests, inspections, and similar quality-control services, and provide reasonable auxiliary services as requested. Notify agency sufficiently in advance of operations to permit assignment of personnel. Provide the following:
1. Access to the Work.
  2. Incidental labor and facilities necessary to facilitate tests and inspections.
  3. Adequate quantities of representative samples of materials that require testing and inspecting. Assist agency in obtaining samples.
  4. Facilities for storage and field-curing of test samples.
  5. Delivery of samples to testing agencies.
  6. Preliminary design mix proposed for use for material mixes that require control by testing agency.
  7. Security and protection for samples and for testing and inspecting equipment at Project site.
- H. Coordination: Coordinate sequence of activities to accommodate required quality-assurance and quality-control services with a minimum of delay and to avoid necessity of removing and replacing construction to accommodate testing and inspecting.
1. Schedule times for tests, inspections, obtaining samples, and similar activities.

## **PART 2 - PRODUCTS (Not Used)**

## **PART 3 - EXECUTION**

### **3.01 REPAIR AND PROTECTION**

- A. General: On completion of testing, inspecting, sample taking, and similar services, repair damaged construction and restore substrates and finishes.
1. Provide materials and comply with installation requirements specified in other Sections of these Specifications. Restore patched areas and extend restoration into adjoining areas in a manner that eliminates evidence of patching.
  2. Comply with the Contract Document requirements for Division 1 Section "Cutting and Patching."
- B. Protect construction exposed by or for quality-control service activities.
- C. Repair and protection are Contractor's responsibility, regardless of the assignment of responsibility for quality-control services.

END OF SECTION 01 40 00





## SECTION 01 45 00 - QUALITY CONTROL PROCEDURES

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. Section Includes:
  - 1. General quality control activities.
  - 2. Procedures for the following:
    - a. Preparation and maintenance of schedule of quality control activities.
    - b. Testing and evaluation of test results.
    - c. Inspections.
    - d. Construction and evaluation of mock-ups.
  - 3. Procedures for quality control activities performed by:
    - a. Public authorities having jurisdiction.
    - b. Architect.
    - c. Independent testing agencies.
    - d. Contractor.
  - 4. Procedures for submittal of quality control documentation.
- B. Quality control activities required are specified in other sections.
- C. See General Conditions for additional requirements for testing, inspections, and approvals.
- D. Related Sections:
  - 1. Submittal procedures: Elsewhere in Division 1.

#### 1.02 CONTRACT CONDITIONS

- A. Independent testing agencies, whether employed by the owner or the contractor, may not change the requirements of the contract documents and may not approve any portion of the work.
- B. Employment of testing agencies, by the contractor or the owner, shall not relieve the contractor of his obligation to perform the work in accordance with the contract documents.

#### 1.03 DEFINITIONS

- A. Certificate: A written statement that a portion of the work as accomplished or a particular product conforms to the requirements of the contract documents.

#### 1.04 SUBMITTALS

- A. Schedule of Quality Control Activities:
  - 1. Submit within same time period as required for progress schedule.
  - 2. Submit within same time period as required for contractor's construction schedule.
  - 3. Distribute to:
    - a. The owner.
    - b. The architect.
    - c. Each entity performing work for which quality control activities are specified.

- B. Reports: Provide certified copies of reports.
  - 1. Unless otherwise indicated, submit for review by the architect.
  - 2. Submit reports not later than the date of application for payment for the work to which the quality control activity relates.
  - 3. Reports shall be prepared by the entity performing the quality control activity.
  - 4. Submit copies directly to governing authorities when so directed.
  - 5. When the contractor employs an independent testing agency, submit copies directly to the architect.
  - 6. Include the following information in all types of reports:
    - a. Date of report.
    - b. Project name (and number, if applicable).
    - c. Description of the quality control activity.
    - d. Name, address, and telephone number of entity performing activity.
    - e. Date quality control activity was performed.
    - f. Specification section(s) involved.
    - g. Basis for evaluation (test method, etc.).
    - h. Results or conclusions, including evaluations and interpretations.
    - i. Title, name, and signature of person performing activity.
  - 7. Include the following information in all test reports:
    - a. Locations from which samples were taken, if any.
    - b. Ambient conditions at time of activity.
    - c. Recommendations for retesting, if any.
- C. Certificates: Submit for review, unless otherwise indicated.
  - 1. Certificates shall be signed by the product manufacturer, unless otherwise specified or not applicable.
  - 2. Include the following information:
    - a. Date of certificate.
    - b. Project name (and number, if applicable).
    - c. Description of the product or system certified.
    - d. Specification section(s) involved.
    - e. When actual materials to be used are to be certified, include lot identification markings, destination or shipment, and quantity in shipment.
    - f. Title, name, and signature of person authorized to make certification.

#### 1.05 QUALITY ASSURANCE

- A. Qualifications of Testing and Inspection Personnel:
  - 1. As indicated in individual sections.
  - 2. Independent Testing Agency Qualifications: When employed by the contractor:
    - a. A firm independent from the contractor's organization.
    - b. Having experience in the testing specified and having the capability to conduct satisfactorily the testing specified without delaying the progress of the work, as shown by information supplied as required by ASTM E 699.
    - c. Approved by the architect.
    - d. Authorized to conduct business in the state in which the project is located.

- B. Testing Equipment: Calibrated at reasonable intervals with devices of an accuracy traceable to either the National Bureau of Standards (NBS) standards or to accepted values of natural physical constants.

#### 1.06 COORDINATION WITH OTHER ENTITIES

- A. Cooperate with other entities performing quality control activities.
- B. Provide samples of materials and design criteria as indicated and when requested.
- C. Provide other assistance, equipment, tools, and storage facilities as specified.
- D. If desired, make arrangements with those entities and pay for additional similar or related testing or inspection required for the contractor's use or convenience.

#### 1.07 SEQUENCING AND SCHEDULING

- A. Prepare a schedule of quality control activities required.
  - 1. Provide the following information for each activity:
    - a. Specification section number.
    - b. Description of the activity.
    - c. Identification of test or inspection methods.
    - d. Enumeration of results required.
    - e. Number of tests required.
    - f. Number and type of samples to be taken, if any.
    - g. Starting time of activity.
    - h. The date that the work will be ready for the owner's testing agency access.
    - i. Elapsed time required for activity.
    - j. Entity responsible.
    - k. Special requirements for activity.
- B. Coordinate quality control activities to avoid delay and to make it unnecessary to uncover work for testing or inspection.

### **PART 2 - PRODUCTS (NOT USED)**

### **PART 3 - EXECUTION**

#### 3.01 GENERAL

- A. Provide work of the specified quality; where quality level is not indicated, provide work of quality customary in similar types of work.
  - 1. Where codes, laws, or regulations require work of higher quality or performance, provide work complying with those codes, laws, and regulations.
  - 2. Where two or more quality provisions of the contract documents conflict, comply with the most stringent requirement; where requirements are different but apparently equal, and where it is uncertain which requirement is most stringent, obtain clarification from the architect before proceeding.
  - 3. Actual quality may exceed the specified quality; verify that such differences are acceptable to the owner (other criteria may make excessive quality undesirable).

- B. Control products, suppliers, manufacturers, site conditions, installers, and workmanship in such a manner as to produce work of the specified quality.
- C. Comply with manufacturers' instructions and recommendations.
  - 1. Keep a record of instructions and recommendations which supplement or conflict with the manufacturer's written instructions.
  - 2. When manufacturers' instructions and recommendations conflict with the contract documents, obtain clarification from the architect before proceeding.
- D. Use installers who are capable of producing work of the specified quality.
- E. Perform all quality control activities specified unless indicated to be performed by other entities.

### 3.02 MOCK-UPS

- A. Mock-ups required are specified in other sections.
- B. Construct mock-ups as specified for actual work, with all components required for a complete installation.
- C. Erect specified mock-ups in locations indicated.
  - 1. Unless otherwise indicated, mock-ups may be located in the position of the finished work, and approved mock-ups may be incorporated into the finished work.
  - 2. Where mock-ups are to be removed, clear area after removal of mock-up and return to original or specified condition.
- D. Where mock-ups are to be approved by the architect, obtain approval of the architect prior to proceeding with installation.

### 3.03 TESTING

- A. Perform tests specified.
- B. When results of tests are unsatisfactory, make whatever changes or repairs are necessary and retest.
- C. Submit written report of each original test and of each retest.

### 3.04 INSPECTING

- A. Perform inspections specified.
- B. When inspections reveal unsatisfactory work, make whatever changes or repairs are necessary and reinspect.
- C. Submit written report of each original inspection and each reinspection.

3.05 PROTECTION AND REPAIR

- A. When work is uncovered during quality control activities, provide protection from damage.
- B. Correct work damaged by quality control activities; where repair is indicated as an unacceptable method, replace the work.

END OF SECTION 01 45 00



## SECTION 01 50 00 - TEMPORARY FACILITIES AND CONTROLS

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes requirements for temporary facilities and controls, including temporary utilities, support facilities, and security and protection facilities.
- B. See Division 01 Section "Execution" for progress cleaning requirements.

#### 1.02 DEFINITIONS

- A. Permanent Enclosure: As determined by Architect, permanent or temporary roofing is complete, insulated, and weathertight; exterior walls are insulated and weathertight; and all openings are closed with permanent construction or substantial temporary closures.

#### 1.03 USE CHARGES

- A. General: Cost or use charges for temporary facilities are not chargeable to Owner or Architect and shall be included in the Contract Sum. Allow other entities to use temporary services and facilities without cost, including, but not limited to, Architect, testing and inspecting agencies and personnel of authorities having jurisdiction.
- B. Water Service: Use water from Owner's existing water system without metering. Owner will pay for water used up to the maximum paid for any 30 day period within the last 12 months. The Contractor will pay for all water used in excess of this amount as indicated by the Owner's master meter readings. Provide connections and extensions of services as required for construction operations.
- C. Electric Power Service: Pay electric-power-service use charges for electricity used by all entities for construction operations.

#### 1.04 QUALITY ASSURANCE

- A. Electric Service: Comply with NECA, NEMA, and UL standards and regulations for temporary electric service. Install service to comply with NFPA 70.
- B. Tests and Inspections: Arrange for authorities having jurisdiction to test and inspect each temporary utility before use. Obtain required certifications and permits.

#### 1.05 PROJECT CONDITIONS

- A. Conditions of Use: The following conditions apply to use of temporary services and facilities by all parties engaged in the Work:
  - 1. Keep temporary services and facilities clean and neat.
  - 2. Relocate temporary services and facilities as required by progress of the Work.

## **PART 2 - PRODUCTS**

### **2.01 MATERIALS**

- A. General: Provide new materials. Undamaged, previously used materials in serviceable condition may be used if approved by Architect. Provide materials suitable for use intended.
- B. Water: Potable.

### **2.02 EQUIPMENT**

- A. Fire Extinguishers: Hand carried, portable, UL rated. Provide class and extinguishing agent as indicated or a combination of extinguishers of NFPA-recommended classes for exposures.
  - 1. Comply with NFPA 10 and NFPA 241 for classification, extinguishing agent, and size required by location and class of fire exposure.
- B. Electrical Outlets: Properly configured, NEMA-polarized outlets to prevent insertion of 110- to 120-V plugs into higher-voltage outlets; equipped with ground-fault circuit interrupters, reset button, and pilot light.
- C. Power Distribution System Circuits: Where permitted and overhead and exposed for surveillance, wiring circuits, not exceeding 125-V ac, 20-A rating, and lighting circuits may be nonmetallic sheathed cable.

## **PART 3 - EXECUTION**

### **3.01 INSTALLATION, GENERAL**

- A. Locate facilities where they will serve Project adequately and result in minimum interference with performance of the Work. Obtain approval from the Owner prior to locating storage trailers. Relocate and modify facilities as required.
- B. Provide each facility ready for use when needed to avoid delay. Maintain and modify as required. Do not remove until facilities are no longer needed or are replaced by authorized use of completed permanent facilities.

### **3.02 TEMPORARY UTILITY INSTALLATION**

- A. General: Engage appropriate local utility company to install temporary service or connect to existing service. Where utility company provides only part of the service, provide the remainder with matching, compatible materials and equipment. Comply with utility company recommendations.
  - 1. Arrange with utility company, Owner, and existing users for time when service can be interrupted, if necessary, to make connections for temporary services.
  - 2. Provide adequate capacity at each stage of construction. Before temporary utility is available, provide trucked-in services.
  - 3. Obtain easements to bring temporary utilities to Project site where Owner's easements cannot be used for that purpose.



- B. Sanitary Facilities: Provide temporary toilets and wash facilities. Comply with regulations and health codes for type, number, location, operation, and maintenance of fixtures and facilities.
  - 1. Disposable Supplies: Provide toilet tissue and similar disposable materials for each facility. Maintain adequate supply. Provide covered waste containers for disposal of used material.
  - 2. Toilets: Install self-contained toilet units. Shield toilets to ensure privacy.
  
- C. Electric Power Service: Provide weatherproof, grounded electric power service and distribution system of sufficient size, capacity, and power characteristics during construction period. Include meters, transformers, overload-protected disconnecting means, automatic ground-fault interrupters, and main distribution switchgear.
  - 1. Install power distribution wiring overhead and rise vertically where least exposed to damage.
  - 2. Use of Owner's existing electric power service will be permitted, as long as equipment is maintained in a condition acceptable to Owner.
  
- D. Electric Distribution: Provide receptacle outlets adequate for connection of power tools and equipment.
  - 1. Provide waterproof connectors to connect separate lengths of electrical power cords if single lengths will not reach areas where construction activities are in progress. Do not exceed safe length-voltage ratio.

### 3.03 SUPPORT FACILITIES INSTALLATION

- A. General: Comply with the following:
  - 1. Locate storage sheds, sanitary facilities, and other temporary construction and support facilities for easy access.
  - 2. Maintain support facilities until near Substantial Completion. Remove before Substantial Completion. Personnel remaining after Substantial Completion will be permitted to use permanent facilities, under conditions acceptable to Owner.
  
- B. Waste Disposal Facilities: Provide waste-collection containers in sizes adequate to handle waste from construction operations. Containerize and clearly label hazardous, dangerous, or unsanitary waste materials separately from other waste. Comply with Division 01 Section "Execution" for progress cleaning requirements.
  - 1. If required by authorities having jurisdiction, provide separate containers, clearly labeled, for each type of waste material to be deposited.
  - 2. Develop a waste management plan for Work performed on Project. Indicate types of waste materials Project will produce and estimate quantities of each type. Provide detailed information for on-site waste storage and separation of recyclable materials. Provide information on destination of each type of waste material and means to be used to dispose of all waste materials.
  
- C. Storage and Fabrication Containers: Provide containers sized, furnished, and equipped to accommodate materials and equipment involved, including temporary utility services.

### 3.04 SECURITY AND PROTECTION FACILITIES INSTALLATION

- A. Environmental Protection: Provide protection, operate temporary facilities, and conduct construction in ways and by methods that comply with environmental regulations and that minimize possible air, waterway, and subsoil contamination or pollution or other undesirable effects. Avoid using tools and equipment that produce harmful noise. Restrict use of noisemaking tools and equipment to hours that will minimize complaints from persons or firms near Project site.
- B. Security Enclosure and Lockup: Install substantial temporary enclosure around partially completed areas of construction. Provide lockable entrances to prevent unauthorized entrance, vandalism, theft, and similar violations of security.
- C. Barricades, Warning Signs, and Lights: Comply with standards and code requirements for erecting structurally adequate barricades. Paint with appropriate colors, graphics, and warning signs to inform personnel and public of possible hazard. Where appropriate and needed, provide lighting, including flashing red or amber lights.
- D. Temporary Fire Protection: Until fire-protection needs are supplied by permanent facilities, install and maintain temporary fire-protection facilities of types needed to protect against reasonably predictable and controllable fire losses. Comply with NFPA 241.
  - 1. Provide fire extinguishers, installed on walls on mounting brackets, visible and accessible from space being served, with sign mounted above.
    - a. Locate fire extinguishers where convenient and effective for their intended purpose; provide not less than one extinguisher on each floor at or near each usable stairwell.
  - 2. Store combustible materials in containers in fire-safe locations.
  - 3. Maintain unobstructed access to fire extinguishers, fire hydrants, temporary fire-protection facilities, stairways, and other access routes for firefighting. Prohibit smoking in hazardous fire-exposure areas.
  - 4. Supervise welding operations, combustion-type temporary heating units, and similar sources of fire ignition.
  - 5. Permanent Fire Protection: At earliest feasible date in each area of Project, complete installation of permanent fire-protection facility, including connected services, and place into operation and use. Instruct key personnel on use of facilities.
  - 6. Develop and supervise an overall fire-prevention and first-aid fire-protection program for personnel at Project site. Review needs with local fire department and establish procedures to be followed. Instruct personnel in methods and procedures. Post warnings and information.

### 3.05 OPERATION, TERMINATION, AND REMOVAL

- A. Supervision: Enforce strict discipline in use of temporary facilities. To minimize waste and abuse, limit availability of temporary facilities to essential and intended uses.
- B. Maintenance: Maintain facilities in good operating condition until removal. Protect from damage caused by freezing temperatures and similar elements.

1. Maintain operation of temporary enclosures, heating, cooling, humidity control, ventilation, and similar facilities on a 24-hour basis where required to achieve indicated results and to avoid possibility of damage.
- C. Termination and Removal: Remove each temporary facility when need for its service has ended, when it has been replaced by authorized use of a permanent facility, or no later than Substantial Completion. Complete or, if necessary, restore permanent construction that may have been delayed because of interference with temporary facility. Repair damaged Work, clean exposed surfaces, and replace construction that cannot be satisfactorily repaired.
1. Materials and facilities that constitute temporary facilities are the property of Contractor. Owner reserves right to take possession of Project identification signs.
  2. At Substantial Completion, clean and renovate permanent facilities used during construction period. Comply with final cleaning requirements in Division 01 Section "Closeout Procedures."

END OF SECTION 01 50 00



## SECTION 01 60 00 - PRODUCT REQUIREMENTS

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes administrative and procedural requirements for selecting products for use in Project; product delivery, storage, and handling; manufacturers' standard warranties on products; special warranties; product substitutions; and comparable products.
- B. See Division 01 Section "Closeout Procedures" for submitting warranties for contract closeout.
- C. See Divisions 02 through 33 Sections for specific requirements for warranties on products and installations specified to be warranted.

#### 1.02 DEFINITIONS

- A. Products: Items purchased for incorporating into the Work, whether purchased for Project or taken from previously purchased stock. The term "product" includes the terms "material," "equipment," "system," and terms of similar intent.
  - 1. Named Products: Items identified by manufacturer's product name, including make or model number or other designation, shown or listed in manufacturer's published product literature that is current as of date of the Contract Documents.
  - 2. New Products: Items that have not previously been incorporated into another project or facility, except that products consisting of recycled-content materials are allowed, unless explicitly stated otherwise. Products salvaged or recycled from other projects are not considered new products.
  - 3. Comparable Product: Product that is demonstrated and approved through submittal process, or where indicated as a product substitution, to have the indicated qualities related to type, function, dimension, in-service performance, physical properties, appearance, and other characteristics that equal or exceed those of specified product.
- B. Substitutions: Changes in products, materials, equipment, and methods of construction from those required by the Contract Documents and proposed by Contractor.
- C. Basis-of-Design Product Specification: Where a specific manufacturer's product is named and accompanied by the words "basis of design," including make or model number or other designation, to establish the significant qualities related to type, function, dimension, in-service performance, physical properties, appearance, and other characteristics for purposes of evaluating comparable products of other named manufacturers.
- D. Manufacturer's Warranty: Preprinted written warranty published by individual manufacturer for a particular product and specifically endorsed by manufacturer to Owner.

- E. Special Warranty: Written warranty required by or incorporated into the Contract Documents, either to extend time limit provided by manufacturer's warranty or to provide more rights for Owner.

### 1.03 SUBMITTALS

- A. Substitution Requests: Submit three copies of each request for consideration. Identify product or fabrication or installation method to be replaced. Include Specification Section number and title and Drawing numbers and titles.
  - 1. All requests for substitutions shall be accompanied with a check in the amount of \$500.00 made payable to Cauthen & Associates, LLC.
  - 2. Substitution Request Form: Use the form included at the end of this section.
  - 3. Documentation: Show compliance with requirements for substitutions and the following, as applicable:
    - a. Statement indicating why specified material or product cannot be provided.
    - b. Coordination information, including a list of changes or modifications needed to other parts of the Work that will be necessary to accommodate proposed substitution.
    - c. Detailed comparison of significant qualities of proposed substitution with those of the Work specified. Significant qualities may include attributes such as performance, weight, size, durability, visual effect, and specific features and requirements indicated.
    - d. Product Data, including drawings and descriptions of products and fabrication and installation procedures.
    - e. Samples, where applicable or requested.
    - f. Material test reports from a qualified testing agency indicating and interpreting test results for compliance with requirements indicated.
    - g. Research/evaluation reports evidencing compliance with building code in effect for Project, from a model code organization acceptable to authorities having jurisdiction.
    - h. Cost information, including a proposal of change, if any, in the Contract Sum.
    - i. Contractor's certification that proposed substitution complies with requirements in the Contract Documents and is appropriate for applications indicated.
    - j. Contractor's waiver of rights to additional payment or time that may subsequently become necessary because of failure of proposed substitution to produce indicated results.
  - 4. Architect's Action: If necessary, Architect will request additional information or documentation for evaluation within one week of receipt of a request for substitution. Architect will notify Contractor of acceptance or rejection of proposed substitution within 10 days of receipt of request, or 5 days of receipt of additional information or documentation, whichever is later.
    - a. Form of Acceptance: Change Order.
    - b. Use product specified if Architect cannot make a decision on use of a proposed substitution within time allocated.
- B. Basis-of-Design Product Specification Submittal: Comply with requirements in Division 01 Section "Submittal Procedures." Show compliance with requirements.

#### 1.04 QUALITY ASSURANCE

- A. Compatibility of Options: If Contractor is given option of selecting between two or more products for use on Project, product selected shall be compatible with products previously selected, even if previously selected products were also options.

#### 1.05 PRODUCT DELIVERY, STORAGE, AND HANDLING

- A. Deliver, store, and handle products using means and methods that will prevent damage, deterioration, and loss, including theft. Comply with manufacturer's written instructions.
  - 1. Schedule delivery to minimize long-term storage at Project site and to prevent overcrowding of construction spaces.
  - 2. Coordinate delivery with installation time to ensure minimum holding time for items that are flammable, hazardous, easily damaged, or sensitive to deterioration, theft, and other losses.
  - 3. Deliver products to Project site in an undamaged condition in manufacturer's original sealed container or other packaging system, complete with labels and instructions for handling, storing, unpacking, protecting, and installing.
  - 4. Inspect products on delivery to ensure compliance with the Contract Documents and to ensure that products are undamaged and properly protected.
  - 5. Store products to allow for inspection and measurement of quantity or counting of units.
  - 6. Store materials in a manner that will not endanger Project structure.
  - 7. Store products that are subject to damage by the elements, under cover in a weathertight enclosure above ground, with ventilation adequate to prevent condensation.
  - 8. Comply with product manufacturer's written instructions for temperature, humidity, ventilation, and weather-protection requirements for storage.
  - 9. Protect stored products from damage.

#### 1.06 PRODUCT WARRANTIES

- A. Warranties specified in other Sections shall be in addition to, and run concurrent with, other warranties required by the Contract Documents. Manufacturer's disclaimers and limitations on product warranties do not relieve Contractor of obligations under requirements of the Contract Documents.
- B. Special Warranties: Prepare a written document that contains appropriate terms and identification, ready for execution. Submit a draft for approval before final execution.
  - 1. Manufacturer's Standard Form: Modified to include Project-specific information and properly executed.
  - 2. Refer to Divisions 02 through 33 Sections for specific content requirements and particular requirements for submitting special warranties.
- C. Submittal Time: Comply with requirements in Division 01 Section "Closeout Procedures."

## **PART 2 - PRODUCTS**

### **2.01 PRODUCT OPTIONS**

- A. General Product Requirements: Provide products that comply with the Contract Documents, that are undamaged and, unless otherwise indicated, that are new at time of installation.
1. Provide products complete with accessories, trim, finish, fasteners, and other items needed for a complete installation and indicated use and effect.
  2. Standard Products: If available, and unless custom products or nonstandard options are specified, provide standard products of types that have been produced and used successfully in similar situations on other projects.
  3. Owner reserves the right to limit selection to products with warranties not in conflict with requirements of the Contract Documents.
  4. Where products are accompanied by the term "as selected," Architect will make selection.
  5. Descriptive, performance, and reference standard requirements in the Specifications establish "salient characteristics" of products.
- B. Product Selection Procedures: Procedures for product selection include the following:
1. Available Products: Where Specification paragraphs or subparagraphs titled "Available Products" introduce a list of names of both products and manufacturers, provide one of the products listed or another product that complies with requirements. Comply with provisions in "Comparable Products" Article to obtain approval for use of an unnamed product.
  2. Available Manufacturers: Where Specification paragraphs or subparagraphs titled "Available Manufacturers" introduce a list of manufacturers' names, provide a product by one of the manufacturers listed or another manufacturer that complies with requirements. Comply with provisions in "Comparable Products" Article to obtain approval for use of an unnamed product.
  3. Basis-of-Design Products: Where Specification paragraphs or subparagraphs titled "Basis-of-Design Product" are included and also introduce or refer to a list of manufacturers' names, provide either the specified product or a comparable product by one of the other named manufacturers. Drawings and Specifications indicate sizes, profiles, dimensions, and other characteristics that are based on the product named. Comply with provisions in "Comparable Products" Article to obtain approval for use of an unnamed product.
    - a. Substitutions may be considered, unless otherwise indicated.
  4. Visual Matching Specification: Where Specifications require matching an established Sample, select a product (and manufacturer) that complies with requirements and matches Architect's sample. Architect's decision will be final on whether a proposed product matches satisfactorily.
    - a. If no product available within specified category matches satisfactorily and complies with other specified requirements, comply with provisions of the Contract Documents on "substitutions" for selection of a matching product.



5. Visual Selection Specification: Where Specifications include the phrase "as selected from manufacturer's colors, patterns, and textures" or a similar phrase, select a product (and manufacturer) that complies with other specified requirements.
  - a. Full Range: Where Specifications include the phrase "full range of colors, patterns, textures" or similar phrase, Architect will select color, pattern, or texture from manufacturer's product line that includes both standard and premium items.

## 2.02 PRODUCT SUBSTITUTIONS

- A. Timing: Architect will consider requests for substitution if received within 15 days after the Notice to Proceed. Requests received after that time may be considered or rejected at discretion of Architect.
- B. Conditions: Architect will consider Contractor's request for substitution when the following conditions are satisfied. If the following conditions are not satisfied, Architect will return requests without action, except to record noncompliance with these requirements:
  1. Requested substitution offers Owner a substantial advantage in cost, time, energy conservation, or other considerations, after deducting additional responsibilities Owner must assume. Owner's additional responsibilities may include compensation to Architect for redesign and evaluation services, increased cost of other construction by Owner, and similar considerations.
  2. Requested substitution does not require extensive revisions to the Contract Documents.
  3. Requested substitution is consistent with the Contract Documents and will produce indicated results.
  4. Substitution request is fully documented and properly submitted.
  5. Requested substitution will not adversely affect Contractor's Construction Schedule.
  6. Requested substitution has received necessary approvals of authorities having jurisdiction.
  7. Requested substitution is compatible with other portions of the Work.
  8. Requested substitution has been coordinated with other portions of the Work.
  9. Requested substitution provides specified warranty.

## 2.03 COMPARABLE PRODUCTS

- A. Where products or manufacturers are specified by name, submit the following, in addition to other required submittals, to obtain approval of an unnamed product:
  1. Evidence that the proposed product does not require extensive revisions to the Contract Documents that it is consistent with the Contract Documents and will produce the indicated results, and that it is compatible with other portions of the Work.

2. Detailed comparison of significant qualities of proposed product with those named in the Specifications. Significant qualities include attributes such as performance, weight, size, durability, visual effect, and specific features and requirements indicated.
3. Evidence that proposed product provides specified warranty.
4. Samples, if requested.

**PART 3 - EXECUTION (Not Used)**

**END OF SECTION 01 60 00**

**SUBSTITUTION REQUEST FORM**

Project: \_\_\_\_\_

To: \_\_\_\_\_ Attn: \_\_\_\_\_

\_\_\_\_\_  
Specified Item: Proposed Substitute

- 
1. The following are attached (Mark all that apply):  
 Complete Description     Catalog     Check  
 Laboratory Tests     Spec Data
  2. The substitution will have the following effects on dimensions, gauges, weights, etc.:
  3. This substitution will have the following effects on wiring, piping, ductwork, etc.:
  4. This substitution will have the following effects on other trades:
  5. This substitution will have the following effect on construction schedules:
  6. The proposed substitute(s) differs from the specified product(s) in quality and performance as follows:
  7. Manufacturer warranties and guarantees for the substitute(s) and the specified product(s) are (check one):  
 The Same     Different (if different, explain below)
  8. Information on the availability of maintenance services and replacement materials for proposed substitute(s) is provided on an attached sheet if applicable. This attachment is:  
 Attached     Not Applicable
  9. Names, addresses, and phone numbers of fabricators and supplier for proposed substitute(s) are provided on an attached sheet if applicable. This attachment is:  
 Applicable     Not Applicable

10. If the proposed substitution is accepted, it will result in:  
 No Cost Impact       A Cost Increase Of \_\_\_\_\_  
 A Cost Decrease Of \_\_\_\_\_  
(If change in cost is indicated, submit an itemization of costs associated with the substitution)
11. License fees or royalties are pending on the proposed substitute.  
 No       Yes (If yes, explain below)
12. The undersigned or the firm represented shall pay for additional studies, investigations, submittals, redesign and analysis by the Designer necessitated by this substitution request.

---

Substitutions must be requested in accordance with applicable contract requirements. After bidding, substitutions are to be submitted only by Contractor. Substitute products should not be ordered or installed without written acceptance.

---

Submitted by: \_\_\_\_\_ Date: \_\_\_\_\_  
Sign here: \_\_\_\_\_  
Name: \_\_\_\_\_ Telephone: \_\_\_\_\_  
Type or Print: \_\_\_\_\_  
For: \_\_\_\_\_  
Name of Firm: \_\_\_\_\_  
Address: \_\_\_\_\_  
Street Address: \_\_\_\_\_  
and Mailing Address \_\_\_\_\_  
if Different: \_\_\_\_\_  
City, State, \_\_\_\_\_  
and Zip Code: \_\_\_\_\_

Designer's Review Comments

- Accepted       Rejected  
 Accepted as Noted       Rejected (received too late)  
 Rejected (submittal incomplete)

Additional Comments:

---

---

---

---

---

For the Designer:

Date:

Signature here: \_\_\_\_\_

## SECTION 01 73 00 - EXECUTION

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes general procedural requirements governing execution of the Work including, but not limited to, the following:
  1. Construction layout.
  2. Field engineering and surveying.
  3. General installation of products.
  4. Progress cleaning.
  5. Starting and adjusting.
  6. Protection of installed construction.
  7. Correction of the Work.

#### 1.02 SUBMITTALS

- A. Certificates: Submit certificate signed by land surveyor or professional engineer certifying that location and elevation of improvements comply with requirements.
- B. Landfill Receipts: Submit copy of receipts issued by a landfill facility, licensed to accept hazardous materials, for hazardous waste disposal. Submit copy of receipts issued by a landfill facility for all demolition material.

#### 1.03 PROJECT CONDITIONS

- A. Some areas of adjacent buildings will be occupied during the period in which the work will be conducted; avoid interference with use of those areas and interruption of access to them.
- B. Take precautions to prevent fires and to facilitate fire-fighting operations.
  1. Keep temporary and permanent fire fighting facilities readily accessible; keep fire fighting routes open.
  2. Do not allow smoking in areas where highly combustible or explosive materials are present.
  3. Carefully supervise the operation of potential fire sources, including heating units.
  4. Conduct welding operations in manner to prevent fire; comply with local regulations.
- C. Take precautions to prevent accidents due to physical hazards:
  1. Provide barricades, warning lights, or signs as required to inform personnel and the public of the hazard being protected against.
- D. Take care to prevent pollution of air, water, and soil.
  1. Comply with environmental protection regulations.
  2. Limit effluent and rainwater runoff into waterways as required by regulations.
  3. Do not dump contaminants in areas that will result in contamination of waterways.
- E. Minimize discharge of effluent and rainwater runoff into sewers.

1. Control sediment discharge into sewers; filter out construction debris, soil, and contaminants.
  2. Comply with regulations and orders of public utilities regarding use of sewers.
  3. Where disposal of effluent or rainwater by means of sewers is not lawful or is not possible, provide alternative methods of disposal.
- F. Control windblown dust; prevent erosion to site and nuisance to neighbors.
- G. Prevent flooding of excavations, below grade construction, and adjacent properties due to rainwater runoff.
- H. Protect existing property indicated to remain.
- I. Do not use tools or equipment which produce harmful levels of noise.
1. Minimize the use of noise-making tools and equipment during hours that adjacent buildings are occupied.
- J. Keep the site and adjacent public ways free of hazardous and unsanitary conditions and public nuisances.
- K. Control rodents and other pests; prevent infestation of adjacent sites and buildings due to pests on this site.
- L. Keep public streets free of debris due to this work.
- M. Provide adequate traffic control by means of signs, signals, and flagmen, as necessary.
- N. Provide temporary means of draining roofs where required.
- O. Conduct construction operations so that none of the work and none of the existing construction is subjected to damaging operations or influences which are in excess of those to be expected during normal occupancy conditions.
- P. Conduct construction operations so that waste of power, water, and fuel is avoided.
- Q. Provide temporary supports as required to prevent movement and structural failure.
- R. Install products only during environmental conditions which will ensure the best possible results.

## **PART 2 - PRODUCTS (Not Used)**

## **PART 3 - EXECUTION**

### **3.01 EXAMINATION**

- A. Existing Conditions: The existence and location of site improvements, utilities, and other construction indicated as existing are not guaranteed. Before beginning work, investigate and verify the existence and location of mechanical and electrical systems and other construction affecting the Work.
  - 1. Before construction, verify the location and points of connection of utility services.
  
- B. Existing Utilities: The existence and location of underground and other utilities and construction indicated as existing are not guaranteed. Before beginning sitework, investigate and verify the existence and location of underground utilities and other construction affecting the Work.
  - 1. Furnish location data for work related to Project that must be performed by public utilities serving Project site.
  
- C. Acceptance of Conditions: Examine substrates, areas, and conditions, with Installer or Applicator present where indicated, for compliance with requirements for installation tolerances and other conditions affecting performance. Record observations.
  - 1. Verify compatibility with and suitability of substrates, including compatibility with existing finishes or primers.
  - 2. Examine roughing-in for mechanical and electrical systems to verify actual locations of connections before equipment and fixture installation.
  - 3. Proceed with installation only after unsatisfactory conditions have been corrected. Proceeding with the Work indicates acceptance of surfaces and conditions.

### **3.02 PREPARATION**

- A. Existing Utility Information: Furnish information to local utility and Owner that is necessary to adjust, move, or relocate existing utility structures, utility poles, lines, services, or other utility appurtenances located in or affected by construction. Coordinate with authorities having jurisdiction.
  
- B. Existing Utility Interruptions: Do not interrupt utilities serving facilities occupied by Owner or others unless permitted under the following conditions and then only after arranging to provide temporary utility services according to requirements indicated:
  - 1. Notify Owner not less than two days in advance of proposed utility interruptions.
  - 2. Do not proceed with utility interruptions without Owner's written permission.
  
- C. Field Measurements: Take field measurements as required to fit the Work properly. Recheck measurements before installing each product. Where portions of the Work are indicated to fit to other construction, verify dimensions of other construction by field measurements before fabrication. Coordinate fabrication schedule with construction progress to avoid delaying the Work.
  
- D. Space Requirements: Verify space requirements and dimensions of items shown diagrammatically on Drawings.

- E. Review of Contract Documents and Field Conditions: Immediately on discovery of the need for clarification of the Contract Documents, submit a request for information to Architect. Include a detailed description of problem encountered, together with recommendations for changing the Contract Documents. Submit requests on Request for Information form found at the end of Section 01 30 00.

### 3.03 CONSTRUCTION LAYOUT

- A. Verification: Before proceeding to lay out the Work, verify layout information shown on Drawings, in relation to the property survey and existing benchmarks. If discrepancies are discovered, notify Architect promptly.
- B. General: Engage a land surveyor or professional engineer to lay out the Work using accepted surveying practices.
  - 1. Establish benchmarks and control points to set lines and levels of construction and elsewhere as needed to locate each element of Project.
  - 2. Establish dimensions within tolerances indicated. Do not scale Drawings to obtain required dimensions.
  - 3. Inform installers of lines and levels to which they must comply.
  - 4. Check the location, level and plumb, of every major element as the Work progresses.
  - 5. Notify Architect when deviations from required lines and levels exceed allowable tolerances.
- C. Site Improvements: Locate and lay out site improvements, including pavements, grading, fill and topsoil placement, utility slopes, and invert elevations.
- D. Building Lines and Levels: Locate and lay out control lines and levels for structures, building foundations, column grids, and floor levels, including those required for mechanical and electrical work. Transfer survey markings and elevations for use with control lines and levels. Level foundations and piers from two or more locations.
- E. Record Log: Maintain a log of layout control work. Record deviations from required lines and levels. Include beginning and ending dates and times of surveys, weather conditions, name and duty of each survey party member, and types of instruments and tapes used. Make the log available for reference by Architect.

### 3.04 FIELD ENGINEERING

- A. Reference Points: Locate existing permanent benchmarks, control points, and similar reference points before beginning the Work. Preserve and protect permanent benchmarks and control points during construction operations.
- B. Benchmarks: Establish and maintain a minimum of two permanent benchmarks on Project site, referenced to data established by survey control points. Comply with authorities having jurisdiction for type and size of benchmark.
  - 1. Record benchmark locations, with horizontal and vertical data, on Project Record Documents.



### 3.05 INSTALLATION

- A. General: Locate the Work and components of the Work accurately, in correct alignment and elevation, as indicated.
  - 1. Make vertical work plumb and make horizontal work level.
  - 2. Where space is limited, install components to maximize space available for maintenance and ease of removal for replacement.
  - 3. Conceal pipes, ducts, and wiring in finished areas, unless otherwise indicated.
- B. Comply with manufacturer's written instructions and recommendations for installing products in applications indicated.
- C. Install products at the time and under conditions that will ensure the best possible results. Maintain conditions required for product performance until Substantial Completion.
- D. Conduct construction operations so no part of the Work is subjected to damaging operations or loading in excess of that expected during normal conditions of occupancy.
- E. Existing Construction:
  - 1. Perform work in existing construction in same manner as for new construction unless otherwise specified.
  - 2. Where a new surface exposed to view is an extension of any existing surface, align both surfaces without a change of plane and make a neat transition between finishes.
    - a. If a change of plane is necessary due to the configuration of the existing surface, terminate the existing surface and its finish along a straight line at a natural line of division.
    - b. Where portions of existing work are removed, patch remaining work with neat transitions between remaining surfaces without evidence of cutting.
    - c. Where neat transitions between remaining surfaces are not possible due to configuration of existing surfaces, obtain instructions from the A/E.
  - 3. Where existing construction is removed, remove existing utility services located within or upon the existing construction.
    - a. Cap cut ends of abandoned piping, conduit, and duct in such a manner that they are concealed in finish work.
- F. Anchors and Fasteners: Provide anchors and fasteners as required to anchor each component securely in place, accurately located and aligned with other portions of the Work.
  - 1. Mounting Heights: Where mounting heights are not indicated, mount components at heights directed by Architect.
  - 2. Allow for building movement, including thermal expansion and contraction.
- G. Joints: Make joints of uniform width. Where joint locations in exposed work are not indicated, arrange joints for the best visual effect. Fit exposed connections together to form hairline joints.
- H. Hazardous Materials: Use products, cleaners, and installation materials that are not considered hazardous.

### 3.06 PROGRESS CLEANING

- A. General: In addition to requirements outlined in the General and Supplementary Conditions, the following conditions shall apply. Coordinate progress cleaning for joint-use areas where more than one installer has worked. Enforce requirements strictly. Dispose of materials lawfully.
  - 1. Comply with requirements in NFPA 241 for removal of combustible waste materials and debris.
  - 2. Containerize hazardous and unsanitary waste materials separately from other waste. Mark containers appropriately and dispose of legally, according to regulations.
- B. Site: Maintain Project site free of waste materials and debris.
- C. Work Areas: Clean areas where work is in progress to the level of cleanliness necessary for proper execution of the Work.
  - 1. Remove liquid spills promptly.
  - 2. Where dust would impair proper execution of the Work, broom-clean or vacuum the entire work area, as appropriate.
- D. Installed Work: Keep installed work clean. Clean installed surfaces according to written instructions of manufacturer or fabricator of product installed, using only cleaning materials specifically recommended. If specific cleaning materials are not recommended, use cleaning materials that are not hazardous to health or property and that will not damage exposed surfaces.
- E. Concealed Spaces: Remove debris from concealed spaces before enclosing the space.
- F. Waste Disposal: Burying or burning waste materials on-site will not be permitted. Washing waste materials down sewers or into waterways will not be permitted.
- G. During handling and installation, clean and protect construction in progress and adjoining materials already in place. Apply protective covering where required to ensure protection from damage or deterioration at Substantial Completion.
- H. Clean and provide maintenance on completed construction as frequently as necessary through the remainder of the construction period. Adjust and lubricate operable components to ensure operability without damaging effects.
- I. Limiting Exposures: Supervise construction operations to assure that no part of the construction, completed or in progress, is subject to harmful, dangerous, damaging, or otherwise deleterious exposure during the construction period.

### 3.07 STARTING AND ADJUSTING

- A. Start equipment and operating components to confirm proper operation. Remove malfunctioning units, replace with new units, and retest.
- B. Adjust operating components for proper operation without binding. Adjust equipment for proper operation.

- C. Test each piece of equipment to verify proper operation. Test and adjust controls and safeties. Replace damaged and malfunctioning controls and equipment.

### 3.08 PROTECTION OF INSTALLED CONSTRUCTION

- A. Provide final protection and maintain conditions that ensure installed Work is without damage or deterioration at time of Completion.
- B. Comply with manufacturer's written instructions for temperature and relative humidity.

### 3.09 CORRECTION OF THE WORK

- A. Repair or remove and replace defective construction. Restore damaged substrates and finishes. Comply with requirements in Division 1 Section "Cutting and Patching."
  - 1. Repairing includes replacing defective parts, refinishing damaged surfaces, touching up with matching materials, and properly adjusting operating equipment.
- B. Restore permanent facilities used during construction to their specified condition.
- C. Remove and replace damaged surfaces that are exposed to view if surfaces cannot be repaired without visible evidence of repair.
- D. Repair components that do not operate properly. Remove and replace operating components that cannot be repaired.
- E. Remove and replace chipped, scratched, and broken glass or reflective surfaces.

END OF SECTION 01 73 00



## SECTION 01 73 29 - CUTTING AND PATCHING

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes procedural requirements for cutting and patching.
- B. See Divisions 02 through 33 Sections for specific requirements and limitations applicable to cutting and patching individual parts of the Work.
- C. Requirements in this Section apply to mechanical and electrical installations. See Divisions 23 and 26 Sections for other requirements and limitations applicable to cutting and patching mechanical and electrical installations.

#### 1.02 QUALITY ASSURANCE

- A. Structural Elements: Do not cut and patch structural elements in a manner that could change their load-carrying capacity or load-deflection ratio.
- B. Operational Elements: Do not cut and patch operating elements and related components in a manner that results in reducing their capacity to perform as intended or that results in increased maintenance or decreased operational life or safety.
- C. Visual Requirements: Do not cut and patch construction in a manner that results in visual evidence of cutting and patching. Do not cut and patch construction exposed on the exterior or in occupied spaces in a manner that would, in Architect's opinion, reduce the building's aesthetic qualities. Remove and replace construction that has been cut and patched in a visually unsatisfactory manner.
  - 1. If possible, retain original Installer or fabricator to cut and patch exposed Work listed below. If it is impossible to engage original Installer or fabricator, engage another recognized, experienced, and specialized firm.

### PART 2 - PRODUCTS

#### 2.01 MATERIALS

- A. General: Comply with requirements specified in other Sections of these Specifications.
- B. Existing Materials: Use materials identical to existing materials. For exposed surfaces, use materials that visually match existing adjacent surfaces to the fullest extent possible.
  - 1. If identical materials are unavailable or cannot be used, use materials that, when installed, will match the visual and functional performance of existing materials.

## **PART 3 - EXECUTION**

### **3.01 EXAMINATION**

- A. Examine surfaces to be cut and patched and conditions under which cutting and patching are to be performed.
  - 1. Compatibility: Before patching, verify compatibility with and suitability of substrates, including compatibility with existing finishes or primers.
  - 2. Proceed with installation only after unsafe or unsatisfactory conditions have been corrected.

### **3.02 PREPARATION**

- A. Temporary Support: Provide temporary support of Work to be cut.
- B. Protection: Protect existing construction during cutting and patching to prevent damage. Provide protection from adverse weather conditions for portions of Project that might be exposed during cutting and patching operations.
- C. Adjoining Areas: Avoid interference with use of adjoining areas or interruption of free passage to adjoining areas.
- D. Existing Services: Where existing services are required to be removed, relocated, or abandoned, bypass such services before cutting to minimize interruption of services to occupied areas.

### **3.03 PERFORMANCE**

- A. General: Employ skilled workers to perform cutting and patching. Proceed with cutting and patching at the earliest feasible time, and complete without delay.
  - 1. Cut existing construction to provide for installation of other components or performance of other construction, and subsequently patch as required to restore surfaces to their original condition.
- B. Cutting: Cut existing construction by sawing, drilling, breaking, chipping, grinding, and similar operations, including excavation, using methods least likely to damage elements retained or adjoining construction. If possible, review proposed procedures with original Installer; comply with original Installer's written recommendations.
  - 1. In general, use hand or small power tools designed for sawing and grinding, not hammering and chopping. Cut holes and slots as small as possible, neatly to size required, and with minimum disturbance of adjacent surfaces. Temporarily cover openings when not in use.
  - 2. Existing Finished Surfaces: Cut or drill from the exposed or finished side into concealed surfaces.
  - 3. Concrete or Masonry: Cut using a cutting machine, such as an abrasive saw or a diamond-core drill.
  - 4. Excavating and Backfilling: Comply with requirements in applicable Division 2 Sections where required by cutting and patching operations.

5. Mechanical and Electrical Services: Cut off pipe or conduit in walls or partitions to be removed. Cap, valve, or plug and seal remaining portion of pipe or conduit to prevent entrance of moisture or other foreign matter after cutting.
  6. Proceed with patching after construction operations requiring cutting are complete.
- C. Patching: Patch construction by filling, repairing, refinishing, closing up, and similar operations following performance of other Work. Patch with durable seams that are as invisible as possible. Provide materials and comply with installation requirements specified in other Sections of these Specifications.
1. Inspection: Where feasible, test and inspect patched areas after completion to demonstrate integrity of installation.
  2. Exposed Finishes: Restore exposed finishes of patched areas and extend finish restoration into retained adjoining construction in a manner that will eliminate evidence of patching and refinishing.
  3. Floors and Walls: Where walls or partitions that are removed extend one finished area into another, patch and repair floor and wall surfaces in the new space. Provide an even surface of uniform finish, color, texture, and appearance. Remove existing floor and wall coverings and replace with new materials, if necessary, to achieve uniform color and appearance.
  4. Ceilings: Patch, repair, or rehang existing ceilings as necessary to provide an even-plane surface of uniform appearance, finish, color and texture.
  5. Exterior Building Enclosure: Patch components in a manner that restores enclosure to a weathertight condition.

END OF SECTION 01 73 29





## SECTION 01 77 19 - CLOSEOUT PROCEDURES

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes administrative and procedural requirements for contract closeout, including, but not limited to, the following:
  - 1. Inspection procedures.
  - 2. Project Record Documents.
  - 3. Operation and maintenance manuals.
  - 4. Warranties.
  - 5. Instruction of Owner's personnel.
  - 6. Final cleaning.
  - 7. Timing.
- B. See Division 01 Section "Payment Procedures" for requirements for Applications for Payment for Substantial and Final Completion.
- C. See Divisions 02 through 33 Sections for specific closeout and special cleaning requirements for products of those Sections.

#### 1.02 DEFINITIONS

- A. Substantial Completion: The point at which all work items have been completed but may require minor adjustments or corrections.
- B. Final Completion: All punch list items have been addressed and accepted by the Owner.

#### 1.03 SUBSTANTIAL COMPLETION

- A. Preliminary Procedures: Before requesting inspection for determining date of Substantial Completion, complete the following. List items below that are incomplete in request.
  - 1. Advise Owner of pending insurance changeover requirements.
  - 2. Submit specific warranties, workmanship bonds, maintenance service agreements, final certifications, and similar documents.
  - 3. Obtain and submit releases permitting Owner unrestricted use of the Work and access to services and utilities. Include occupancy permits, operating certificates, and similar releases.
  - 4. Prepare and submit Project Record Documents, operation and maintenance manuals, and similar final record information.
  - 5. Deliver tools, spare parts, extra materials, and similar items to location designated by Owner. Label with manufacturer's name and model number where applicable.
  - 6. Make final changeover of permanent locks and deliver keys to Owner. Advise Owner's personnel of changeover in security provisions.
  - 7. Complete startup testing of systems.
  - 8. Submit test/adjust/balance records.

9. Terminate and remove temporary facilities from Project site, along with mockups, construction tools, and similar elements.
  10. Advise Owner of changeover in heat and other utilities.
  11. Submit changeover information related to Owner's occupancy, use, operation, and maintenance.
  12. Complete final cleaning requirements, including touchup painting.
  13. Touch up and otherwise repair and restore marred exposed finishes to eliminate visual defects.
- B. Inspection: Submit a written request for inspection for Substantial Completion. On receipt of request, Architect will proceed with inspection. Architect will prepare the Certificate of Substantial Completion after inspection or will notify Contractor of additional items identified by the Architect that must be corrected before certificate will be issued.
1. If the Architect determines the Work is not Substantially Complete, the inspection will be terminated. The Contractor shall notify the Architect in writing when the work is ready for re-inspection and shall include a check for \$500.00 made payable to Cauthen & Associates, LLC to cover the cost for re-inspection.

#### 1.04 FINAL COMPLETION

- A. Preliminary Procedures: Before requesting final inspection for determining date of Final Completion, complete the following:
1. Submit a final Application for Payment according to Division 01 Section "Payment Procedures."
  2. Submit certified copy of Architect's Substantial Completion inspection list of items to be completed or corrected (punch list), endorsed and dated by Architect. The certified copy of the list shall state that each item has been completed or otherwise resolved for acceptance.
  3. Submit evidence of final, continuing insurance coverage complying with insurance requirements.
  4. Submit pest-control final inspection report and warranty.
  5. Instruct Owner's personnel in operation, adjustment, and maintenance of products, equipment, and systems.

#### 1.05 LIST OF UNACCEPTABLE ITEMS (PUNCH LIST)

- A. Preparation: Architect shall prepare a list of unacceptable items. Include name and identification of each space and area affected by construction operations for incomplete items and items needing correction including, if necessary, areas disturbed by Contractor that are outside the limits of construction. Punch list items shall be completed as soon as possible but in no case longer than 14 calendar days. Failure to complete punch list items in a timely manner may result in rejection of bids on future projects for poor performance in accordance with Section 4(2)(3) of the Instructions to Bidders for Contracts Form HUD-5369.

#### 1.06 PROJECT RECORD DOCUMENTS

- A. General: Do not use Project Record Documents for construction purposes. Protect Project Record Documents from deterioration and loss. Provide access to Project Record Documents for Architect's reference during normal working hours.

- B. Record Drawings: Maintain and submit one set of blue- or black-line white prints of Contract Drawings and Shop Drawings.
  - 1. Mark Record Prints to show the actual installation where installation varies from that shown originally. Require individual or entity who obtained record data, whether individual or entity is Installer, subcontractor, or similar entity, to prepare the marked-up Record Prints.
    - a. Give particular attention to information on concealed elements that cannot be readily identified and recorded later.
    - b. Record data as soon as possible after obtaining it. Record and check the markup before enclosing concealed installations.
  - 2. Mark record sets with erasable, red-colored pencil. Use other colors to distinguish between changes for different categories of the Work at the same location.
  - 3. Note Construction Change Directive numbers, Change Order numbers, alternate numbers, and similar identification where applicable.
  - 4. Identify and date each Record Drawing; include the designation "PROJECT RECORD DRAWING" in a prominent location. Organize into manageable sets; bind each set with durable paper cover sheets. Include identification on cover sheets.
- C. Miscellaneous Record Submittals: Assemble miscellaneous records required by other Specification Sections for miscellaneous record keeping and submittal in connection with actual performance of the Work. Bind or file miscellaneous records and identify each, ready for continued use and reference.

#### 1.07 OPERATION AND MAINTENANCE MANUALS

- A. Assemble three complete sets of operation and maintenance data indicating the operation and maintenance of each system, subsystem, and piece of equipment not part of a system. Include operation and maintenance data required in individual Specification Sections and as follows:
  - 1. Operation Data: Include emergency instructions and procedures, system and equipment descriptions, operating procedures, and sequence of operations.
  - 2. Maintenance Data: Include manufacturer's information, list of spare parts, maintenance procedures, maintenance and service schedules for preventive and routine maintenance, and copies of warranties and bonds.
- B. Organize operation and maintenance manuals into suitable sets of manageable size. Bind and index data in heavy-duty, three-ring, vinyl-covered, loose-leaf binders, in thickness necessary to accommodate contents, with pocket inside the covers to receive folded oversized sheets. Identify each binder on front and spine with the printed title "OPERATION AND MAINTENANCE MANUAL," Project name, and subject matter of contents. Each manual shall contain the following materials in the order listed:
  - 1. Title page.
  - 2. Table of contents.
  - 3. List of subcontractors and material suppliers.
  - 4. Manual contents.

- C. Title Page: Include the following information:
    - 1. Name and address of Project.
    - 2. Name and address of Owner.
    - 3. Name and contact information for Contractor.
    - 4. Name and contact information for Architect.
  - D. Table of Contents:
    - 1. List each item included in the manual.
  - E. List of Subcontractors and Material Suppliers: include the following information:
    - 1. Name and contact information for each Subcontractor.
    - 2. Name and contact information for each major material supplier.
  - F. Manual Contents: Organize into sets of manageable size.
- 1.08 WARRANTIES
- A. Submittal Time: Submit written warranties on request of Architect for designated portions of the Work where commencement of warranties other than date of Substantial Completion is indicated.
  - B. Organize warranty documents into an orderly sequence based on the table of contents of the Project Manual.
    - 1. Bind warranties and bonds in heavy-duty, 3-ring, vinyl-covered, loose-leaf binders, thickness as necessary to accommodate contents, and sized to receive 8-1/2-by-11-inch paper.
    - 2. Provide heavy paper dividers with plastic-covered tabs for each separate warranty. Mark tab to identify the product or installation. Provide a typed description of the product or installation, including the name of the product and the name, address, and telephone number of Installer.
    - 3. Identify each binder on the front and spine with the typed or printed title "WARRANTIES," Project name, and name of Contractor.
  - C. Provide additional copies of each warranty to include in operation and maintenance manuals.

## **PART 2 - PRODUCTS**

### 2.01 MATERIALS

- A. Cleaning Agents: Use cleaning materials and agents recommended by manufacturer or fabricator of the surface to be cleaned. Do not use cleaning agents that are potentially hazardous to health or property or that might damage finished surfaces.

## **PART 3 - EXECUTION**

### **3.01 DEMONSTRATION AND TRAINING**

- A. Instruction: Instruct Owner's personnel to adjust, operate, and maintain systems, subsystems, and equipment not part of a system.
  - 1. Provide instructors experienced in operation and maintenance procedures.
  - 2. Provide instruction at mutually agreed-on times. For equipment that requires seasonal operation, provide similar instruction at the start of each season.
  - 3. Schedule training with Owner with at least seven days' advance notice.
  - 4. Coordinate instructors, including providing notification of dates, times, length of instruction, and course content.

### **3.02 FINAL CLEANING**

- A. General: Provide final cleaning. Conduct cleaning and waste-removal operations to comply with local laws and ordinances and Federal and local environmental and antipollution regulations.
- B. Cleaning: Employ experienced workers or professional cleaners for final cleaning. Clean each surface or unit to condition expected in an average commercial building cleaning and maintenance program. Comply with manufacturer's written instructions.
  - 1. Complete the following cleaning operations before requesting inspection for certification of Substantial Completion for entire Project or for a portion of Project:
    - a. Clean Project site, yard, and grounds, in areas disturbed by construction activities, including landscape development areas, of rubbish, waste material, litter, and other foreign substances.
    - b. Sweep paved areas broom clean. Remove petrochemical spills, stains, and other foreign deposits.
    - c. Rake grounds that are neither planted nor paved to a smooth, even-textured surface.
    - d. Remove tools, construction equipment, machinery, and surplus material from Project site.
    - e. Clean exposed exterior and interior hard-surfaced finishes to a dirt-free condition, free of stains, films, and similar foreign substances. Avoid disturbing natural weathering of exterior surfaces. Restore reflective surfaces to their original condition.
    - f. Remove debris and surface dust from limited access spaces, including roofs, plenums, shafts, trenches, equipment vaults, manholes, attics, and similar spaces.
    - g. Sweep concrete floors broom-clean in unoccupied spaces.
    - h. Clean transparent materials, including mirrors and glass in doors and windows. Remove glazing compounds and other noticeable, vision-obscuring materials. Replace chipped or broken glass and other damaged transparent materials. Polish mirrors and glass, taking care not to scratch surfaces.

- i. Remove labels that are not permanent.
  - j. Touch up and otherwise repair and restore marred, exposed finishes and surfaces. Replace finishes and surfaces that cannot be satisfactorily repaired or restored or that already show evidence of repair or restoration.
    - 1) Do not paint over "UL" and similar labels, including mechanical and electrical nameplates.
  - k. Wipe surfaces of mechanical and electrical equipment, and similar equipment. Remove excess lubrication, paint and mortar droppings, and other foreign substances.
  - l. Replace parts subject to unusual operating conditions.
  - m. Clean plumbing fixtures to a sanitary condition, free of stains, including stains resulting from water exposure.
  - n. Replace disposable air filters and clean permanent air filters. Clean exposed surfaces of diffusers, registers, and grills.
  - o. Clean light fixtures, lamps, globes, and reflectors to function with full efficiency. Replace burned-out bulbs, and those noticeably dimmed by hours of use, and defective and noisy starters in fluorescent and mercury vapor fixtures to comply with requirements for new fixtures.
  - p. Leave Project clean and ready for occupancy.
- C. Pest Control: Engage an experienced, licensed exterminator to make a final inspection and rid Project of rodents, insects, and other pests. Prepare a report.
- D. Comply with safety standards for cleaning. Do not burn waste materials. Do not bury debris or excess materials on Owner's property. Do not discharge volatile, harmful, or dangerous materials into drainage systems. Remove waste materials from Project site and dispose of lawfully.

### 3.03 TIMING

- A. All closeout documents shall be submitted to A/E for review within 30 days of establishing the substantial completion date.
- B. Delays beyond the control of the Contractor must be documented and substantiated. Failure to do so may result in rejection of bids on future projects for poor performance in accordance with Section 4(2)(3) of the Instructions to Bidders for Contracts Form HUD-5369.

END OF SECTION 01 77 19

## SECTION 02 41 00 - SELECTIVE DEMOLITION

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes demolition and removal of the following:
  - 1. Selected portions of a building or structure.
  - 2. Selected site elements.
  - 3. Repair procedures for selective demolition operations.

#### 1.02 DEFINITIONS

- A. Remove: Detach items from existing construction and legally dispose of them off-site, unless indicated to be removed and salvaged or removed and reinstalled.
- B. Remove and Salvage: Detach items from existing construction and deliver them to Owner ready for reuse.
- C. Remove and Reinstall: Detach items from existing construction, prepare them for reuse, and reinstall them where indicated.
- D. Existing to Remain: Existing items of construction that are not to be removed and that are not otherwise indicated to be removed, removed and salvaged, or removed and reinstalled.

#### 1.03 MATERIALS OWNERSHIP

- A. Except for items or materials indicated to be reused, salvaged, reinstalled, or otherwise indicated to remain Owner's property, demolished materials shall become Contractor's property and shall be removed from Project site.

#### 1.04 QUALITY ASSURANCE

- A. Regulatory Requirements: Comply with governing EPA notification regulations before beginning selective demolition. Comply with hauling and disposal regulations of authorities having jurisdiction.
- B. Standards: Comply with ANSI A10.6 and NFPA 241.

#### 1.05 PROJECT CONDITIONS

- A. Owner will occupy portions of building immediately adjacent to selective demolition area. Conduct selective demolition so Owner's operations will not be disrupted. Provide not less than 72 hours' notice to Owner of activities that will affect Owner's operations.
- B. Maintain access to existing walkways, corridors, and other adjacent occupied or used facilities.
  - 1. Do not close or obstruct walkways, corridors, or other occupied or used facilities without written permission from authorities having jurisdiction.

- C. Owner assumes no responsibility for condition of areas to be selectively demolished.
  - 1. Conditions existing at time of inspection for bidding purpose will be maintained by Owner as far as practical.
- D. Hazardous Materials: It is not expected that hazardous materials will be encountered in the Work.
  - 1. If materials suspected of containing hazardous materials are encountered, do not disturb; immediately notify Architect and Owner.
- E. Storage or sale of removed items or materials on-site will not be permitted.
- F. Utility Service: Maintain existing utilities indicated to remain in service and protect them against damage during selective demolition operations.
  - 1. Maintain fire-protection facilities in service during selective demolition operations.

## **PART 2 - PRODUCTS**

### 2.01 REPAIR MATERIALS

- A. Use repair materials identical to existing materials.
  - 1. If identical materials are unavailable or cannot be used for exposed surfaces, use materials that visually match existing adjacent surfaces to the fullest extent possible.
  - 2. Use materials which installed performance equals or surpasses that of existing materials.

## **PART 3 - EXECUTION**

### 3.01 EXAMINATION

- A. Verify that utilities have been disconnected and capped.
- B. Survey existing conditions and correlate with requirements indicated to determine extent of selective demolition required.
- C. Inventory and record the condition of items to be removed and reinstalled and items to be removed and salvaged.
- D. When unanticipated mechanical, electrical, or structural elements that conflict with intended function or design are encountered, investigate and measure the nature and extent of conflict. Promptly submit a written report to Architect.
- E. Engage a professional engineer to survey condition of building to determine whether removing any element might result in structural deficiency or unplanned collapse of any portion of structure or adjacent structures during selective demolition operations.

### 3.02 UTILITY SERVICES

- A. Existing Utilities: Maintain services indicated to remain and protect them against damage during selective demolition operations.



- B. Do not interrupt existing utilities serving occupied or operating facilities unless authorized in writing by Owner and authorities having jurisdiction. Provide temporary services during interruptions to existing utilities, as acceptable to Owner and to authorities having jurisdiction.
  - 1. Provide at least 72 hours' notice to Owner if shutdown of service is required during changeover.
- C. Utility Requirements: Locate, identify, disconnect, and seal or cap off indicated utilities serving areas to be selectively demolished.
  - 1. Arrange to shut off indicated utilities with utility companies.
  - 2. If utility services are required to be removed, relocated, or abandoned, provide temporary utilities before proceeding with selective demolition that bypass area of selective demolition and that maintain continuity of service to other parts of building.
  - 3. Cut off pipe or conduit in walls or partitions to be removed. Cap, valve, or plug and seal remaining portion of pipe or conduit after bypassing.
- D. Utility Requirements: Refer to Division 22 and 26 Sections for shutting off, disconnecting, removing, and sealing or capping utilities. Do not start selective demolition work until utility disconnecting and sealing have been completed and verified in writing.

### 3.03 PREPARATION

- A. Site Access and Temporary Controls: Conduct selective demolition and debris-removal operations to ensure minimum interference with roads, streets, walks, walkways, and other adjacent occupied and used facilities.
  - 1. Do not close or obstruct streets, walks, walkways, or other adjacent occupied or used facilities without permission from Owner and authorities having jurisdiction. Provide alternate routes around closed or obstructed traffic ways if required by governing regulations.
  - 2. Erect temporary protection, such as walks, fences, railings, canopies, and covered passageways, where required by authorities having jurisdiction.
  - 3. Protect existing site improvements, appurtenances, and landscaping to remain.
- B. Temporary Facilities: Provide temporary barricades and other protection required to prevent injury to people and damage to adjacent buildings and facilities to remain.
- C. Temporary Enclosures: Provide temporary enclosures for protection of existing building and construction, in progress and completed, from exposure, foul weather, other construction operations, and similar activities. Provide temporary weathertight enclosure for building exterior.
- D. Temporary Partitions: Erect and maintain dustproof partitions and temporary enclosures to limit dust and dirt migration and to separate areas from fumes and noise.
- E. Temporary Shoring: Provide and maintain interior and exterior shoring, bracing, or structural support to preserve stability and prevent movement, settlement, or collapse of construction to remain, and to prevent unexpected or uncontrolled movement or collapse of construction being demolished.

### 3.04 POLLUTION CONTROLS

- A. Dust Control: Use water mist, temporary enclosures, and other suitable methods to limit spread of dust and dirt. Comply with governing environmental-protection regulations.
- B. Disposal: Remove and transport debris in a manner that will prevent spillage on adjacent surfaces and areas.
- C. Cleaning: Clean adjacent structures and improvements of dust, dirt, and debris caused by selective demolition operations. Return adjacent areas to condition existing before selective demolition operations began.

### 3.05 SELECTIVE DEMOLITION

- A. General: Demolish and remove existing construction only to the extent required by new construction and as indicated. Use methods required to complete the Work within limitations of governing regulations.
  - 1. Neatly cut openings and holes plumb, square, and true to dimensions required. Use cutting methods least likely to damage construction to remain or adjoining construction.
  - 2. Cut or drill from the exposed or finished side into concealed surfaces to avoid marring existing finished surfaces.
  - 3. Do not use cutting torches until work area is cleared of flammable materials. At concealed spaces, such as duct and pipe interiors, verify condition and contents of hidden space before starting flame-cutting operations. Maintain portable fire-suppression devices during flame-cutting operations.
  - 4. Locate selective demolition equipment and remove debris and materials so as not to impose excessive loads on supporting walls, floors, or framing.
- B. Existing Facilities: Comply with Owner's requirements for using and protecting walkways, building entries, and other building facilities during selective demolition operations.
- C. Removed and Salvaged Items:
  - 1. Clean salvaged items.
  - 2. Pack or crate items after cleaning. Identify contents of containers.
  - 3. Store items in a secure area until delivery to Owner.
  - 4. Transport items to Owner's storage area designated by Owner.
  - 5. Protect items from damage during transport and storage.
- D. Removed and Reinstalled Items:
  - 1. Clean and repair items to functional condition adequate for intended reuse. Paint equipment to match new equipment.
  - 2. Pack or crate items after cleaning and repairing. Identify contents of containers.
  - 3. Protect items from damage during transport and storage.
  - 4. Reinstall items in locations indicated. Comply with installation requirements for new materials and equipment. Provide connections, supports, and miscellaneous materials necessary to make item functional for use indicated.

- E. Existing Items to Remain: Protect construction indicated to remain against damage and soiling during selective demolition. When permitted by Architect, items may be removed to a suitable, protected storage location during selective demolition and cleaned and reinstalled in their original locations after selective demolition operations are complete.

### 3.06 PATCHING AND REPAIRS

- A. General: Promptly repair damage to adjacent construction caused by selective demolition operations.
- B. Patching: Comply with Division 01 Section "Cutting and Patching."
- C. Repairs: Where repairs to existing surfaces are required, patch to produce surfaces suitable for new materials.
  - 1. Completely fill holes and depressions in existing masonry walls that are to remain with an approved masonry patching material applied according to manufacturer's written recommendations.
- D. Finishes: Restore exposed finishes of patched areas and extend restoration into adjoining construction in a manner that eliminates evidence of patching and refinishing.
- E. Floors and Walls: Where walls or partitions that are demolished extend one finished area into another, patch and repair floor and wall surfaces in the new space. Provide an even surface of uniform finish color, texture, and appearance. Remove existing floor and wall coverings and replace with new materials, if necessary, to achieve uniform color and appearance.
- F. Ceilings: Patch, repair, or rehang existing ceilings as necessary to provide an even-plane surface of uniform appearance, finish, color and texture.

### 3.07 DISPOSAL OF DEMOLISHED MATERIALS

- A. General: Promptly dispose of demolished materials. Do not allow demolished materials to accumulate on-site.
- B. Burning: Do not burn demolished materials.
- C. Disposal: Transport demolished materials off Owner's property and legally dispose of them.

END OF SECTION 02 41 00



**Photographs of Existing Damage**

Total Contract Days Elapsed: \_\_\_\_\_  
Total Contract Days: \_\_\_\_\_

Sheet \_\_\_\_\_ of \_\_\_\_\_  
Date of Transmittal: \_\_\_\_\_

AFFIX PHOTO HERE

AFFIX PHOTO HERE

Photo No. \_\_\_\_\_  
Unit Address: \_\_\_\_\_

Remarks: \_\_\_\_\_

Photo No. \_\_\_\_\_  
Unit Address: \_\_\_\_\_

Remarks: \_\_\_\_\_

**Photographs of Existing Damage**

Total Contract Days Elapsed: \_\_\_\_\_

Total Contract Days: \_\_\_\_\_

Sheet \_\_\_\_\_ of \_\_\_\_\_

Date of Transmittal: \_\_\_\_\_

Photo No. \_\_\_\_\_

Unit Address: \_\_\_\_\_

\_\_\_\_\_

Remarks: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

AFFIX PHOTO HERE

Photo No. \_\_\_\_\_

Unit Address: \_\_\_\_\_

\_\_\_\_\_

Remarks: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

AFFIX PHOTO HERE

## **SECTION 03 30 00 - CAST-IN-PLACE CONCRETE**

### **PART 1 - GENERAL**

#### **1.1 RELATED DOCUMENTS**

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### **1.2 SUMMARY**

- A. Section includes cast-in-place concrete, including reinforcement, concrete materials, mixture design, placement procedures, and finishes.

#### **1.3 ACTION SUBMITTALS**

- A. Product Data: For each type of product.
- B. Design Mixtures: For each concrete mixture.

#### **1.4 QUALITY ASSURANCE**

- A. Ready-Mix-Concrete Manufacturer Qualifications: A firm experienced in manufacturing ready-mixed concrete products and that complies with ASTM C 94/C 94M requirements for production facilities and equipment.

### **PART 2 - PRODUCTS**

#### **2.1 CONCRETE, GENERAL**

- A. Comply with the following sections of ACI 301 unless modified by requirements in the Contract Documents:

#### **2.2 FORM-FACING MATERIALS**

- A. Smooth-Formed Finished Concrete: Form-facing panels that provide continuous, true, and smooth concrete surfaces. Furnish in largest practicable sizes to minimize number of joints.
  - 1. Plywood, metal, or other approved panel materials.

- B. Form-Release Agent: Commercially formulated form-release agent that does not bond with, stain, or adversely affect concrete surfaces and does not impair subsequent treatments of concrete surfaces.
  - 1. Formulate form-release agent with rust inhibitor for steel form-facing materials.

### 2.3 STEEL REINFORCEMENT

- A. Plain-Steel Welded-Wire Reinforcement: ASTM A 1064/A 1064M, plain, fabricated from as-drawn steel wire into flat sheets.

### 2.4 CONCRETE MATERIALS

- A. Source Limitations: Obtain each type or class of cementitious material of the same brand from the same manufacturer's plant, obtain aggregate from single source, and obtain admixtures from single source from single manufacturer.
- B. Cementitious Materials:
  - 1. Portland Cement: ASTM C 150/C 150M, Type I.
  - 2. Fly Ash: ASTM C 618, Class C or F.
- C. Lightweight Aggregate: ASTM C 330/C 330M, 1-inch nominal maximum aggregate size.
- D. Water: ASTM C 94/C 94M.

### 2.5 CURING MATERIALS

- A. Moisture-Retaining Cover: ASTM C 171, polyethylene film or white burlap-polyethylene sheet.
- B. Water: Potable.
- C. Clear, Waterborne, Membrane-Forming Curing Compound: ASTM C 309, Type 1, Class B.
  - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
    - a. ChemMasters, Inc.
    - b. Dayton Superior.
    - c. Euclid Chemical Company (The); an RPM company.
    - d. Kaufman Products, Inc.
    - e. Laticrete International, Inc.
    - f. W.R. Meadows, Inc.



## 2.6 CONCRETE MIXTURES, GENERAL

- A. Prepare design mixtures for each type and strength of concrete, proportioned on the basis of laboratory trial mixture or field test data, or both, according to ACI 301 (ACI 301M).
  - 1. Use a qualified independent testing agency for preparing and reporting proposed mixture designs based on laboratory trial mixtures.
- B. Cementitious Materials: Use fly ash, pozzolan, slag cement, and silica fume as needed to reduce the total amount of portland cement, which would otherwise be used, by not less than 40 percent.
- C. Admixtures: Use admixtures according to manufacturer's written instructions.
  - 1. Use water-reducing high-range water-reducing or plasticizing admixture in concrete, as required, for placement and workability.
  - 2. Use water-reducing and -retarding admixture when required by high temperatures, low humidity, or other adverse placement conditions.

## 2.7 CONCRETE MIXTURES

- A. Comply with ACI 301.
- B. Normal-Weight Concrete:
  - 1. Minimum Compressive Strength: 4000 psi at 28 days.
  - 2. Maximum W/C Ratio: 0.45.
  - 3. Slump Limit: 5 inches, plus or minus 1 inch.
  - 4. Air Content: 6 percent, plus or minus 1.5 percent at point of delivery for 3/4-inch nominal maximum aggregate size.

## 2.8 CONCRETE MIXING

- A. Ready-Mixed Concrete: Measure, batch, mix, and deliver concrete according to ASTM C 94/C 94M, and furnish batch ticket information.
  - 1. When air temperature is between 85 and 90 deg F, reduce mixing and delivery time from 1-1/2 hours to 75 minutes; when air temperature is above 90 deg F, reduce mixing and delivery time to 60 minutes.

# PART 3 - EXECUTION

## 3.1 FORMWORK INSTALLATION

- A. Design, erect, shore, brace, and maintain formwork, according to ACI 301, to support vertical, lateral, static, and dynamic loads, and construction loads that might be applied, until structure can support such loads.

- B. Construct formwork so concrete members and structures are of size, shape, alignment, elevation, and position indicated, within tolerance limits of ACI 117.
- C. Construct forms tight enough to prevent loss of concrete mortar.
- D. Construct forms for easy removal without hammering or prying against concrete surfaces. Provide crush or wrecking plates where stripping may damage cast-concrete surfaces.
  - 1. Do not use rust-stained steel form-facing material.
- E. Set edge forms, bulkheads, and intermediate screed strips for slabs to achieve required elevations in finished concrete surfaces. Provide and secure units to support screed strips; use strike-off templates or compacting-type screeds.
- F. Do not chamfer exterior corners and edges of permanently exposed concrete.
- G. Clean forms and adjacent surfaces to receive concrete. Remove chips, wood, sawdust, dirt, and other debris just before placing concrete.
- H. Retighten forms and bracing before placing concrete, as required, to prevent mortar leaks and maintain proper alignment.
- I. Coat contact surfaces of forms with form-release agent, according to manufacturer's written instructions, before placing reinforcement.

### 3.2 STEEL REINFORCEMENT INSTALLATION

- A. General: Comply with CRSI's "Manual of Standard Practice" for fabricating, placing, and supporting reinforcement.
- B. Install welded-wire reinforcement in longest practicable lengths on bar supports spaced to minimize sagging. Lap edges and ends of adjoining sheets at least one mesh spacing. Offset laps of adjoining sheet widths to prevent continuous laps in either direction. Lace overlaps with wire.

### 3.3 JOINTS

- A. General: Construct joints true to line with faces perpendicular to surface plane of concrete.
- B. Construction Joints: Install so strength and appearance of concrete are not impaired, at locations indicated or as approved by Architect.
  - 1. Place joints perpendicular to main reinforcement. Continue reinforcement across construction joints unless otherwise indicated.
- C. Contraction Joints in Slabs-on-Grade: Form weakened-plane contraction joints, sectioning concrete into areas as indicated. Construct contraction joints for a depth equal to at least one-fourth of concrete thickness as follows:

1. Grooved Joints: Form contraction joints after initial floating by grooving and finishing each edge of joint to a radius of 1/8 inch. Repeat grooving of contraction joints after applying surface finishes. Eliminate groover tool marks on concrete surfaces.

### 3.4 CONCRETE PLACEMENT

- A. Comply with ACI 301 for placing concrete.
- B. Before placing concrete, verify that installation of formwork, reinforcement, and embedded items is complete and that required inspections are completed.
- C. Do not add water to concrete during delivery, at Project site, or during placement.
- D. Deposit and consolidate concrete for slabs in a continuous operation, within limits of construction joints, until placement of a panel or section is complete.
  1. Consolidate concrete during placement operations, so concrete is thoroughly worked around reinforcement and other embedded items and into corners.
  2. Maintain reinforcement in position during concrete placement.
  3. Screed slab surfaces with a straightedge and strike off to correct elevations.
  4. Begin initial floating using bull floats or darbies to form a uniform and open-textured surface plane, before excess bleedwater appears on the surface. Do not further disturb slab surfaces before starting finishing operations.

### 3.5 FINISHING FLOORS AND SLABS

- A. General: Comply with ACI 302.1R recommendations for screeding, restraightening, and finishing operations for concrete surfaces. Do not wet concrete surfaces.
- B. Broom Finish: Apply a broom finish to exterior concrete.
  1. Immediately after float finishing, slightly roughen trafficked surface by brooming with fiber-bristle broom perpendicular to main traffic route. Coordinate required final finish with Architect before application.

### 3.6 CONCRETE PROTECTING AND CURING

- A. General: Protect freshly placed concrete from premature drying and excessive cold or hot temperatures. Comply with ACI 306.1 for cold-weather protection and ACI 301 for hot-weather protection during curing.
- B. Evaporation Retarder: Apply evaporation retarder to unformed concrete surfaces if hot, dry, or windy conditions cause moisture loss approaching 0.2 lb/sq. ft. x h before and during finishing operations. Apply according to manufacturer's written instructions after placing, screeding, and bull floating or darbying concrete, but before float finishing.
- C. Begin curing after finishing concrete but not before free water has disappeared from concrete surface.

- D. Curing Methods: Cure formed and unformed concrete for at least seven days by one or a combination of the following methods:
1. Moisture Curing: Keep surfaces continuously moist for not less than seven days with the following materials:
    - a. Water.
    - b. Continuous water-fog spray.
    - c. Absorptive cover, water saturated, and kept continuously wet. Cover concrete surfaces and edges with 12-inch lap over adjacent absorptive covers.
  2. Moisture-Retaining-Cover Curing: Cover concrete surfaces with moisture-retaining cover for curing concrete, placed in widest practicable width, with sides and ends lapped at least 12 inches, and sealed by waterproof tape or adhesive. Cure for not less than seven days. Immediately repair any holes or tears during curing period, using cover material and waterproof tape.
  3. Curing Compound: Apply uniformly in continuous operation by power spray or roller according to manufacturer's written instructions. Recoat areas subjected to heavy rainfall within three hours after initial application. Maintain continuity of coating and repair damage during curing period.

### 3.7 CONCRETE SURFACE REPAIRS

- A. Defective Concrete: Repair and patch defective areas when approved by Architect. Remove and replace concrete that cannot be repaired and patched to Architect's approval.
- B. Patching Mortar: Mix dry-pack patching mortar, consisting of 1 part portland cement to 2-1/2 parts fine aggregate passing a No. 16 sieve, using only enough water for handling and placing.
- C. Repairing Unformed Surfaces: Test unformed surfaces, such as slabs, for finish and verify surface tolerances specified for each surface. Correct low and high areas. Test surfaces sloped to drain for trueness of slope and smoothness; use a sloped template.
1. Repair finished surfaces containing defects. Surface defects include spalls, popouts, honeycombs, rock pockets, crazing and cracks in excess of 0.01 inch wide or that penetrate to reinforcement or completely through unreinforced sections regardless of width, and other objectionable conditions.
  2. Correct localized low areas during or immediately after completing surface finishing operations by cutting out low areas and replacing with patching mortar. Finish repaired areas to blend into adjacent concrete.
  3. Repair defective areas, except random cracks and single holes 1 inch or less in diameter, by cutting out and replacing with fresh concrete. Remove defective areas with clean, square cuts and expose steel reinforcement with at least a 3/4-inch clearance all around. Dampen concrete surfaces in contact with patching concrete and apply bonding agent. Mix patching concrete of same materials and mixture as original concrete, except without coarse aggregate. Place, compact, and finish to blend with adjacent finished concrete. Cure in same manner as adjacent concrete.

4. Repair random cracks and single holes 1 inch or less in diameter with patching mortar. Groove top of cracks and cut out holes to sound concrete and clean off dust, dirt, and loose particles. Dampen cleaned concrete surfaces and apply bonding agent. Place patching mortar before bonding agent has dried. Compact patching mortar and finish to match adjacent concrete. Keep patched area continuously moist for at least 72 hours.

END OF SECTION 03 30 53



## SECTION 23 00 00 – GENERAL PROVISIONS FOR MECHANICAL

### PART 1 - GENERAL

#### 1.01 SCOPE

- A. Special Conditions section and General Requirements section are made part of this Division.
- B. This Division includes the sections, but not necessarily limited to, listed in the Division Table of Contents.

#### 1.02 GENERAL

- A. The work included in this division consists of furnishing all labor, equipment, transportation, excavation, backfill, supplies, material, appurtenances and services necessary for the satisfactory installation of the complete and operating Mechanical System(s) indicated or specified in the Contract Documents.
- B. Any materials, labor, equipment or services not mentioned specifically herein which may be necessary to complete or perfect any part of the Mechanical Systems in a substantial manner, in compliance with the requirements stated, implied or intended in the drawings and/or specifications, shall be included as part of this Contract.
- C. It is the intent of this Contract to deliver to the Owner's a "like new" project once work is complete. Although plans and specifications are complete to the extent possible, it shall be the responsibility of the Contractors involved to remove and/or relocate or re-attach any existing items which interfere with the new work required for the complete installation without additional cost to the Owner.

#### 1.03 INTENT

- A. It is the intention of the Contract Documents to call for finished work, tested and ready for operation.
- B. Details not usually shown or specified, but necessary for the proper installation and operation of systems, equipment, materials, etc., shall be included in the work, the same as if herein specified or indicated.

#### 1.04 EXAMINATION OF SITE AND CONDITIONS

- A. Each Proposer shall inform himself of all conditions under which the work is to be performed, the site of the work, the structure of the ground, above and below grade, the obstacles that may be encountered, the availability and location of necessary facilities and all relevant matters concerning the work. Each Proposer

shall also fully acquaint himself with all existing conditions as to ingress and egress, distance of haul from supply points, routes for transportation of materials, facilities and services, availability of utilities, etc. His proposal shall cover all expenses or disbursements in connection with such matters and conditions. No allowance will be made for lack of knowledge concerning such conditions after bids are accepted.

#### 1.05 DRAWINGS AND SPECIFICATIONS

- A. The drawings are diagrammatic only and indicate the general arrangement of the work to be followed. If deviations from the layouts are necessitated by field conditions, detailed layouts of the proposed departures shall be submitted to the Engineer for approval before proceeding with the work. The drawings are not intended to show every item, which may be necessary to complete the systems. All Proposers shall anticipate that additional items may be required and submit their bid accordingly.
- B. The drawings and specifications are intended to supplement each other. No Proposer shall take advantage of conflict between them, or between parties of either. Should this condition exist, the Proposer shall request a clarification not less than twelve days prior to the submission of the proposal so that the condition may be clarified by Addendum. In the event that such a condition arises after work is started, the interpretation of the Engineer shall be final.
- C. The drawings and specifications shall be considered to be cooperative and anything appearing in the specifications, which may not be indicated on the drawings or conversely, shall be considered as part of the Contract and must be executed the same as though indicated by both.
- D. The Contractor shall make all his own measurements in the field and shall be responsible for correct fitting. He shall coordinate this work with all other branches of work in such a manner as to cause a minimum of conflict or delay.
- E. The Engineer shall reserve the right to make adjustments in location of piping, ductwork, equipment, etc. where such adjustments are in the interest of improving the project.
- F. Should conflict or overlap (duplication) of work between the various trades become evident, this shall be called to the attention of the Engineer. In such event neither trade shall assume that he is to be relieved of the work which is specified under his branch until instructions in writing are received from the Engineer.
- G. Unless dimensioned, the drawings only indicate approximate locations of equipment, piping, ductwork, etc. Dimensions given in figures on the drawings shall take precedence over scaled dimensions and all dimensions, whether given in figures or scaled, shall be verified in the field to insure no conflict with other work.
- H. Where on the Drawings a portion of the work is drawn out and the remainder is indicated in outline, or not indicated at all, the parts drawn out shall apply to all other like portions of the work. Where ornamentation or other detail is indicated by



starting only, such detail shall be continued throughout the courses or parts in which it occurs and shall also apply to all other similar parts of the work, unless otherwise indicated.

- I. Details not usually shown or specified, but necessary for the proper installation and operation of systems, equipment, materials, etc., shall be included in the work, the same as if herein specified or indicated.
- J. Where on the Contract Documents the word typical is used, it shall mean that the work method or means indicated as typical shall be repeated in and each time it occurs whether indicated or not.
- K. Special Note: Always check ceiling heights indicated on Architectural Drawings and Schedules and ensure that they may be maintained after all mechanical and electrical equipment is installed. Do not install equipment in the affected area until the conflict is resolved.

#### 1.06 REVIEW OF CONTRACT DOCUMENTS AND FIELD CONDITIONS BY CONTRACTOR

- A. By execution of this Contract, the Contractor warrants that he has visited the site of the proposed work, and fully acquainted himself with the conditions there existing relating to construction and labor and that he fully understands the facilities, difficulties, and restrictions attending the execution of the work under Contract. The Contractor further warrants that he has thoroughly examined and is familiar with the drawings, specifications and all other documents comprising the Contract. The Contractor further warrants that by execution of this Contract, his failure, when he was bidding on this Contract, to receive or examine any form, instrument, or document, or to visit the site and acquaint himself with the conditions there existing, in no way relieves the Contractor. The Contractor agrees that the Owner shall be justified in rejecting any claim based on facts regarding conditions for which he should have been on prior notice.
- B. Before ordering material or performing any work, the Contractor shall verify all measurements at the work site. Any difference between dimensions on the Drawings and actual measurements shall be brought to the Engineer's attention for his consideration before the work may proceed. No extra compensation will be allowed because of difference between actual measurements and dimensions indicated on the Drawings. The Contractor shall assume full responsibility for accuracy of measurements obtained at the Work Site.
- C. Dimensions, which are lacking, shall be obtained from the Architect. In no case shall Drawings be scaled.
- D. All subcontractors shall familiarize themselves with all of the conditions relating to this Contract since the terms set forth in the General Conditions binds all subcontractors to the Contract.

1.07 STRUCTURAL RESPONSIBILITY

- A. This contractor, in performing installation of his equipment and related work, shall be responsible for properly bracing, supporting, etc., any construction to guard against cracking settling, collapsing, displacing or weakening. No structural member shall be cut or otherwise weakened in any manner without the expressed consent of the Architect/Engineer.

1.08 WORK LAYOUT

- A. This contractor shall layout his work from construction lines and levels established by the General Contractor and shall be responsible for the proper location and placement of his work.
- B. Maintain all benchmarks, monuments, and other reference points; replace as directed if disturbed or destroyed.

1.09 UTILITIES

- A. Work confronting existing utilities shall be coordinated with the regulatory agencies and utility companies. Liability for damage to adjacent property and/or utilities shall be the burden of the contractor.

1.10 PROTECTION OF THE BUILDING

- A. This contractor shall not store materials or equipment on any roof of any building in such quantity that these parts of the building will be overloaded in any way.
- B. This contractor shall exercise care and shall confine all work within the contact limit lines.

1.11 PROTECTION OF STORED EQUIPMENT

- A. Provide suitable storage for, and completely protect all materials and equipment prior to installation. Storage shall be dry, clean and safe. Any materials or equipment damaged, deteriorated, rusted or defaced due to improper storage shall be fully repaired, refinished or replaced, as directed by the Engineer, and any materials or equipment lost through theft or mishandling shall be replaced, all without additional cost to the Owner.

1.12 COORDINATION BETWEEN TRADES

- A. Work under this Division shall be coordinated with work of the other Divisions.
- B. Each Proposer shall review all drawings and specifications including Architectural, Mechanical, Electrical, Fire Protection, Landscaping, Structural, Surveys, etc., to

ensure that the work he intends to provide does not encroach a conflict with or affect the work of others in any way. Where such effect does occur, it shall be the Proposer's responsibility to satisfactorily eliminate any such encroachment conflict or effect prior to the submission of his proposal. Each Proposer shall in particular ensure that there is adequate space to install his equipment and materials. Failure to do so shall result in the correction of such encroachment conflict or effect of any work awarded to the Proposer and shall be accomplished fully without expense to others and that they are reasonably accessible for maintenance. Check closely all mechanical and electrical closets, chases, ceiling voids, wall voids, crawl spaces, etc., to insure adequate spaces.

- C. It shall be the responsibility of this contractor to leave the necessary room for other trades. No extra compensation will be allowed to cover the cost of relocating piping, equipment, ductwork, etc., or equipment found encroaching on space required by others.
- D. This contractor shall make all mechanical connections, etc., to equipment furnished by others whenever such equipment is shown on any part of the drawings or mentioned in any section of the specifications, unless otherwise specified.

#### 1.13 SUBSTITUTION OF MATERIALS AND EQUIPMENT

- A. When this contractor requests approval of substitute materials and/or equipment, except when under formal alternate proposal, it shall be understood and agreed that such substitution, if approved, will be made without cost to the Owner or Engineer, regardless of changes in connections, spacing, electrical services, building space requirements, etc. In all cases where substitutions affect other trades, the contractor offering such substitutions shall reimburse all affected contractors for all necessary changes in their work.

#### 1.14 CODES AND STANDARDS

- A. Pertinent Federal, State and Local requirements and regulations are hereby made part of this contract. In case of conflict between Contract Documents and above listed requirements, the latter shall govern. Requirements of authority having local jurisdiction shall supersede all other requirements. Use of the term "code" in sections of the specification refers to applicable requirements and regulations of above agencies.
- B. Compliance with the Occupational Safety and Health Act shall be the responsibility of the contractor and under no circumstances shall the Engineer be an authority or be held responsible for any acts concerning this regulation.
- C. All equipment and material shall meet the minimum requirements of seismic bracing as governed by the authority having jurisdiction.

1.15 PROJECT CLEAN-UP

- A. The Contractor shall export off site, all debris resulting from work under this Division. Burning of debris at the project site is not permitted.
- B. Each contractor shall maintain his portion of this project in a neat and orderly fashion, disposing of debris, cartons, crates and boxes as the contents are installed in the project. This clean up shall be accomplished each day in order not to create hardships on the other trades.

1.16 INSTALLATION

- A. Installation of all mechanical equipment for the project as specified in these specifications and indicated on the drawings shall be in accordance with the general requirements of this section. Additional installation requirements applicable to individual systems are specified in the specific system section.
- B. All equipment shall be installed at locations indicated on the drawings and as specified herein.
- C. Assembly and installation of equipment shall be in strict accordance with manufacturer's installation instructions.
- D. Equipment shall be securely anchored in place. Care shall be exercised to correctly orient equipment before securing in place.
- E. All equipment and material installations shall meet the minimum requirements of seismic bracing as governed by the authority having jurisdiction.

1.17 OBSOLETE OR REMOVED EQUIPMENT AND MATERIALS

- A. The contractor shall remove all existing materials and equipment made obsolete by, and interfering with the additions, alterations, or razing as shown on the plans and specified. Maintain such existing equipment and materials intact and in existing condition insofar as possible.
- B. Unless otherwise specifically stated in the specifications or shown on the drawings, all such removed material and equipment, not to be reused, shall be removed from the site and disposed of in a proper manner.

1.18 PERMITS, FEES AND CERTIFICATES

- A. Each respective contractor shall obtain and pay all permits and licenses required by Federal, State and Local Ordinances for his type work. All fees in connection with inspections, permits, licenses, approvals, etc. shall be paid by the contractor whose work is affected.

#### 1.19 TESTING AND ADJUSTMENT

- A. The complete installation shall be tested as in regular service.
- B. Adjust all belts, sheaves, dampers, valves, etc., and leave in full and successful working condition. Lubricate all motors as recommended by manufacturer's instructions.
- C. All failures or defects in workmanship or material, which are revealed by the tests, shall be promptly corrected and the test reconducted.
- D. This Contractor shall be responsible for all materials and labor to provide sheave, belt and/or pulley replacement to meet the required airflows and/or tolerances specified.

#### 1.20 MECHANICAL CONTRACTOR QUALIFICATIONS

- A. The successful Mechanical Contracting Firm for this project shall have:
  - 1. Heating, Ventilation and Air Conditioning Master Contractor and Journeyman Mechanic License.

#### 1.21 GUARANTEES AND WARRANTIES

- A. This Contractor shall guarantee all equipment, apparatus, materials and workmanship entering into this contract to be the best of its respective kind, and shall replace all parts at his own expense, which have been proven defective, per the terms of the Contract. Items of equipment, which may have longer guarantees, shall have warranties and guarantees completed, in order, and in effect at the time of final acceptance of the work by the Engineer/Architect. This contractor shall furnish all such warranties and guarantees at the time of final acceptance of the work.

#### 1.22 SHOP DRAWINGS AND OTHER RELATED SUBMITTALS

- A. The type of submittal information required for each item of equipment is scheduled at the end of this section. Unless noted otherwise, submittals shall be furnished in electronic format. The Contractor shall furnish a single pdf file for each submittal. Submittals shall be clearly labeled as to what is contained within and shall note the related Specification Section. The Contractor shall be responsible for providing a numbering convention for submittals to allow easy tracking of submittals.
- B. Submittals for color selections shall not be electronically submitted. Provide hard copies of the colors. Printed color selections are not acceptable.
- C. Unless otherwise specified, materials and equipment must be a standard product of manufacturers regularly engaged in production of such items.

1. The contractor shall secure right to use any patented article, method or apparatus used in work.
  2. When substitute item of equipment has been submitted for approval, the mechanical contractor shall submit layout drawings indicating the changes necessary to adapt the substitute item of equipment to the design, when requested by the Engineer. All cost of the requested drawings shall be the responsibility of the contractor offering the substitutions.
  3. Under no circumstances will materials be considered for substitution, which are not a product of a manufacturer regularly engaged in production of such material or which is a product of one who merely assembles products of other manufacturers into fabricated units. Material submitted for substitution shall be subject to express and implied warranties of one manufacturer only.
- D. If substitution of material results in incidental extra costs on part of any trade under contract, such costs shall be borne by contractor desiring substitution.
1. Submittal data shall include specification data, such as metal gauges, finishes, optional accessories, etc., even though such equipment and materials may be detailed on the drawings or specified. In addition, the submittal data shall include performance (certification) data, wiring diagrams where applicable, accurate dimensional data and a recommended spare parts list. Outline or dimensional drawings alone are not acceptable.
  2. No roughing-in connections, etc., shall be done until approved equipment submittals are in the hands of the contractors. It shall be the contractor's responsibility to obtain approved drawings and to make all connections, etc., in the neatest and most workmanlike manner possible. Each contractor shall coordinate with all other contractors having any connections, roughing-in, etc., to the equipment.
  3. In general, normal catalog information (with the particular items underlined or otherwise denoted as being the submitted item) will be acceptable as submittal data. Installation, operating and maintenance instructions must be that information, specifically applicable to the item furnished, ordinarily supplied with the equipment to the owner with any modifications indicated. Wiring diagrams must be correct for the application. Generalized wiring diagrams, showing alternate methods of connection, will not be acceptable unless all unrelated sections are marked out.
  4. Submittal data sheets, which indicate several different model numbers, figure numbers, optional accessories, installation arrangements, etc., shall be clearly marked to indicate the specific items of equipment to be furnished. Samples and certificates shall be furnished as requested. Submittal data must be complete for each piece of equipment; piecemeal data will not be processed.
  5. It shall be noted that approval of shop drawings by the Engineer applies only to general design, arrangement, type, capacity and quality. Such approval doesn't apply to quantities, dimensions, connection locations and the like. In all cases, the contractor alone shall be responsible for furnishing the proper quantity of equipment and/or materials required, that all equipment fits the available space in a satisfactory manner, and that all connections are suitably located.

6. Before the project is accepted, all submittal data (shop drawings, etc.) must be complete and approved.
7. In addition to shop drawings described above, the following information is required of the contractor to be furnished to the Engineer.

1.23 HVAC DOCUMENT REQUIREMENTS

ITEM OR DESCRIPTION OF EQUIPMENT REQUIRING SHOP DRAWINGS	P A R T S	L I S T	O P E R A T I N G	M A N U A L	W I R I N G	D I A G R A M	C E R T I F I C A T I O N	S A M P L E S
Spilt System Furnace/Condensing Units	X		X		X			
Ductwork Flex Connections	X							
Refrigerant Piping	X							
Air Filters						X		
Mechanical Insulation	X					X		
Hangers, and Supports for Mechanical	X					X		
Line Hide/Shroud/Pipe Covering Systems	X							X



#### 1.24 OPERATION AND MAINTENANCE DATA

- A. The Contractor shall submit a single copy of the Operation and Maintenance Manuals prior to final completion.
- B. Operation and Maintenance Manuals (O&M's) shall be submitted in electronic format. Provide one pdf file per Specification Division.
- C. Prepare pdf files with the title for each file to include the Specification Division Number and brief description of contents (example: "Division 23 – HVAC Equipment").
- D. The first page of pdf file shall be a coversheet titled "Operation and Maintenance Manual". Include table of contents with page numbers. Provide bookmarks within the pdf file labeled for each section contained within the file.
- E. Include the following within O&M's
  1. Part 1: Directory, listing names, addresses, and telephone numbers of Architect/Engineer, Contractor, Subcontractors, and major equipment suppliers.
  2. Part 2: Operation and maintenance instructions, arranged by system and subdivided. For each category, identify names, addresses, and telephone numbers of subcontractors and suppliers. Identify the following:
    - a. Significant design criteria.
    - b. List of equipment
    - c. Parts list for each component.
    - d. Operating instructions.
    - e. Maintenance instructions for equipment and systems.
    - f. Maintenance instructions for special finishes, including recommended cleaning methods and materials and special precautions identifying detrimental agents.
  3. Part 3: Project documents and certificates, including the following:
    - a. Shop drawings and product data.
    - b. Power quality test results (including any required grounding tests).
    - c. Certificates.
    - d. Photocopies of warranties and bonds.
- F. Submit one copy of completed pdf's in final form on DVD or solid-state media fifteen (15) days prior to final inspection. This copy will be returned after final inspection with Owner's comments. Revise content of documents as required prior to final submittal.
- G. Submit final pdf's revised within ten (10) days after final inspection. Provide at minimum three (3) DVD or solid-state copies.

1.25 TRAINING/INSTRUCTION

- A. General Operating/Maintenance Instruction: Arrange for each installer of work requiring continuing maintenance or operation, to meet with the Owner's personnel, at project site, to provide basic instructions needed for proper operation and maintenance of entire work. Include instructions by manufacturer's representatives where installers are not expert in the required procedures. Review maintenance manuals, record documentations, tools, spare parts and materials, lubricants, fuels, identification system, control sequences, hazards, cleaning and similar procedures and facilities. For operational equipment, demonstrate start-up, shutdown, emergency operations, noise and vibration adjustments, safety, economy/efficiency adjustments, energy effectiveness, and similar operations. Review maintenance and operations in relation with applicable Warranties, Agreements to Maintain, Bonds, and similar continuing commitments.

**PART 2 - PRODUCTS (Not Used)**

**PART 3 - EXECUTION (Not Used)**

END OF SECTION 23 00 00

## SECTION 23 05 00 - COMMON WORK RESULTS FOR MECHANICAL

### PART 1 - GENERAL

#### 1.01 SUMMARY.

- A. This Section includes the following:
  - 1. Demolition.
  - 2. Equipment installation requirements common to equipment sections.
  - 3. Duct systems – common requirements.
  - 4. Supports and anchorages.

#### 1.02 DEFINITIONS

- A. Finished Spaces: Spaces other than mechanical and electrical equipment rooms, furred spaces, chases, unheated spaces immediately below roof, spaces above ceilings, unexcavated spaces, crawlspaces, and tunnels.
- B. Exposed, Interior Installations: Exposed to view indoors. Examples include finished occupied spaces and mechanical equipment rooms.
- C. Exposed, Exterior Installations: Exposed to view outdoors or subject to outdoor ambient temperatures and weather conditions. Examples include rooftop locations.
- D. Concealed, Interior Installations: Concealed from view and protected from physical contact by building occupants. Examples include above ceilings and in chases.
- E. Concealed, Exterior Installations: Concealed from view and protected from weather conditions and physical contact by building occupants but subject to outdoor ambient temperatures. Examples include installations within unheated shelters.

#### 1.03 QUALITY ASSURANCE

- A. Electrical Characteristics for Equipment: Equipment of higher electrical characteristics may be furnished provided such proposed equipment is approved in writing and connecting electrical services, circuit breakers, and conduit sizes are appropriately modified. If minimum energy ratings or efficiencies are specified, equipment shall comply with requirements.

## **PART 2 - PRODUCTS (NOT USED)**

## **PART 3 - EXECUTION**

### **3.01 DEMOLITION**

- A. Disconnect, demolish, and remove systems, equipment, and components indicated to be removed.
  - 1. Piping to Be Removed: Remove entire piping system when section of system is indicated (unless noted otherwise). Remove portion of piping indicated to be removed and cap or plug remaining piping with same or compatible piping material.
  - 2. Equipment to Be Removed: Disconnect, cap services, and remove equipment with all associated appurtenances.
  - 3. Equipment to Be Removed and Reinstalled: Disconnect and cap services and remove, clean, and store equipment; when appropriate, reinstall, reconnect, and make equipment operational.
  - 4. Equipment to Be Removed and Salvaged: Disconnect and cap services, remove equipment, deliver, and store at Owner designated location.
  - 5. Ducts to Be Removed: Remove portion of ducts indicated to be removed and plug remaining ducts with same or compatible ductwork material.
- B. If pipe, insulation, or equipment to remain is damaged in appearance or is unserviceable, remove damaged or unserviceable portions and replace with new products of equal capacity and quality.

### **3.02 EQUIPMENT INSTALLATION - COMMON REQUIREMENTS**

- A. Install equipment to allow maximum possible clearances.
- B. Install equipment level and plumb, parallel and perpendicular to other building systems and components in exposed interior spaces.
- C. Install equipment to facilitate service, maintenance, and repair or replacement of components. Connect equipment for ease of disconnecting, with minimum interference to other installations.
- D. Install equipment to allow clearance for piping installed at required slope.
- E. All installed equipment shall meet the seismic bracing requirements of the governing jurisdiction

### **3.03 DUCT SYSTEMS - COMMON REQUIREMENTS**

- A. Install duct according to the following requirements and Sections specifying duct systems.

- B. Drawing plans, schematics, and diagrams indicate general location and arrangement of duct systems. Indicated locations and arrangements were used to size duct and calculate friction loss, expansion, fan sizing, and other design considerations. Install duct as indicated unless deviations to layout are approved by the Engineer.
- C. Install duct to permit damper servicing.
- D. Install duct free of sags and bends.
- E. Install fittings for changes in direction and branch connections.
- F. Install duct to allow application of insulation.
- G. Install sheetmetal flanges for penetrations of walls, ceilings, and floors.
- H. Install sleeves for duct passing through masonry walls.
- I. Verify final equipment locations for roughing-in.
- J. Refer to equipment specifications in other Sections of these Specifications for roughing-in requirements.

#### 3.04 ERECTION OF METAL SUPPORTS AND ANCHORAGES

- A. Cut, fit, and place miscellaneous metal supports accurately in location, alignment, and elevation to support and anchor materials and equipment.
- B. Field Welding: Comply with AWS D1.1.

#### 3.05 ERECTION OF WOOD SUPPORTS AND ANCHORAGES

- A. Cut, fit, and place wood grounds, nailers, blocking, and anchorages to support, and anchor materials and equipment.
- B. Select fastener sizes that will not penetrate members if opposite side will be exposed to view or will receive finish materials. Tighten connections between members. Install fasteners without splitting wood members.
- C. Attach to substrates as required to support applied loads.

END OF SECTION 23 05 00



## SECTION 23 07 00 - MECHANICAL INSULATION

### PART 1 - GENERAL

#### 1.01 SUMMARY

A. Section Includes:

1. Insulation Materials:

- a. Flexible elastomeric.
- b. Mineral fiber.

2. Factory-applied jackets.
3. Field-applied jackets.
4. Tapes.
5. Securements.

#### 1.02 SUBMITTALS

A. Product Data: For each type of product indicated.

B. Shop Drawings:

1. Detail application of protective shields, saddles, and inserts at hangers for each type of insulation and hanger.
2. Detail insulation application at pipe expansion joints for each type of insulation.
3. Detail insulation application at elbows, fittings, flanges, valves, and specialties for each type of insulation.
4. Detail removable insulation at piping specialties, equipment connections, and access panels.

#### 1.03 QUALITY ASSURANCE

A. Fire-Test-Response Characteristics: Insulation and related materials shall have fire-test-response characteristics indicated, as determined by testing identical products per ASTM E 84, by a testing and inspecting agency acceptable to authorities having jurisdiction. Factory label insulation and jacket materials and adhesive, mastic, tapes, and cement material containers, with appropriate markings of applicable testing and inspecting agency.

1. Insulation Installed Indoors: Flame-spread index of 25 or less, and smoke-developed index of 50 or less.
2. Insulation Installed Outdoors: Flame-spread index of 75 or less, and smoke-developed index of 150 or less.

## **PART 2 - PRODUCTS**

### 2.01 INSULATION MATERIALS

- A. Comply with requirements in Part 3 schedule articles for where insulating materials shall be applied.
- B. Products shall not contain asbestos, lead, mercury, or mercury compounds.
- C. Products that come in contact with stainless steel shall have a leachable chloride content of less than 50 ppm when tested according to ASTM C 871.
- D. Insulation materials for use on austenitic stainless steel shall be qualified as acceptable according to ASTM C 795.
- E. Foam insulation materials shall not use CFC or HCFC blowing agents in the manufacturing process.
- F. Flexible Elastomeric: Closed-cell, sponge- or expanded-rubber materials. Comply with ASTM C 534, Type I for tubular materials and Type II for sheet materials.
  - 1. Products: Subject to compliance with requirements, provide one of the following:
    - a. Armacell LLC.
    - b. RBX Corporation.
    - c. Approved equal.
- G. Mineral-Fiber Blanket Insulation: Mineral or glass fibers bonded with a thermosetting resin. Comply with ASTM C 553, Type II and ASTM C 1290, Type III with factory applied FSK jacket. Factory-applied jacket requirements are specified in "Factory-Applied Jackets" Article.
  - 1. Products: Subject to compliance with requirements, provide one of the following:
    - a. CertainTeed Corp.
    - b. Johns Manville.
    - c. Knauf Insulation.
    - d. Owens Corning.
    - e. Approved equal.
- H. Mineral-Fiber, Preformed Pipe Insulation:
  - 1. Products: Subject to compliance with requirements, provide one of the following:
    - a. Johns Manville.
    - b. Knauf Insulation.
    - c. Owens Corning.
    - d. Approved equal.



2. Type I, 850 deg F Materials: Mineral or glass fibers bonded with a thermosetting resin. Comply with ASTM C 547, Type I, Grade A, with factory applied ASJ. Factory-applied jacket requirements are specified in "Factory-Applied Jackets" Article.

## 2.02 FACTORY-APPLIED JACKETS

- A. Insulation system schedules indicate factory-applied jackets on various applications. When factory-applied jackets are indicated, comply with the following:
  1. ASJ: White, kraft-paper, fiberglass-reinforced scrim with aluminum-foil backing; complying with ASTM C 1136, Type I.
  2. FSK Jacket: Aluminum-foil, fiberglass-reinforced scrim with kraft-paper backing; complying with ASTM C 1136, Type II.

## 2.03 FIELD-APPLIED JACKETS

- A. Field-applied jackets shall comply with ASTM C 921, Type I, unless otherwise indicated.
- B. PVC Jacket: High-impact-resistant, UV-resistant PVC complying with ASTM D 1784, Class 16354-C; thickness as scheduled; roll stock ready for shop or field cutting and forming. Thickness is indicated in field-applied jacket schedules.
  1. Products: Subject to compliance with requirements, provide one of the following:
    - a. Johns Manville.
    - b. Speedline Corporation.
    - c. Approved equal.
  2. Adhesive: As recommended by jacket material manufacturer.
  3. Color: White.
  4. Factory-fabricated fitting covers to match jacket if available; otherwise, field fabricate.
    - a. Shapes: 45- and 90-degree, short- and long-radius elbows, tees, valves, flanges, unions, reducers, end caps, soil-pipe hubs, traps, mechanical joints, and P-trap and supply covers for lavatories.
  5. Factory-fabricated tank heads and tank side panels.
- C. Self-Adhesive Outdoor Jacket: 60-mil- thick, laminated vapor barrier and waterproofing membrane for installation over insulation located aboveground outdoors; consisting of a rubberized bituminous resin on a crosslaminated polyethylene film covered with stucco-embossed aluminum-foil facing.
  1. Products: Subject to compliance with requirements, provide one of the following:
    - a. Polyguard.

- b. Approved equal.

## 2.04 TAPES

- A. ASJ Tape: White vapor-retarder tape matching factory-applied jacket with acrylic adhesive, complying with ASTM C 1136.

1. Products: Subject to compliance with requirements, provide one of the following:

- a. Avery Dennison Corporation, Specialty Tapes Division; Fasson 0835.
- b. Compac Corp.
- c. Ideal Tape Co.
- d. Venture Tape.
- e. Approved equal.

2. Width: 3 inches.

3. Thickness: 11.5 mils.

4. Adhesion: 90 ounces force/inch in width.

5. Elongation: 2 percent.

6. Tensile Strength: 40 lbf/inch in width.

7. ASJ Tape Disks and Squares: Precut disks or squares of ASJ tape.

- B. FSK Tape: Foil-face, vapor-retarder tape matching factory-applied jacket with acrylic adhesive; complying with ASTM C 1136.

1. Products: Subject to compliance with requirements, provide one of the following:

- a. Avery Dennison Corporation, Specialty Tapes Division.
- b. Compac Corp.
- c. Ideal Tape Co., Inc.
- d. Venture Tape.
- e. Approved equal.

2. Width: 3 inches.

3. Thickness: 6.5 mils.

4. Adhesion: 90 ounces force/inch in width.

5. Elongation: 2 percent.

6. Tensile Strength: 40 lbf/inch in width.

7. FSK Tape Disks and Squares: Precut disks or squares of FSK tape.

## 2.05 SECUREMENTS

- A. Staples: Outward-clinching insulation staples, nominal 3/4-inch- wide, stainless steel or Monel.

- B. Wire: 0.062-inch soft-annealed, galvanized steel.

1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:

- a. Childers Products.
- b. PABCO Metals Corporation.
- c. RPR Products, Inc.
- d. Approved equal.

### **PART 3 - EXECUTION**

#### **3.01 PREPARATION**

- A. Surface Preparation: Clean and dry surfaces to receive insulation. Remove materials that will adversely affect insulation application.

#### **3.02 GENERAL INSTALLATION REQUIREMENTS**

- A. Install insulation materials, accessories, and finishes with smooth, straight, and even surfaces; free of voids throughout the length of equipment, ducts and fittings, and piping including fittings, valves, and specialties.
- B. Install insulation materials, forms, vapor barriers or retarders, jackets, and thicknesses required for each item of equipment, duct system, and pipe system as specified in insulation system schedules.
- C. Install accessories compatible with insulation materials and suitable for the service. Install accessories that do not corrode, soften, or otherwise attack insulation or jacket in either wet or dry state.
- D. Install insulation with longitudinal seams at bottom of horizontal runs.
- E. Install multiple layers of insulation with longitudinal and end seams staggered.
- F. Do not weld brackets, clips, or other attachment devices to piping, fittings, and specialties.
- G. Keep insulation materials dry during application and finishing.
- H. Install insulation with tight longitudinal seams and end joints. Bond seams and joints with mechanical staples and adhesive recommended by insulation material manufacturer.
- I. Install insulation with least number of joints practical.
- J. Where vapor barrier is indicated, seal joints, seams, and penetrations in insulation at hangers, supports, anchors, and other projections with vapor-barrier mastic.
  - 1. Install insulation continuously through hangers and around anchor attachments.
  - 2. For insulation application where vapor barriers are indicated, extend insulation on anchor legs from point of attachment to supported item to point of attachment

- to structure. Taper and seal ends at attachment to structure with vapor-barrier mastic.
  - 3. Install insert materials and install insulation to tightly join the insert. Seal insulation to insulation inserts with adhesive or sealing compound recommended by insulation material manufacturer.
  - 4. Cover inserts with jacket material matching adjacent pipe insulation. Install shields over jacket, arranged to protect jacket from tear or puncture by hanger, support, and shield.
- K. Apply adhesives, mastics, and sealants at manufacturer's recommended coverage rate and wet and dry film thicknesses.
- L. Install insulation with factory-applied jackets as follows:
- 1. Draw jacket tight and smooth.
  - 2. Cover circumferential joints with 3-inch- wide strips, of same material as insulation jacket. Secure strips with adhesive and outward clinching staples along both edges of strip; spaced 4 inches o.c.
  - 3. Overlap jacket longitudinal seams at least 1-1/2 inches. Install insulation with longitudinal seams at bottom. Clean and dry surface to receive self-sealing lap. Staple laps with outward clinching staples along edge at 4 inches o.c.
    - a. For below ambient services, apply vapor-barrier over staples.
  - 4. Cover joints and seams with tape as recommended by insulation material manufacturer to maintain vapor seal.
  - 5. Where vapor barriers are indicated, apply vapor-barrier on seams and joints and at ends.
- M. Cut insulation in a manner to avoid compressing insulation more than 75 percent of its nominal thickness.
- N. Finish installation with systems at operating conditions. Repair joint separations and cracking due to thermal movement.
- O. Repair damaged insulation facings by applying same facing material over damaged areas. Extend patches at least 4 inches beyond damaged areas. Adhere, staple, and seal patches similar to butt joints.
- P. For above ambient services, do not install insulation to the following:
- 1. Vibration-control devices.
  - 2. Testing agency labels and stamps.
  - 3. Nameplates and data plates.
  - 4. Manholes.
  - 5. Handholes.
  - 6. Cleanouts.

### 3.03 PENETRATIONS

- A. Insulation Installation at Underground Exterior Wall Penetrations: Terminate insulation flush with sleeve seal. Seal terminations with flashing sealant.
- B. Insulation Installation at Aboveground Exterior Wall Penetrations: Install insulation continuously through wall penetrations.
  - 1. Seal penetrations with flashing sealant.
  - 2. For applications requiring only indoor insulation, terminate insulation inside wall surface and seal with joint sealant. For applications requiring indoor and outdoor insulation, install insulation for outdoor applications tightly joined to indoor insulation ends. Seal joint with joint sealant.
  - 3. Extend jacket of outdoor insulation outside wall flashing and overlap wall flashing at least 2 inches.
  - 4. Seal jacket to wall flashing with flashing sealant.
- C. Insulation Installation at Roof, Floor, Interior Wall and Partition Penetrations (That Are Not Fire Rated):
  - 1. Install insulation continuously through walls and partitions.

### 3.04 PENETRATIONS THROUGH FIRE-RATED ASSEMBLIES

- A. Insulation Installation at Fire-Rated Wall and Partition Penetrations:
  - 1. Duct: Terminate insulation at fire damper sleeves for fire-rated wall and partition penetrations. Externally insulate damper sleeves to match adjacent insulation and overlap duct insulation at least 2 inches.
  - 2. Pipe: Install insulation continuously through penetrations of fire-rated walls and partitions.

### 3.05 GENERAL PIPE INSULATION INSTALLATION

- A. Requirements in this article generally apply to all insulation materials except where more specific requirements are specified in various pipe insulation material installation articles.
- B. Insulation Installation on Fittings, Valves, Strainers, Flanges, and Unions:
  - 1. Install insulation over fittings, valves, strainers, flanges, unions, and other specialties with continuous thermal and vapor-retarder integrity, unless otherwise indicated.
  - 2. Insulate pipe elbows using preformed fitting insulation or mitered fittings made from same material and density as adjacent pipe insulation. Each piece shall be butted tightly against adjoining piece and bonded with adhesive. Fill joints, seams, voids, and irregular surfaces with insulating cement finished to a smooth, hard, and uniform contour that is uniform with adjoining pipe insulation.

3. Insulate tee fittings with preformed fitting insulation or sectional pipe insulation of same material and thickness as used for adjacent pipe. Cut sectional pipe insulation to fit. Butt each section closely to the next and hold in place with tie wire. Bond pieces with adhesive.
  4. Insulate valves using preformed fitting insulation or sectional pipe insulation of same material, density, and thickness as used for adjacent pipe. Overlap adjoining pipe insulation by not less than two times the thickness of pipe insulation, or one pipe diameter, whichever is thicker. For valves, insulate up to and including the bonnets, valve stuffing-box studs, bolts, and nuts. Fill joints, seams, and irregular surfaces with insulating cement.
  5. Insulate strainers using preformed fitting insulation or sectional pipe insulation of same material, density, and thickness as used for adjacent pipe. Overlap adjoining pipe insulation by not less than two times the thickness of pipe insulation, or one pipe diameter, whichever is thicker. Fill joints, seams, and irregular surfaces with insulating cement. Insulate strainers so strainer basket flange or plug can be easily removed and replaced without damaging the insulation and jacket. Provide a removable reusable insulation cover. For below ambient services, provide a design that maintains vapor barrier.
  6. Insulate flanges and unions using a section of oversized preformed pipe insulation. Overlap adjoining pipe insulation by not less than two times the thickness of pipe insulation, or one pipe diameter, whichever is thicker.
  7. Cover segmented insulated surfaces with a layer of finishing cement and coat with a mastic. Install vapor-barrier mastic for below ambient services and a breather mastic for above ambient services. Reinforce the mastic with fabric-reinforcing mesh. Trowel the mastic to a smooth and well-shaped contour.
  8. For services not specified to receive a field-applied jacket except for flexible elastomeric, install fitted PVC cover over elbows, tees, strainers, valves, flanges, and unions. Terminate ends with PVC end caps. Tape PVC covers to adjoining insulation facing using PVC tape.
  9. Stencil or label the outside insulation jacket of each union with the word "UNION." Match size and color of pipe labels.
- C. Insulate instrument connections for thermometers, pressure gages, pressure temperature taps, test connections, flow meters, sensors, switches, and transmitters on insulated pipes, vessels, and equipment. Shape insulation at these connections by tapering it to and around the connection with insulating cement and finish with finishing cement, mastic, and flashing sealant.

### 3.06 FLEXIBLE ELASTOMERIC INSULATION INSTALLATION

- A. Seal longitudinal seams and end joints with manufacturers recommended adhesive to eliminate openings in insulation that allow passage of air to surface being insulated.
- B. Insulation Installation on Pipe Flanges:
  1. Install pipe insulation to outer diameter of pipe flange.
  2. Make width of insulation section same as overall width of flange and bolts, plus twice the thickness of pipe insulation.

3. Fill voids between inner circumference of flange insulation and outer circumference of adjacent straight pipe segments with cut sections of sheet insulation of same thickness as pipe insulation.
4. Secure insulation to flanges and seal seams with manufacturer's recommended adhesive to eliminate openings in insulation that allow passage of air to surface being insulated.

C. Insulation Installation on Pipe Fittings and Elbows:

1. Install mitered sections of pipe insulation.
2. Secure insulation materials and seal seams with manufacturer's recommended adhesive to eliminate openings in insulation that allow passage of air to surface being insulated.

D. Insulation Installation on Valves and Pipe Specialties:

1. Install preformed valve covers manufactured of same material as pipe insulation when available.
2. When preformed valve covers are not available, install cut sections of pipe and sheet insulation to valve body. Arrange insulation to permit access to packing and to allow valve operation without disturbing insulation.
3. Install insulation to flanges as specified for flange insulation application.
4. Secure insulation to valves and specialties and seal seams with manufacturer's recommended adhesive to eliminate openings in insulation that allow passage of air to surface being insulated.

### 3.07 MINERAL-FIBER INSULATION INSTALLATION

A. Insulation Installation on Straight Pipes and Tubes:

1. Secure each layer of preformed pipe insulation to pipe with wire or bands and tighten bands without deforming insulation materials.
2. Where vapor barriers are indicated, seal longitudinal seams, end joints, and protrusions with vapor-barrier mastic and joint sealant.
3. For insulation with factory-applied jackets on above ambient surfaces, secure laps with outward clinched staples at 6 inches o.c.
4. For insulation with factory-applied jackets on below ambient surfaces, do not staple longitudinal tabs but secure tabs with additional adhesive as recommended by insulation material manufacturer and seal with vapor-barrier mastic and flashing sealant.

B. Insulation Installation on Pipe Flanges:

1. Install preformed pipe insulation to outer diameter of pipe flange.
2. Make width of insulation section same as overall width of flange and bolts, plus twice the thickness of pipe insulation.
3. Fill voids between inner circumference of flange insulation and outer circumference of adjacent straight pipe segments with mineral-fiber blanket insulation.

4. Install jacket material with manufacturer's recommended adhesive, overlap seams at least 1 inch, and seal joints with flashing sealant.

C. Insulation Installation on Pipe Fittings and Elbows:

1. Install preformed sections of same material as straight segments of pipe insulation when available.
2. When preformed insulation elbows and fittings are not available, install mitered sections of pipe insulation, to a thickness equal to adjoining pipe insulation. Secure insulation materials with wire or bands.

D. Insulation Installation on Valves and Pipe Specialties:

1. Install preformed sections of same material as straight segments of pipe insulation when available.
2. When preformed sections are not available, install mitered sections of pipe insulation to valve body.
3. Arrange insulation to permit access to packing and to allow valve operation without disturbing insulation.
4. Install insulation to flanges as specified for flange insulation application.

E. Blanket Insulation Installation on Ducts and Plenums:

1. For ducts and plenums with surface temperatures below ambient, install a continuous unbroken vapor barrier. Create a facing lap for longitudinal seams and end joints with insulation by removing 2 inches from 1 edge and 1 end of insulation segment. Secure laps to adjacent insulation section with 1/2-inch outward-clinching staples, 1-inch o.c. Install vapor barrier consisting of factory- or field-applied jacket, adhesive, vapor-barrier mastic, and sealant at joints, seams, and protrusions.
  - a. Repair punctures, tears, and penetrations with tape or mastic to maintain vapor-barrier seal.
2. Overlap unfaced blankets a minimum of 2 inches on longitudinal seams and end joints. At end joints, secure with steel bands spaced a maximum of 18 inches o.c.
3. Install insulation on rectangular duct elbows and transitions with a full insulation section for each surface. Install insulation on round and flat-oval duct elbows with individually mitered gores cut to fit the elbow.
4. Insulate duct stiffeners, hangers, and flanges that protrude beyond insulation surface with 6-inch-wide strips of same material used to insulate duct. Secure on alternating sides of stiffener, hanger, and flange with pins spaced 6 inches o.c.

### 3.08 FIELD QUALITY CONTROL

- A. Perform tests and inspections.



B. Tests and Inspections:

1. Inspect ductwork, randomly selected by Engineer, by removing field-applied jacket and insulation in layers in reverse order of their installation. Extent of inspection shall be limited to two location(s) for each duct system defined in the "Duct Insulation Schedule, General" Article.
2. Inspect field-insulated equipment, randomly selected by Engineer, by removing field-applied jacket and insulation in layers in reverse order of their installation. Extent of inspection shall be limited to two location(s) for each type of equipment defined in the "Equipment Insulation Schedule" Article. For large equipment, remove only a portion adequate to determine compliance.
3. Inspect pipe, fittings, strainers, and valves, randomly selected by Engineer, by removing field-applied jacket and insulation in layers in reverse order of their installation. Extent of inspection shall be limited to two locations of straight pipe, two locations of threaded fittings, two locations of welded fittings, two locations of threaded strainers, two locations of welded strainers, two locations of threaded valves, and two locations of flanged valves for each pipe service defined in the "Piping Insulation Schedule, General" Article.

- C. All insulation applications will be considered defective Work if sample inspection reveals noncompliance with requirements.

3.09 DUCT INSULATION SCHEDULE, GENERAL

A. Ducts and Terminal Devices Requiring Insulation:

1. Indoor supply and return-air ducts.

B. Items Not Insulated:

1. Factory-insulated flexible ducts.
2. Factory-insulated plenums and casings.
3. Flexible connectors.
4. Vibration-control devices.
5. Factory-insulated access panels and doors.

3.10 INDOOR DUCT AND TERMINAL DEVICES INSULATION SCHEDULE

- A. Supply-Air Duct within Mechanical Rooms Insulation: Mineral-fiber blanket with factory-applied FSK Jacket, 2.2 inches thick and 0.75-lb/cu. ft. nominal density.
- B. Return-Air Duct Insulation: Anti-Microbial mineral fiber liner, ½" thick, 3.8-lb/cu.ft. nominal density.

3.11 PIPING INSULATION SCHEDULE, GENERAL

- A. Acceptable preformed pipe and tubular insulation materials and thicknesses are identified for each piping system and pipe size range. If more than one material is listed for a piping system, selection from materials listed is Contractor's option.
- B. Items Not Insulated: Unless otherwise indicated, do not install insulation on the following:
  - 1. Underground piping.
  - 2. Chrome-plated pipes and fittings unless there is a potential for personnel injury.

3.12 INDOOR/OUTDOOR PIPING INSULATION SCHEDULE

- A. Refrigerant Piping: Insulation shall be the following.
  - 1. Flexible Elastomeric, Type I, with UV protection:  $\frac{3}{4}$  inch thick. (Insulate both suction and liquid lines from condensing unit to metal shroud enclosure.)

3.13 OUTDOOR, FIELD-APPLIED JACKET SCHEDULE

- A. Install jacket over insulation material. For insulation with factory-applied jacket, install the field-applied jacket over the factory-applied jacket.
- B. Refrigerant Piping, Exposed:
  - 1. UV Resistant PVC jacket and fitting covers.
  - 2. Line-Hide system or metal shroud system as described in drawings shall be provided to completely hide and cover refrigerant lines and associated condensate, power, control wiring, conduit etc.

END OF SECTION 23 07 00

## SECTION 23 23 00 - REFRIGERANT PIPING

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes refrigerant piping used for air-conditioning applications.

#### 1.02 PERFORMANCE REQUIREMENTS

- A. Line Test Pressure for Refrigerant R-410A:

- 1. Suction Lines: 315 psig.
- 2. Hot-Gas and Liquid Lines: 550 psig.

#### 1.03 SUBMITTALS

- A. Product Data: For each type of valve and refrigerant piping specialty indicated. Include pressure drop based on manufacturer's test data.

- 1. Refrigerant piping indicated on Drawings is schematic only. Size piping layout, including oil traps, double risers, specialties, and pipe and tube sizes to accommodate, as a minimum, equipment provided, elevation difference between compressor and evaporator, and length of piping to ensure proper operation and compliance with warranties of connected equipment.

- B. Operation and maintenance data.

#### 1.04 QUALITY ASSURANCE

- A. Comply with ASHRAE 15-2013, "Safety Standard for Refrigeration Systems."

- B. Comply with ASME B31.5, "Refrigeration Piping and Heat Transfer Components."

- C. Comply with ASHRAE 34-2013 "Designation and Safety Classification of Refrigerants."

#### 1.05 PRODUCT STORAGE AND HANDLING

- A. Store piping in a clean and protected area with end caps in place to ensure that piping interior and exterior are clean when installed.

## **PART 2 - PRODUCTS**

### **2.01 COPPER TUBE AND FITTINGS**

- A. Copper Tube: ASTM B 88, Type K or L and ASTM B 280.
- B. Wrought-Copper Fittings: ASME B16.22.
- C. Wrought-Copper Unions: ASME B16.22.
- D. Brazing Filler Metals: AWS A5.8.

### **2.02 VALVES AND SPECIALTIES**

#### **A. Diaphragm Packless Valves:**

1. Body and Bonnet: Forged brass or cast bronze; globe design with straight-through or angle pattern.
2. Diaphragm: Phosphor bronze and stainless steel with stainless-steel spring.
3. Operator: Rising stem and hand wheel.
4. Seat: Nylon.
5. End Connections: Socket, union, or flanged.
6. Working Pressure Rating: 500 psig.
7. Maximum Operating Temperature: 275 deg F.

#### **B. Packed-Angle Valves:**

1. Body and Bonnet: Forged brass or cast bronze.
2. Packing: Molded stem, back seating, and replaceable under pressure.
3. Operator: Rising stem.
4. Seat: Non-rotating, self-aligning polytetrafluoroethylene.
5. Seal Cap: Forged-brass or valox hex cap.
6. End Connections: Socket, union, threaded, or flanged.
7. Working Pressure Rating: 500 psig.
8. Maximum Operating Temperature: 275 deg F.

#### **C. Check Valves:**

1. Body: Ductile iron, forged brass, or cast bronze; globe pattern.
2. Bonnet: Bolted ductile iron, forged brass, or cast bronze; or brass hex plug.
3. Piston: Removable polytetrafluoroethylene seat.
4. Closing Spring: Stainless steel.
5. Manual Opening Stem: Seal cap, plated-steel stem, and graphite seal.
6. End Connections: Socket, union, threaded, or flanged.
7. Maximum Opening Pressure: 0.50 psig.
8. Working Pressure Rating: 500 psig.
9. Maximum Operating Temperature: 275 deg F.

#### **D. Service Valves:**

1. Body: Forged brass with brass cap including key end to remove core.
  2. Core: Removable ball-type check valve with stainless-steel spring.
  3. Seat: Polytetrafluoroethylene.
  4. End Connections: Copper spring.
  5. Working Pressure Rating: 500 psig.
- E. Solenoid Valves: Comply with ARI 760 and UL 429; listed and labeled by an NRTL.
1. Body and Bonnet: Plated steel.
  2. Solenoid Tube, Plunger, Closing Spring, and Seat Orifice: Stainless steel.
  3. Seat: Polytetrafluoroethylene.
  4. End Connections: Threaded.
  5. Electrical: Molded, watertight coil in NEMA 250 enclosure of type required by location with 1/2-inch conduit adapter, and 115-V ac coil.
  6. Working Pressure Rating: 400 psig.
  7. Maximum Operating Temperature: 240 deg F.
  8. Manual operator.
- F. Safety Relief Valves: Comply with ASME Boiler and Pressure Vessel Code; listed and labeled by an NRTL.
1. Body and Bonnet: Ductile iron and steel, with neoprene O-ring seal.
  2. Piston, Closing Spring, and Seat Insert: Stainless steel.
  3. Seat Disc: Polytetrafluoroethylene.
  4. End Connections: Threaded.
  5. Working Pressure Rating: 400 psig.
  6. Maximum Operating Temperature: 240 deg F.
- G. Thermostatic Expansion Valves: Comply with ARI 750.
1. Body, Bonnet, and Seal Cap: Forged brass or steel.
  2. Diaphragm, Piston, Closing Spring, and Seat Insert: Stainless steel.
  3. Packing and Gaskets: Non-asbestos.
  4. Capillary and Bulb: Copper tubing filled with refrigerant charge.
  5. Suction Temperature: 40 deg F.
  6. Superheat: Adjustable.
  7. Reverse-flow option (for heat-pump applications).
  8. End Connections: Socket, flare, or threaded union.
  9. Working Pressure Rating: 450 psig.
- H. Straight-Type Strainers:
1. Body: Welded steel with corrosion-resistant coating.
  2. Screen: 100-mesh stainless steel.
  3. End Connections: Socket or flare.
  4. Working Pressure Rating: 500 psig.
  5. Maximum Operating Temperature: 275 deg F.
- I. Angle-Type Strainers:

1. Body: Forged brass or cast bronze.
2. Drain Plug: Brass hex plug.
3. Screen: 100-mesh Monel.
4. End Connections: Socket or flare.
5. Working Pressure Rating: 500 psig.
6. Maximum Operating Temperature: 275 deg F.

J. Moisture/Liquid Indicators:

1. Body: Forged brass.
2. Window: Replaceable, clear, fused glass window with indicating element protected by filter screen.
3. Indicator: Color coded to show moisture content in ppm.
4. Minimum Moisture Indicator Sensitivity: Indicate moisture above 60 ppm.
5. End Connections: Socket or flare.
6. Working Pressure Rating: 500 psig.
7. Maximum Operating Temperature: 240 deg F.

K. Replaceable-Core Filter Dryers: Comply with ARI 730.

1. Body and Cover: Painted-steel shell with ductile-iron cover, stainless-steel screws, and neoprene gaskets.
2. Filter Media: 10 micron, pleated with integral end rings; stainless-steel support.
3. Desiccant Media: Activated charcoal.
4. Designed for reverse flow (for heat-pump applications).
5. End Connections: Socket.
6. Access Ports: NPS 1/4 connections at entering and leaving sides for pressure differential measurement.
7. Maximum Pressure Loss: 2 psig.
8. Rated Flow: As specified on drawings.
9. Working Pressure Rating: 500 psig.
10. Maximum Operating Temperature: 240 deg F.

L. Permanent Filter Dryers: Comply with ARI 730.

1. Body and Cover: Painted-steel shell.
2. Filter Media: 10 micron, pleated with integral end rings; stainless-steel support.
3. Desiccant Media: Activated charcoal.
4. Designed for reverse flow (for heat-pump applications).
5. End Connections: Socket.
6. Access Ports: NPS 1/4 connections at entering and leaving sides for pressure differential measurement.
7. Maximum Pressure Loss: 2 psig.
8. Rated Flow: As specified on drawings.
9. Working Pressure Rating: 500 psig.
10. Maximum Operating Temperature: 240 deg F.

M. Liquid Accumulators: Comply with ARI 495.

1. Body: Welded steel with corrosion-resistant coating.

2. End Connections: Socket or threaded.
3. Working Pressure Rating: 500 psig.
4. Maximum Operating Temperature: 275 deg F.

## 2.03 REFRIGERANTS

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
1. Atofina Chemicals, Inc.
  2. DuPont Company; Fluorochemicals Div.
  3. Honeywell, Inc.; Genetron Refrigerants.
  4. INEOS Fluor Americas LLC.
  5. Approved equal.
- B. R-410A.

## PART 3 - EXECUTION

### 3.01 PIPING APPLICATIONS

- A. Hot-gas, liquid, and suction Lines NPS 4 and Smaller for Conventional Air-Conditioning Applications: Copper, Type L (B), drawn-temper tubing and wrought-copper fittings with brazed joints.
- B. Safety-Relief-Valve Discharge Piping: Copper, Type K (A), drawn-temper tubing and wrought-copper fittings with brazed joints.

### 3.02 VALVE AND SPECIALTY APPLICATIONS

- A. Install packed-angle valves in suction and discharge lines of compressor.
- B. Install service valves for gage taps at strainers if they are not an integral part of strainers.
- C. Install a check valve at the compressor discharge and a liquid accumulator at the compressor suction connection.
- D. Except as otherwise indicated, install packed-angle valves on inlet and outlet side of filter dryers.
- E. Install a full-sized, three-valve bypass around filter dryers.
- F. Install solenoid valves upstream from each expansion valve. Install solenoid valves in horizontal lines with coil at top.

- G. Install thermostatic expansion valves as close as possible to distributors on evaporators.
  - 1. Install valve so diaphragm case is warmer than bulb.
  - 2. Secure bulb to clean, straight, horizontal section of suction line using two bulb straps. Do not mount bulb in a trap or at bottom of the line.
  - 3. If external equalizer lines are required, make connection where it will reflect suction-line pressure at bulb location.
- H. Install safety relief valves where required by ASME Boiler and Pressure Vessel Code. Pipe safety-relief-valve discharge line to outside according to ASHRAE 15.
- I. Install moisture/liquid indicators in liquid line at the inlet of the thermostatic expansion valve or at the inlet of the evaporator coil capillary tube.
- J. Install strainers upstream from and adjacent to the following unless they are furnished as an integral assembly for device being protected:
  - 1. Solenoid valves.
  - 2. Thermostatic expansion valves.
  - 3. Compressor.
- K. Install filter dryers in liquid line between compressor and thermostatic expansion valve, and in the suction line at the compressor.
- L. Install flexible connectors at compressors.

### 3.03 PIPING INSTALLATION

- A. Install refrigerant piping according to ASHRAE 15, latest issue with addendums.
- B. Install piping in concealed locations unless otherwise indicated and except in equipment rooms and service areas.
- C. Install piping indicated to be exposed and piping in equipment rooms and service areas at right angles or parallel to building walls. Diagonal runs are prohibited unless specifically indicated otherwise.
- D. Install piping above accessible ceilings to allow sufficient space for ceiling panel removal.
- E. Install piping adjacent to machines to allow service and maintenance.
- F. Install piping free of sags and bends.
- G. Install fittings for changes in direction and branch connections.
- H. Select system components with pressure rating equal to or greater than system operating pressure.



- I. Install piping as short and direct as possible, with a minimum number of joints, elbows, and fittings.
- J. Arrange piping to allow inspection and service of refrigeration equipment. Install valves and specialties in accessible locations to allow for service and inspection. Install access doors or panels if valves or equipment requiring maintenance are concealed behind finished surfaces.
- K. Slope refrigerant piping as follows:
  - 1. Install horizontal hot-gas discharge piping with a uniform slope downward away from compressor.
  - 2. Install horizontal suction lines with a uniform slope downward to compressor.
  - 3. Install traps and double risers to entrain oil in vertical runs.
  - 4. Liquid lines may be installed level.
- L. When brazing, remove solenoid-valve coils and sight glasses; also remove valve stems, seats, and packing, and accessible internal parts of refrigerant specialties. Do not apply heat near expansion-valve bulb.
- M. Install pipe sleeves at penetrations in exterior walls.
- N. Install piping with adequate clearance between pipe and adjacent walls and hangers or between pipes for insulation installation.
- O. Install sleeves through floors, walls, or ceilings, sized to permit installation of full-thickness insulation.
- P. Seal pipe penetrations through exterior walls.
- Q. Identify refrigerant piping and valves.

### 3.04 PIPE JOINT CONSTRUCTION

- A. Brazed Joints: Construct joints according to AWS's "Brazing Handbook," Chapter "Pipe and Tube."
  - 1. Use Type BcuP, copper-phosphorus alloy for joining copper socket fittings with copper pipe.
  - 2. Use Type BA<sub>g</sub>, cadmium-free silver alloy for joining copper with bronze or steel.

### 3.05 HANGERS AND SUPPORTS

- A. Install the following pipe attachments:
  - 1. Adjustable steel clevis hangers for individual horizontal runs less than 20 feet long.
  - 2. Copper-clad hangers and supports for hangers and supports in direct contact with copper pipe.

- B. Install hangers for copper tubing with the following maximum spacing and minimum rod sizes:

1. NPS 1/2: Maximum span, 60 inches; minimum rod size, 1/4 inch.
2. NPS 5/8: Maximum span, 60 inches; minimum rod size, 1/4 inch.
3. NPS 1: Maximum span, 72 inches; minimum rod size, 1/4 inch.
4. NPS 1-1/4: Maximum span, 96 inches; minimum rod size, 3/8 inch.
5. NPS 1-1/2: Maximum span, 96 inches; minimum rod size, 3/8 inch.
6. NPS 2: Maximum span, 96 inches; minimum rod size, 3/8 inch.
7. NPS 2-1/2: Maximum span, 108 inches; minimum rod size, 3/8 inch.

### 3.06 FIELD QUALITY CONTROL

- A. Tests and Inspections:

1. Comply with ASME B31.5, Chapter VI.
2. Test refrigerant piping and specialties. Isolate compressor, condenser, evaporator, and safety devices from test pressure if they are not rated above the test pressure.
3. Test high- and low-pressure side piping of each system separately at not less than the pressures indicated in Part 1 "Performance Requirements" Article.
  - a. Fill system with nitrogen to the required test pressure.
  - b. System shall maintain test pressure at the manifold gage throughout duration of test.
  - c. Test joints and fittings with electronic leak detector or by brushing a small amount of soap and glycerin solution over joints.
  - d. Remake leaking joints using new materials and retest until satisfactory results are achieved.

### 3.07 SYSTEM CHARGING

- A. Charge system using the following procedures:

1. Install core in filter dryers after leak test but before evacuation.
2. Evacuate entire refrigerant system with a vacuum pump to 500 micrometers. If vacuum holds for 12 hours, system is ready for charging.
3. Break vacuum with refrigerant gas, allowing pressure to build up to 2 psig.
4. Charge system with a new filter-dryer core in charging line.
5. Provide final refrigerant charge to Engineer in writing along with certified start-up reports.

### 3.08 ADJUSTING

- A. Adjust thermostatic expansion valve to obtain proper evaporator superheat.
- B. Adjust high- and low-pressure switch settings to avoid short cycling in response to fluctuating suction pressure.

- C. Adjust set-point temperature of air-conditioning controllers to the system design temperature.
- D. Perform the following adjustments before operating the refrigeration system, according to manufacturer's written instructions:
  - 1. Verify that compressor oil level is correct.
  - 2. Open compressor suction and discharge valves.
  - 3. Open refrigerant valves except bypass valves that are used for other purposes.
  - 4. Check open compressor-motor alignment and verify lubrication for motors and bearings.
- E. Replace core of replaceable filter dryer after system has been adjusted and after design flow rates and pressures are established.

END OF SECTION 23 23 00



## SECTION 23 54 00 – FURNACES AND CONDENSING UNITS

### PART 1 - GENERAL

#### 1.01 SUMMARY

- A. This Section includes the following:
  - 1. Gas-fired, noncondensing furnaces and accessories.
  - 2. Thermostats.
  - 3. Air filters.
  - 4. Refrigeration components.
  - 5. Condensing units.

#### 1.02 SUBMITTALS

- A. Product Data: Include rated capacities, operating characteristics, furnished specialties, and accessories for each of the following:
  - 1. Furnace.
  - 2. Thermostat.
  - 3. Air filter.
  - 4. Refrigeration components.
  - 5. Condensing units.
- B. Operation and Maintenance Data.
- C. Warranty.

#### 1.03 QUALITY ASSURANCE

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
- B. Comply with NFPA 70.

#### 1.04 WARRANTY

- A. Special Warranty: Manufacturer's standard form in which manufacturer agrees to repair or replace the following components of furnaces that fail in materials or workmanship within specified warranty period:
  - 1. Warranty Period, Commencing on Date of Substantial Completion:

- a. Furnace Heat Exchanger: 10 years.
- b. Integrated Ignition and Blower Control Circuit Board: 1 year.
- c. Refrigeration Compressors: 5 year.
- d. Evaporator and Condenser Coils: 5 years.

## **PART 2 - PRODUCTS**

### **2.01 GAS-FIRED FURNACES, NONCONDENSING**

- A. Subject to compliance with requirements, provide products by one of the following:
  1. Carrier Corporation.
  2. Daikin.
  3. York International Corp.
  4. Approved equal.
- B. General Requirements for Gas-Fired, Noncondensing Furnaces: Factory assembled, piped, wired, and tested; complying with ANSI Z21.47/CSA 2.3, "Gas-Fired Central Furnaces," and with NFPA 54.
- C. Cabinet: Steel.
  1. Cabinet interior around heat exchanger shall be factory-installed insulation.
  2. Lift-out panels shall expose burners and all other items requiring access for maintenance.
  3. Factory paint external cabinets in manufacturer's standard color.
- D. Fan: Centrifugal, factory balanced, resilient mounted, drive drive.
  1. Special Motor Features: Single speed, premium efficiency, with internal thermal protection and permanent lubrication.
  2. Special Motor Features: Multitapped, multispeed with internal thermal protection and permanent lubrication.
  3. Special Motor Features: Electronically controlled motor (ECM) controlled by integrated furnace/blower control.
- E. Heat Exchanger: Stainless steel.
- F. Burner:
  1. Gas Valve: 100 percent safety main gas valve, main shutoff valve, pressure regulator, safety pilot with electronic flame sensor, limit control, transformer, and combination ignition/fan timer control board.
  2. Ignition: Electric pilot ignition, with hot-surface igniter or electric spark ignition.
- G. Gas-Burner Safety Controls:
  1. Electronic Flame Sensor: Prevents gas valve from opening until pilot flame is proven; stops gas flow on ignition failure.

2. Flame Rollout Switch: Installed on burner box; prevents burner operation.
3. Limit Control: Fixed stop at maximum permissible setting; de-energizes burner on excessive bonnet temperature; automatic reset.

- H. Combustion-Air Inducer: Centrifugal fan with thermally protected motor and sleeve bearings prepurges heat exchanger and vents combustion products; pressure switch prevents furnace operation if combustion-air inlet or flue outlet is blocked.
- I. Furnace Controls: Solid-state board integrates ignition, heat, cooling, and fan speeds; adjustable fan-on and fan-off timing; terminals for connection to accessories.

## 2.02 THERMOSTATS

- A. Solid-State Thermostat: Wall-mounting, non-programmable, microprocessor-based unit with manual switching from heating to cooling. Honeywell Model No. TH1110D1003 or approved Equal.
- B. Heating-Cooling Thermostat: Adjustable temperature, heating mode – cooling mode, wall-mounting.
- C. Control Wiring: Unshielded twisted-pair cabling.
1. No. 24 AWG, 100-ohm, four pair.
  2. Cable Jacket Color: Blue.

## 2.03 AIR FILTERS

- A. Disposable Filters: 1-inch- thick MERV 8.

## 2.04 REFRIGERATION COMPONENTS

- A. General Refrigeration Component Requirements:
1. Refrigeration compressor, coils, and specialties shall be designed to operate with HCFC-free refrigerants.
  2. Energy-Efficiency Ratio: Equal to or greater than prescribed by ASHRAE/IESNA 90.1, "Energy Standard for Buildings except Low-Rise Residential Buildings."
- B. Refrigerant Coil: Copper tubes mechanically expanded into aluminum fins. Comply with ARI 210/240, "Unitary Air-Conditioning and Air-Source Heat Pump Equipment." Match size with furnace. Include condensate drain pan with accessible drain outlet.
1. Refrigerant Coil Enclosure: Steel, matching furnace and evaporator coil, with access panel and flanges for integral mounting at or on furnace cabinet and galvanized sheet metal drain pan coated with black asphaltic base paint.

- C. Refrigerant Piping: Comply with requirements in Division 23 Section "Refrigerant Piping."
- D. Air-Cooled, Compressor-Condenser Unit:
  - 1. Casing: Steel, finished with baked enamel, with removable panels for access to controls, weep holes for water drainage, and mounting holes in base. Provide brass service valves, fittings, and gage ports on exterior of casing.
  - 2. Compressor: Hermetically sealed scroll type.
    - a. Crankcase heater.
    - b. Vibration isolation mounts for compressor.
    - c. Compressor motor shall have thermal- and current-sensitive overload devices, start capacitor, relay, and contactor.
    - d. Two-speed compressor motors shall have manual-reset high-pressure switch and automatic-reset low-pressure switch.
    - e. Refrigerant Charge: R-410A.
    - f. Additional options as scheduled on drawings.
  - 3. Refrigerant Coil: Copper tube, with mechanically bonded aluminum fins, complying with ARI 210/240, and with liquid subcooler.
  - 4. Fan: Aluminum-propeller type, directly connected to motor.
  - 5. Motor: Permanently lubricated, with integral thermal-overload protection.
  - 6. Low Ambient Kit: Permits operation down to 45 deg F.
- E. Capacities and Characteristics: As specified on drawings.

### **PART 3 - EXECUTION**

#### **3.01 INSTALLATION**

- A. Install gas-fired furnaces and associated fuel and vent features and systems according to NFPA 54.
- B. Base-Mounted Units: Secure units to substrate. Provide optional bottom closure base if required by installation conditions.
  - 1. Anchor furnace to substrate to resist code-required seismic acceleration.
- C. Plenum-Base Mounted Units: Fabricate and install full-size, return air plenum base minimum 18" high. Fabricate plenum as necessary for proper structural support. Internally line plenum and secure liner.
- D. Controls: Install thermostats at mounting height and location of existing thermostats.
- E. Wiring Method: Install control wiring in accessible ceiling spaces and in conduit within walls. Conceal control wiring except in unfinished spaces.
  - 1. Wiring shall be plenum rated.



- F. Install ground-mounted, compressor-condenser components on concrete bases. Fasten condensing unit to concrete base with lag screw.
- G. Install roof-mounted, compressor-condenser components on adjustable, leveling, vibration isolating support legs for mounting on existing sloped roofs. Anchor units to supports with removable, cadmium-plated fasteners. Set supports on appropriate protective padding to prevent damage to existing roof.
- H. Provide additional tie-downs and securements to roof mounted compressor-condenser units to prevent unit from moving/falling through normal use and in the event of high winds or seismic.

### 3.02 CONNECTIONS

- A. Install piping adjacent to equipment to allow service and maintenance.
- B. Vent Connection, Noncondensing, Gas-Fired Furnaces: Connect Type B vents to furnace vent connection and extend as required for fully functioning vent system.
- C. Connect ducts to furnace with flexible connector.
- D. Connect refrigerant tubing kits to refrigerant coil in furnace and to air-cooled, compressor-condenser unit.
  - 1. Soldered Joints: Apply ASTM B 813, water-flushable flux, unless otherwise indicated, to tube end. Construct joints according to ASTM B 828 or CDA's "Copper Tube Handbook," using lead-free solder alloy complying with ASTM B 32.
- E. Comply with requirements in Section 23 23 00 "Refrigerant Piping" for installation and joint construction of refrigerant piping.
- F. Complete installation and startup checks and start units according to manufacturer's written instructions.
- G. Verify proper operation of capacity control device.
- H. Adjust airflow and initial temperature set points.
- I. Set controls, burner, and other adjustments for optimum heating performance and efficiency. Adjust heat-distribution features, including shutters, dampers, and relays, to provide optimum heating performance and system efficiency.
- J. After completing installation, clean furnaces internally according to manufacturer's written instructions.
- K. Install new filters in each furnace at Substantial Completion.

### 3.03 FIELD QUALITY CONTROL

- A. Perform the following field tests and inspections and prepare test reports:
1. Perform electrical test and visual and mechanical inspection.
  2. Leak Test: After installation, charge systems with refrigerant and oil and test for leaks. Repair leaks replace lost refrigerant and oil, and retest until no leaks exist.
  3. Operational Test: After electrical circuitry has been energized, start units to confirm proper operation, product capability, and compliance with requirements.
  4. Verify that fan wheel is rotating in the correct direction and is not vibrating or binding.
  5. Test and adjust controls and safeties. Replace damaged and malfunctioning controls and equipment.
  6. Test airflows to verify speed is set to scheduled values. Contractor shall modify fan speed settings to provide scheduled CFM.
- B. Verify that vibration isolation and flexible connections properly dampen vibration transmission to structure.

END OF SECTION 23 54 00

## SECTION 26 00 00 – GENERAL PROVISIONS FOR ELECTRICAL

### PART 1 - GENERAL

#### 1.01 SCOPE

- A. Special Conditions section and General Requirements section are made part of this Division.
- B. This Division includes the sections, but not necessarily limited to, listed in the Division Table of Contents.

#### 1.02 GENERAL

- A. The work included in this division consists of furnishing all labor, equipment, transportation, excavation, backfill, supplies, material, appurtenances and services necessary for the satisfactory installation of the complete and operating Electrical System(s) indicated or specified in the Contract Documents.
- B. Any materials, labor, equipment or services not mentioned specifically herein which may be necessary to complete or perfect any part of the Electrical Systems in a substantial manner, in compliance with the requirements stated, implied or intended in the drawings and/or specifications, shall be included as part of this Contract.
- C. It is the intent of this Contract to deliver to the Owner's a "like new" project once work is complete. Although plans and specifications are complete to the extent possible, it shall be the responsibility of the Contractors involved to remove and/or relocate or re-attach any existing items which interfere with the new work required for the complete installation without additional cost to the Owner.

#### 1.03 INTENT

- A. It is the intention of the Contract Documents to call for finished work, tested and ready for operation.
- B. Details not usually shown or specified, but necessary for the proper installation and operation of systems, equipment, materials, etc., shall be included in the work, the same as if herein specified or indicated.

#### 1.04 EXAMINATION OF SITE AND CONDITIONS

- A. Each Proposer shall inform himself of all conditions under which the work is to be performed, the site of the work, the structure of the ground, above and below grade, the obstacles that may be encountered, the availability and location of necessary facilities and all relevant matters concerning the work. Each Proposer

shall also fully acquaint himself with all existing conditions as to ingress and egress, distance of haul from supply points, routes for transportation of materials, facilities and services, availability of utilities, etc. His proposal shall cover all expenses or disbursements in connection with such matters and conditions. No allowance will be made for lack of knowledge concerning such conditions after bids are accepted.

#### 1.05 DRAWINGS AND SPECIFICATIONS

- A. The drawings are diagrammatic only and indicate the general arrangement of the work to be followed. If deviations from the layouts are necessitated by field conditions, detailed layouts of the proposed departures shall be submitted to the Engineer for approval before proceeding with the work. The drawings are not intended to show every item, which may be necessary to complete the systems. All Proposers shall anticipate that additional items may be required and submit their bid accordingly.
- B. The drawings and specifications are intended to supplement each other. No Proposer shall take advantage of conflict between them, or between parties of either. Should this condition exist, the Proposer shall request a clarification not less than twelve days prior to the submission of the proposal so that the condition may be clarified by Addendum. In the event that such a condition arises after work is started, the interpretation of the Engineer shall be final.
- C. The drawings and specifications shall be considered to be cooperative and anything appearing in the specifications, which may not be indicated on the drawings or conversely, shall be considered as part of the Contract and must be executed the same as though indicated by both.
- D. The Contractor shall make all his own measurements in the field and shall be responsible for correct fitting. He shall coordinate this work with all other branches of work in such a manner as to cause a minimum of conflict or delay.
- E. The Engineer shall reserve the right to make adjustments in location of piping, ductwork, equipment, etc. where such adjustments are in the interest of improving the project.
- F. Should conflict or overlap (duplication) of work between the various trades become evident, this shall be called to the attention of the Engineer. In such event neither trade shall assume that he is to be relieved of the work which is specified under his branch until instructions in writing are received from the Engineer.
- G. Unless dimensioned, the drawings only indicate approximate locations. Dimensions given in figures on the drawings shall take precedence over scaled dimensions and all dimensions, whether given in figures or scaled, shall be verified in the field to insure no conflict with other work.
- H. Where on the Drawings a portion of the work is drawn out and the remainder is indicated in outline, or not indicated at all, the parts drawn out shall apply to all other like portions of the work. Where ornamentation or other detail is indicated by

starting only, such detail shall be continued throughout the courses or parts in which it occurs and shall also apply to all other similar parts of the work, unless otherwise indicated.

- I. Details not usually shown or specified, but necessary for the proper installation and operation of systems, equipment, materials, etc., shall be included in the work, the same as if herein specified or indicated.
- J. Where on the Contract Documents the word typical is used, it shall mean that the work method or means indicated as typical shall be repeated in and each time it occurs whether indicated or not.
- K. Special Note: Always check ceiling heights indicated on Architectural Drawings and Schedules and ensure that they may be maintained after all mechanical and electrical equipment is installed. Do not install equipment in the affected area until the conflict is resolved.

1.06 REVIEW OF CONTRACT DOCUMENTS AND FIELD CONDITIONS BY CONTRACTOR

- A. By execution of this Contract, the Contractor warrants that he has visited the site of the proposed work, and fully acquainted himself with the conditions there existing relating to construction and labor and that he fully understands the facilities, difficulties, and restrictions attending the execution of the work under Contract. The Contractor further warrants that he has thoroughly examined and is familiar with the drawings, specifications and all other documents comprising the Contract. The Contractor further warrants that by execution of this Contract, his failure, when he was bidding on this Contract, to receive or examine any form, instrument, or document, or to visit the site and acquaint himself with the conditions there existing, in no way relieves the Contractor. The Contractor agrees that the Owner shall be justified in rejecting any claim based on facts regarding conditions for which he should have been on prior notice.
- B. Before ordering material or performing any work, the Contractor shall verify all measurements at the work site. Any difference between dimensions on the Drawings and actual measurements shall be brought to the Engineer's attention for his consideration before the work may proceed. No extra compensation will be allowed because of difference between actual measurements and dimensions indicated on the Drawings. The Contractor shall assume full responsibility for accuracy of measurements obtained at the Work Site.
- C. Dimensions, which are lacking, shall be obtained from the Architect. In no case shall Drawings be scaled.
- D. All subcontractors shall familiarize themselves with all of the conditions relating to this Contract since the terms set forth in the General Conditions binds all subcontractors to the Contract.

#### 1.07 WORK LAYOUT

- A. This contractor shall layout his work from construction lines and levels established by the General Contractor and shall be responsible for the proper location and placement of his work.
- B. Maintain all benchmarks, monuments, and other reference points; replace as directed if disturbed or destroyed.

#### 1.08 PROTECTION OF STORED EQUIPMENT

- A. Provide suitable storage for, and completely protect all materials and equipment prior to installation. Storage shall be dry, clean and safe. Any materials or equipment damaged, deteriorated, rusted or defaced due to improper storage shall be fully repaired, refinished or replaced, as directed by the Engineer and any materials or equipment lost through theft or mishandling shall be replaced, all without additional cost to the Owner.

#### 1.09 COORDINATION BETWEEN TRADES

- A. Each Proposer shall review all drawings and specifications including Architectural, Mechanical, Electrical, Fire Protection, Landscaping, Structural, Surveys, etc., to ensure that the work he intends to provide does not encroach a conflict with or affect the work of others in any way. Where such effect does occur, it shall be the Proposer's responsibility to satisfactorily eliminate any such encroachment conflict or effect prior to the submission of his proposal. Each Proposer shall in particular ensure that there is adequate space to install his equipment and materials. Failure to do so shall result in the correction of such encroachment conflict or effect of any work awarded to the Proposer and shall be accomplished fully without expense to others and that they are reasonably accessible for maintenance. Check closely all mechanical and electrical closets, chases, ceiling voids, wall voids, crawl spaces, etc., to insure adequate spaces.
- B. It shall be the responsibility of this contractor to leave the necessary room for other trades. No extra compensation will be allowed to cover the cost of relocating conduit, boxes, etc., or equipment found encroaching on space required by others.

#### 1.10 EQUIPMENT CONNECTIONS AND WIRING

- A. This contractor shall make all electrical connections, etc., to equipment furnished by others whenever such equipment is shown on any part of the drawings or mentioned in any section of the specifications, unless otherwise specified.
- B. Supervision, to assure proper functioning and operation shall be provided by the trade furnishing the equipment or apparatus so connected.
- C. Unless otherwise specifically noted on the drawings or elsewhere in these specifications, all wiring shall be done by this contractor, including connections,

etc., to all equipment requiring electrical services furnished under other sections of this specification. This contractor shall furnish and install all disconnects, overload protection, motor control apparatus, etc., for all equipment unless otherwise specifically noted elsewhere as being provided with, or as a part of, the equipment.

#### 1.11 SUBSTITUTION OF MATERIALS AND EQUIPMENT

- A. When this contractor requests approval of substitute materials and/or equipment, except when under formal alternate proposal, it shall be understood and agreed that such substitution, if approved, will be made without cost to the Owner or Engineer, regardless of changes in connections, spacing, electrical services, etc. In all cases where substitutions affect other trades, the contractor offering such substitutions shall reimburse all affected contractors for all necessary changes in their work.

#### 1.12 CODES AND STANDARDS

- A. Pertinent Federal, State and Local requirements and regulations are hereby made part of this contract. In case of conflict between Contract Documents and above listed requirements, the latter shall govern. Requirements of authority having local jurisdiction shall supersede all other requirements. Use of the term "code" in sections of the specification refers to applicable requirements and regulations of above agencies.
- B. All electrical installation shall be made in accordance with the latest edition of the National Electrical Code and supplements in force at the time of bid opening, all materials employed shall bear Underwriters' official labels where such labeling is customary. In the event that local codes are more rigid than the National Electrical Code, both codes shall be considered as jointly governing and the requirements of either and/or both then prevail.
- C. Following is a list of abbreviations for codes and standards, which are referred to in the specifications. Where such reference is made, the code or standard becomes a part of the specification as if the code or standard were included herein. Reference is always to the latest edition of the code or standard unless otherwise specifically noted.

##### 1. Industry and Agency Standards, Codes and Specifications

ANSI - American National Standards Institution

ASTM - American Society of Testing and Materials

NBFU - National Board of Fire Underwriters'

NBS - National Bureau of Standards

NEMA - National Electrical Manufacturers Association

UL - Underwriters' Laboratories

NEC - National Electrical Code

NESC - National Electrical Safety Code

IPCEA - Insulated Power Cable Engineers Association

IEEE - Institute of Electrical and Electronics Engineers

- D. Compliance with the Occupational Safety and Health Act shall be the responsibility of the contractor and under no circumstances shall the Engineer/Architect be an authority or be held responsible for any acts concerning this regulation.

#### 1.13 MATERIALS AND EQUIPMENT

- A. General. Material and equipment shall be furnished as specified in this section and in each individual electrical section of these specifications and shall be in strict accordance with the required ANSI, ASTM, NEMA, IPCEA, UL, NEC, or other recognized standards, codes and specifications listed. Applicable codes, standards and manufacturers' products referred to in these specifications shall establish minimum requirements for material, equipment and installation furnished.
- B. Bolting shall be carbon steel conforming to ASTM A-307 with heavy hexagonal nut.
- C. Angles, Channels, Beams, Bars and Rods shall be steel conforming to ASTM A-36.

#### 1.14 INSTALLATION

- A. Installation of all electrical equipment for the project as specified in these specifications and indicated on the drawings shall be in accordance with the general requirements of this section. Additional installation requirements applicable to individual systems are specified in the specific system section.
- B. All equipment shall be installed at locations indicated on the drawings and as specified herein.
- C. Assembly and installation of equipment shall be in strict accordance with manufacturer's installation instructions.
- D. Equipment shall be securely anchored in place. Care shall be exercised to correctly orient equipment before securing in place.
- E. All equipment and material shall meet the minimum requirements of seismic bracing as governed by the authority having jurisdiction.



#### 1.15 OBSOLETE OR REMOVED EQUIPMENT AND MATERIALS

- A. The Electrical Contractor shall remove all existing materials and equipment made obsolete by, and interfering with the additions, alterations, or razing as shown on the plans and specified. Maintain such existing equipment and materials intact and in existing condition insofar as possible.
- B. Unless otherwise specifically stated in the specifications or shown on the drawings, all such removed material and equipment, not to be reused, shall be removed from the site and disposed of in a proper manner.

#### 1.16 CONTINUOUS OPERATION AND CUT-OVER

- A. The present services, facilities, or equipment shall be left intact until such time that the new permanent installation is completed, or temporary means provided for continuous operation.
- B. All new services, equipment, etc., for the new installation shall be installed complete to a point of connection before attempting to make new connections.
- C. To facilitate the continuous operation of the system and building, the cut-over work shall be done at off-peak periods. Such periods to be arranged by conference between the Contractor, Owner and the Engineer. All contractors shall rigidly adhere to the program so determined.
- D. All material installed shall meet the minimum requirements of the Local Code for seismic bracing and be installed in such a manner suitable for the seismic zone which applies.

#### 1.17 TESTS

- A. Following the completion of all wiring installation, test the individual systems and eliminate any existing grounding of potential conductors, short circuits, other faults, etc.

#### 1.18 PERMITS, FEES AND CERTIFICATES

- A. Each respective contractor shall obtain and pay all permits and licenses required by Federal, State and Local Ordinances for his type work. All fees in connection with inspections, permits, licenses and approvals shall be paid by the contractor whose work is affected.

#### 1.19 ELECTRICAL INSPECTION FOR CONTRACT COMPLIANCE

- A. The contractor shall be responsible for obtaining and coordination of required electrical inspections and any fees and charges associated with the inspections. Inspections shall be made by an Electrical Inspector Certified by the authority

having jurisdiction. The contractor shall furnish the Engineer and Owner a copy of the Electrical Certificate of approval before final payment will be made.

#### 1.20 PROJECT CLEAN-UP

- A. The Contractor shall export off site, all debris resulting from work under this Division. Burning of debris at the project site is not permitted.
- B. Each contractor shall maintain his portion of this project in a neat and orderly fashion, disposing of debris, cartons, crates and boxes as the contents are installed in the project. This clean-up shall be accomplished each day in order not to create hardships on the other trades.

#### 1.21 GUARANTEES AND WARRANTIES

- A. This Contractor shall guarantee all equipment, apparatus, materials and workmanship entering into this contract to be the best of its respective kind, and shall replace all parts at his own expense, which have been proven defective, within one year from final acceptance of the work by the Owner. Items of equipment, which may have longer guarantees, shall have warranties and guarantees completed, in order, and in effect at the time of final acceptance of the work by the Architect. This contractor shall furnish all such warranties and guarantees at the time of final acceptance of the work.

#### 1.22 SHOP DRAWINGS AND OTHER RELATED SUBMITTALS

- A. The type of submittal information required for each item of equipment is scheduled at the end of this section. Unless noted otherwise, submittals shall be furnished in electronic format. The Contractor shall furnish a single pdf file for each submittal. Submittals shall be clearly labeled as to what is contained within and shall note the related Specification Section. The Contractor shall be responsible for providing a numbering convention for submittals to allow easy tracking of submittals.
- B. Submittals for color selections shall not be electronically submitted. Provide hard copies of the colors. Printed color selections are not acceptable.
- C. Unless otherwise specified, materials and equipment must be a standard product of manufacturers regularly engaged in production of such items.
  - 1. The contractor shall secure right to use any patented article, method or apparatus used in work.
  - 2. When substitute item of equipment has been submitted for approval, the mechanical contractor shall submit layout drawings indicating the changes necessary to adapt the substitute item of equipment to the design, when requested by the Engineer. All cost of the requested drawings shall be the responsibility of the contractor offering the substitutions.
  - 3. Under no circumstances will materials be considered for substitution, which are not a product of a manufacturer regularly engaged in production of such material

or which is a product of one who merely assembles products of other manufacturers into fabricated units. Material submitted for substitution shall be subject to express and implied warranties of one manufacturer only.

- D. If substitution of material results in incidental extra costs on part of any trade under contract, such costs shall be borne by contractor desiring substitution.
1. Submittal data shall include specification data, such as metal gauges, finishes, optional accessories, etc., even though such equipment and materials may be detailed on the drawings or specified. In addition, the submittal data shall include performance (certification) data, wiring diagrams where applicable, accurate dimensional data and a recommended spare parts list. Outline or dimensional drawings alone are not acceptable.
  2. No roughing-in connections, etc., shall be done until approved equipment submittals are in the hands of the contractors. It shall be the contractor's responsibility to obtain approved drawings and to make all connections, etc., in the neatest and most workmanlike manner possible. Each contractor shall coordinate with all other contractors having any connections, roughing-in, etc., to the equipment.
  3. In general, normal catalog information (with the particular items underlined or otherwise denoted as being the submitted item) will be acceptable as submittal data. Installation, operating and maintenance instructions must be that information, specifically applicable to the item furnished, ordinarily supplied with the equipment to the owner with any modifications indicated. Wiring diagrams must be correct for the application. Generalized wiring diagrams, showing alternate methods of connection, will not be acceptable unless all unrelated sections are marked out.
  4. Submittal data sheets, which indicate several different model numbers, figure numbers, optional accessories, installation arrangements, etc., shall be clearly marked to indicate the specific items of equipment to be furnished. Samples and certificates shall be furnished as requested. Submittal data must be complete for each piece of equipment; piecemeal data will not be processed.
  5. It shall be noted that approval of shop drawings by the Engineer applies only to general design, arrangement, type, capacity and quality. Such approval doesn't apply to quantities, dimensions, connection locations and the like. In all cases, the contractor alone shall be responsible for furnishing the proper quantity of equipment and/or materials required, that all equipment fits the available space in a satisfactory manner, and that all connections are suitably located.
  6. Before the project is accepted, all submittal data (shop drawings, etc.) must be complete and approved.
  7. In addition to shop drawings described above, the following information is required of the contractor to be furnished to the Engineer.

1.23 ELECTRICAL DOCUMENT REQUIREMENTS

ITEM OR DESCRIPTION OF EQUIPMENT REQUIRING SHOP DRAWINGS	P A R T S	L I S T	O P E R A T I N G	M A N U A L	W I R I N G	D I A G R A M	C E R T I F I C A T I O N	S A M P L E S
Disconnect Switches and Breakers							X	
Metal "While In Use" device cover								
GFIC duplex Receptacles								

#### 1.24 OPERATION AND MAINTENANCE DATA

- A. The Contractor shall submit a single copy of the Operation and Maintenance Manuals prior to final completion.
- B. Operation and Maintenance Manuals (O&M's) shall be submitted in electronic format. Provide one pdf file per Specification Division.
- C. Prepare pdf files with the title for each file to include the Specification Division Number and brief description of contents (example: "Division 23 – HVAC Equipment").
- D. The first page of pdf file shall be a coversheet titled "Operation and Maintenance Manual". Include table of contents with page numbers. Provide bookmarks within the pdf file labeled for each section contained within the file.
- E. Include the following within O&M's
  - 1. Part 1: Directory, listing names, addresses, and telephone numbers of Architect/Engineer, Contractor, Subcontractors, and major equipment suppliers.
  - 2. Part 2: Operation and maintenance instructions, arranged by system and subdivided. For each category, identify names, addresses, and telephone numbers of subcontractors and suppliers. Identify the following:
    - a. Significant design criteria.
    - b. List of equipment
    - c. Parts list for each component.
    - d. Operating instructions.
    - e. Maintenance instructions for equipment and systems.
    - f. Maintenance instructions for special finishes, including recommended cleaning methods and materials and special precautions identifying detrimental agents.
  - 3. Part 3: Project documents and certificates, including the following:
    - a. Shop drawings and product data.
    - b. Power quality test results (including any required grounding tests).
    - c. Certificates.
    - d. Photocopies of warranties and bonds.
- F. Submit one copy of completed pdf's in final form on DVD or solid-state media fifteen (15) days prior to final inspection. This copy will be returned after final inspection with Owner's comments. Revise content of documents as required prior to final submittal.
- G. Submit final pdf's revised within ten (10) days after final inspection. Provide at minimum three (3) DVD or solid-state copies.

## 1.25 TRAINING/INSTRUCTION

- A. General Operating/Maintenance Instruction: Arrange for each installer of work requiring continuing maintenance or operation, to meet with the Owner's personnel, at project site, to provide basic instructions needed for proper operation and maintenance of entire work. Include instructions by manufacturer's representatives where installers are not expert in the required procedures. Review maintenance manuals, record documentations, tools, spare parts and materials, lubricants, fuels, identification system, control sequences, hazards, cleaning and similar procedures and facilities. For operational equipment, demonstrate start-up, shutdown, emergency operations, noise and vibration adjustments, safety, economy/efficiency adjustments, energy effectiveness, and similar operations. Review maintenance and operations in relation with applicable Warranties, Agreements to Maintain, Bonds, and similar continuing commitments.
- B. Program Structure: Develop an instruction program that includes individual training modules for each system and equipment not part of a system, as required by individual Specification Sections.
- C. Training Modules: Develop a learning objective and teaching outline for each module. Include description of specific skills and knowledge that participant is expected to master. For each module, include instruction for the following:
  - 1. Basis of System Design, Operational Requirements, and Criteria: Include system and equipment descriptions, operating standards, regulatory requirements, equipment function, operating characteristics, limiting conditions, and performance curves.
  - 2. Documentation: Review emergency, operations, and maintenance manuals; Project Record Documents; identification systems; warranties and bonds; and maintenance service agreements.
  - 3. Emergencies: Include instructions on stopping; shutdown instructions; operating instructions for conditions outside normal operating limits; instructions on meaning of warnings, trouble indications, and error messages; and required sequences for electric or electronic systems.
  - 4. Operations: Include startup, break-in, control, and safety procedures; stopping and normal shutdown instructions; routine, normal, seasonal, and weekend operating instructions; operating procedures for emergencies and equipment failure; and required sequences for electric or electronic systems.
  - 5. Adjustments: Include alignments and checking, noise, vibration, economy, and efficiency adjustments.
  - 6. Troubleshooting: Include diagnostic instructions and test and inspection procedures.
  - 7. Maintenance: Include inspection procedures, types of cleaning agents, methods of cleaning, procedures for preventive and routine maintenance, and instruction on use of special tools.
  - 8. Repairs: Include diagnosis, repair, and disassembly instructions; instructions for identifying parts; and review of spare parts needed for operation and maintenance.

**PART 2 - PRODUCTS (NOT USED)**

**PART 3 - EXECUTION (NOT USED)**

END OF SECTION 26 00 00





## SECTION 26 05 00 - COMMON WORK RESULTS FOR ELECTRICAL

### PART 1 - GENERAL

#### 1.01 SUMMARY

A. Section Includes:

1. Sleeves for raceways and cables.
2. Sleeve seals.
3. Grout.
4. Common electrical installation requirements.

#### 1.02 SUBMITTALS

- A. Product Data: For sleeve seals.

### PART 2 - PRODUCTS

#### 2.01 SLEEVES FOR RACEWAYS AND CABLES

- A. Steel Pipe Sleeves: ASTM A 53/A 53M, Type E, Grade B, Schedule 40, galvanized steel, plain ends.

- B. Sleeves for Rectangular Openings: Galvanized sheet steel.

1. Minimum Metal Thickness:

- a. For sleeve cross-section rectangle perimeter less than 50 inches and no side more than 16 inches, thickness shall be 0.052 inch.
- b. For sleeve cross-section rectangle perimeter equal to, or more than, 50 inches and 1 or more sides equal to, or more than, 16 inches, thickness shall be 0.138 inch.

#### 2.02 GROUT

- A. Nonmetallic, Shrinkage-Resistant Grout: ASTM C 1107, factory-packaged, nonmetallic aggregate grout, noncorrosive, nonstaining, mixed with water to consistency suitable for application and a 30-minute working time.

### **PART 3 - EXECUTION**

#### **3.01 COMMON REQUIREMENTS FOR ELECTRICAL INSTALLATION**

- A. Comply with NECA 1.
- B. Measure indicated mounting heights to bottom of unit for suspended items and to center of unit for wall-mounting items.
- C. Comply with all requirements of N.E.C. article 110 and others, which apply.
- D. Headroom Maintenance: If mounting heights or other location criteria are not indicated, arrange and install components and equipment to provide maximum possible headroom consistent with these requirements.
- E. Equipment: Install to facilitate service, maintenance, and repair or replacement of components of both electrical equipment and other nearby installations. Connect in such a way as to facilitate future disconnecting with minimum interference with other items in the vicinity.
- F. Right of Way: Give to piping systems installed at a required slope.

#### **3.02 SLEEVE INSTALLATION FOR ELECTRICAL PENETRATIONS**

- A. Electrical penetrations occur when raceways, cables, wireways, cable trays, or busways penetrate concrete slabs, concrete or masonry walls, or fire-rated floor and wall assemblies.
- B. Concrete Slabs and Walls: Install sleeves for penetrations unless core-drilled holes or formed openings are used. Install sleeves during erection of slabs and walls.
- C. Use pipe sleeves unless penetration arrangement requires rectangular sleeved opening.
- D. Fire-Rated Assemblies: Install sleeves for penetrations of fire-rated floor and wall assemblies unless openings compatible with firestop system used are fabricated during construction of floor or wall.
- E. Cut sleeves to length for mounting flush with both surfaces of walls.
- F. Extend sleeves installed in floors 2 inches above finished floor level.
- G. Size pipe sleeves to provide 1/4-inch annular clear space between sleeve and raceway or cable, unless indicated otherwise.
- H. Seal space outside of sleeves with grout for penetrations of concrete and masonry
  - 1. Promptly pack grout solidly between sleeve and wall so no voids remain. Tool exposed surfaces smooth; protect grout while curing.

- I. Interior Penetrations of Non-Fire-Rated Walls and Floors: Seal annular space between sleeve and raceway or cable, using joint sealant appropriate for size, depth, and location of joint. Comply with requirements in other sections of this specification or as indicated on the drawings.
- J. Fire-Rated-Assembly Penetrations: Maintain indicated fire rating of walls, partitions, ceilings, and floors at raceway and cable penetrations. Install sleeves and seal raceway and cable penetration sleeves with firestop materials. Comply with requirements in other sections of this specification or as indicated on the drawings.
- K. Roof-Penetration Sleeves: Seal penetration of individual raceways and cables with architectural approved means or flexible boot-type flashing units applied in coordination with roofing work.
- L. Aboveground, Exterior-Wall Penetrations: Seal penetrations using steel pipe sleeves and mechanical sleeve seals. Select sleeve size to allow for 1-inch annular clear space between pipe and sleeve for installing mechanical sleeve seals.

### 3.03 FIRESTOPPING

- A. Apply firestopping to penetrations of fire-rated floor and wall assemblies for electrical installations to restore original fire-resistance rating of assembly. Firestopping materials and installation requirements are specified in "Penetration Firestopping."

END OF SECTION 26 05 00



## **SECTION 26 05 19 – LOW-VOLTAGE ELECTRICAL POWER CONDUCTORS AND CABLES**

### **PART 1 - GENERAL**

#### **1.01 SUMMARY**

A. This Section includes the following:

1. Building wires and cables rated 600 V and less.
2. Connectors, splices, and terminations rated 600 V and less.

#### **1.02 SUBMITTALS**

- A. Product Data: For each type of product indicated.
- B. Field quality-control test reports.

#### **1.03 QUALITY ASSURANCE**

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
- B. Comply with NFPA 70.

### **PART 2 - PRODUCTS**

#### **2.01 CONDUCTORS AND CABLES**

- A. Copper Conductors: Comply with NEMA WC 70.
- B. Conductor Insulation: Comply with NEMA WC 70 for Types THHN-THWN.

#### **2.02 CONNECTORS AND SPLICES**

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
1. AFC Cable Systems, Inc.
  2. Hubbell Power Systems, Inc.
  3. O-Z/Gedney; EGS Electrical Group LLC.
  4. 3M; Electrical Products Division.

5. Tyco Electronics Corp.

- B. Description: Factory-fabricated connectors and splices of size, ampacity rating, material, type, and class for application and service indicated.

## 2.03 SLEEVES FOR CABLES

- A. Steel Pipe Sleeves: ASTM A 53/A 53M, Type E, Grade B, Schedule 40, galvanized steel, plain ends.
- B. Cast-Iron Pipe Sleeves: Cast or fabricated "wall pipe," equivalent to ductile-iron pressure pipe, with plain ends and integral waterstop, unless otherwise indicated.
- C. Coordinate sleeve selection and application with selection and application of firestopping specified in Division 7 Section "Through-Penetration Firestop Systems."

## 2.04 SLEEVE SEALS

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
- B. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
1. Advance Products & Systems, Inc.
  2. Calpico, Inc.
  3. Metraflex Co.
  4. Pipeline Seal and Insulator, Inc.
- C. Description: Modular sealing device, designed for field assembly, to fill annular space between sleeve and cable.
1. Sealing Elements: EPDM interlocking links shaped to fit surface of cable or conduit. Include type and number required for material and size of raceway or cable.

## **PART 3 - EXECUTION**

### 3.01 CONDUCTOR MATERIAL APPLICATIONS

- A. Branch Circuits: Copper. stranded for branch circuits in raceway.

3.02 CONDUCTOR INSULATION AND MULTICONDUCTOR CABLE APPLICATIONS AND WIRING METHODS

- A. Branch Circuits Concealed in Ceilings, Walls, and Partitions: Type THHN-THWN, in raceway.
- B. Branch Circuits exposed outdoors, indoors: Type THHN-THWN, single conductors in raceway.
- C. Class 1 Control Circuits: Type THHN-THWN, in raceway.
- D. Class 2 Control Circuits: Power-limited cable, concealed in building finishes.

3.03 INSTALLATION OF CONDUCTORS AND CABLES

- A. Conceal cables in finished walls, ceilings, and floors, unless otherwise indicated.
- B. Use manufacturer-approved pulling compound or lubricant where necessary; compound used must not deteriorate conductor or insulation. Do not exceed manufacturer's recommended maximum pulling tensions and sidewall pressure values.
- C. Use pulling means, including fish tape, cable, rope, and basket-weave wire/cable grips, that will not damage cables or raceway.
- D. Tighten electrical connectors and terminals according to manufacturer's published torque-tightening values. If manufacturer's torque values are not indicated, use those specified in UL 486A and UL 486B.
- E. Make splices and taps that are compatible with conductor material and that possess equivalent or better mechanical strength and insulation ratings than un-spliced conductors.
  - 1. Use oxide inhibitor in each splice and tap conductor for aluminum conductors.
- F. Wiring at Outlets: Install conductor at each outlet, with at least 6 inches of slack.

END OF SECTION 26 05 19





## **SECTION 26 05 26 - GROUNDING AND BONDING FOR ELECTRICAL SYSTEMS**

### **PART 1 - GENERAL**

#### 1.01 SUMMARY

- A. Section Includes: Grounding systems and equipment.

#### 1.02 SUBMITTALS

- A. Product Data: For each type of product indicated.

#### 1.03 QUALITY ASSURANCE

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- B. Comply with UL 467 for grounding and bonding materials and equipment.

### **PART 2 - PRODUCTS**

#### 2.01 CONDUCTORS

- A. Insulated Conductors: Copper wire or cable insulated for 600 V unless otherwise required by applicable Code or authorities having jurisdiction.
- B. Bare Copper Conductors:
  - 1. Solid Conductors: ASTM B 3.
  - 2. Stranded Conductors: ASTM B 8.

#### 2.02 CONNECTORS

- A. Listed and labeled by an NRTL acceptable to authorities having jurisdiction for applications in which used and for specific types, sizes, and combinations of conductors and other items connected.

### **PART 3 - EXECUTION**

#### **3.01 APPLICATIONS**

- A. Conductors: Install stranded conductors for branch circuits unless otherwise indicated.

#### **3.02 EQUIPMENT GROUNDING**

- A. Install insulated equipment grounding conductors with the following items, in addition to those required by NFPA 70:
  - 1. Feeders and branch circuits.
  - 2. Receptacle circuits.
  - 3. Single-phase motor and appliance branch circuits.
  - 4. Flexible raceway runs.

#### **3.03 INSTALLATION**

- A. Grounding Conductors: Route along shortest and straightest paths possible unless otherwise indicated or required by Code. Avoid obstructing access or placing conductors where they may be subjected to strain, impact, or damage.

#### **3.04 LABELING**

- A. Comply with requirements in Division 26 Section "Electrical Identification" Article for instruction signs. The label or its text shall be green.

#### **3.05 FIELD QUALITY CONTROL**

- A. Perform the following tests and inspections and prepare test reports:
  - 1. After installing grounding system but before permanent electrical circuits have been energized, test for compliance with requirements.
  - 2. Inspect physical and mechanical condition. Verify tightness of accessible, bolted, electrical connections with a calibrated torque wrench according to manufacturer's written instructions.

END OF SECTION 26 05 26

## **SECTION 26 05 33 - RACEWAYS AND BOXES FOR ELECTRICAL SYSTEMS**

### **PART 1 - GENERAL**

#### **1.01 SUMMARY**

- A. This Section includes raceways, fittings, boxes, enclosures, and cabinets for electrical wiring.

#### **1.02 SUBMITTALS**

- A. Product Data: For wireways and fittings, hinged-cover enclosures, and cabinets.

#### **1.03 QUALITY ASSURANCE**

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
- B. Comply with NFPA 70.

### **PART 2 - PRODUCTS**

#### **2.01 METAL CONDUIT AND TUBING**

- A. Rigid Steel Conduit: ANSI C80.1.
- B. EMT: ANSI C80.3.
- C. FMC: Zinc-coated steel.
- D. LFMC: Flexible steel conduit with PVC jacket.
- E. Fittings for Conduit (Including all Types and Flexible and Liquidtight), EMT, and Cable: NEMA FB 1; listed for type and size raceway with which used, and for application and environment in which installed.

#### **2.02 BOXES, ENCLOSURES, AND CABINETS**

- A. Sheet Metal Outlet and Device Boxes: NEMA OS 1.
- B. Cast-Metal Outlet and Device Boxes: NEMA FB 1, aluminum, Type FD, with gasketed cover.

- C. Small Sheet Metal Pull and Junction Boxes: NEMA OS 1.

### **PART 3 - EXECUTION**

#### **3.01 RACEWAY APPLICATION**

- A. Outdoors: Apply raceway products as specified below, unless otherwise indicated:
1. Exposed Conduit: Rigid steel conduit.
  2. Concealed Conduit, Aboveground: Rigid steel conduit.
  3. Connection to Vibrating Equipment (Including Transformers and Hydraulic, Pneumatic, Electric Solenoid, or Motor-Driven Equipment): LFMC.
  4. Boxes and Enclosures, Aboveground: NEMA 250, Type 3R.
- B. Comply with the following indoor applications, unless otherwise indicated:
1. Dry locations: EMT
  2. Connection to Vibrating Equipment (Including Transformers and Hydraulic, Pneumatic, Electric Solenoid, or Motor-Driven Equipment): FMC, except use LFMC in damp or wet locations.
  3. Damp or Wet Locations: Rigid steel conduit.
- C. Minimum Raceway Size: 1/2-inch trade size.
- D. Raceway Fittings: Compatible with raceways and suitable for use and location.
1. Rigid Steel Conduit: Use threaded rigid steel conduit fittings, unless otherwise indicated.

#### **3.02 INSTALLATION**

- A. Comply with NECA 1 for installation requirements applicable to products specified in Part 2 except where requirements on Drawings or in this Article are stricter.
- B. Keep raceways at least 6 inches away from parallel runs of flues and steam or hot-water pipes. Install horizontal raceway runs above water and steam piping.
- C. Complete raceway installation before starting conductor installation.
- D. Arrange stub-ups so curved portions of bends are not visible above the finished slab.
- E. Install no more than the equivalent of three 90-degree bends in any conduit run except for communications conduits, for which fewer bends are allowed.
- F. Conceal conduit within finished walls, ceilings, and floors, unless otherwise indicated.

- G. Raceway Terminations at Locations Subject to Moisture or Vibration: Use insulating bushings to protect conductors, including conductors smaller than No. 4 AWG.
- H. Install pull wires in empty raceways. Use polypropylene or monofilament plastic line with not less than 200-lb tensile strength. Leave at least 12 inches of slack at each end of pull wire.
- I. Flexible Conduit Connections: Use maximum of 72 inches of flexible conduit for equipment subject to vibration, noise transmission, or movement; and for transformers and motors.
  - 1. Use LFMC in damp or wet locations subject to severe physical damage.

END OF SECTION 26 05 33



## **SECTION 26 28 16 - ENCLOSED SWITCHES AND CIRCUIT BREAKERS**

### **PART 1 - GENERAL**

#### 1.01 SUMMARY

- A. Section Includes:
  - 1. Non-fusible switches.
  - 2. Molded-case circuit breakers (MCCBs).
  - 3. Enclosures.

#### 1.02 SUBMITTALS

- A. Product Data: For each type of enclosed switch, circuit breaker, accessory, and component indicated.
- B. Shop Drawings: For enclosed switches and circuit breakers. Include plans, elevations, sections, details, and attachments to other work.
  - 1. Wiring Diagrams: For power, signal, and control wiring.
- C. Field quality-control reports.
- D. Operation and maintenance data.

#### 1.03 QUALITY ASSURANCE

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- B. Comply with NFPA 70.

### **PART 2 - PRODUCTS**

#### 2.01 NON-FUSIBLE SWITCHES

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
  - 1. Eaton Electrical Inc.; Cutler-Hammer Business Unit.
  - 2. General Electric Company; GE Consumer & Industrial - Electrical Distribution.
  - 3. Siemens Energy & Automation, Inc.

4. Square D; a brand of Schneider Electric.

B. Type GD, General Duty, Single Throw, 600 A and Smaller: UL 98 and NEMA KS 1, horsepower rated, lockable handle with capability to accept two padlocks, and interlocked with cover in closed position. Suitable and listed for the environment installed in.

C. Accessories:

1. Equipment Ground Kit: Internally mounted and labeled for copper and aluminum ground conductors.

2. Neutral Kit: Internally mounted; insulated, capable of being grounded and bonded; labeled for copper and aluminum neutral conductors.

3. Lugs: Suitable for number, size, and conductor material.

## 2.02 MOLDED-CASE CIRCUIT BREAKERS

A. Manufacturers: Subject to compliance with requirements, provide products by one of the following available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:

1. Eaton Electrical Inc.; Cutler-Hammer Business Unit.

2. General Electric Company; GE Consumer & Industrial - Electrical Distribution.

3. Siemens Energy & Automation, Inc.

4. Square D; a brand of Schneider Electric.

B. General Requirements: Comply with UL 489, NEMA AB 1, and NEMA AB 3, with interrupting capacity to comply with available fault currents.

C. Thermal-Magnetic Circuit Breakers: Inverse time-current element for low-level overloads and instantaneous magnetic trip element for short circuits. Adjustable magnetic trip setting for circuit-breaker frame sizes 250 A and larger. GFCI and AFCI as applicable for the connected load per N.E.C.

D. Features and Accessories:

1. Standard frame sizes, trip ratings, and number of poles.

2. Lugs: Suitable for number, size, trip ratings, and conductor material.

3. Application Listing: Appropriate for application.

## 2.03 ENCLOSURES

A. Enclosed Switches and Circuit Breakers: NEMA AB 1, NEMA KS 1, NEMA 250, and UL 50, to comply with environmental conditions at installed location.

1. Indoor, Dry and Clean Locations: NEMA 250, Type 1.

2. Outdoor Locations: NEMA 250, Type 3R.



**PART 3 - EXECUTION**

3.01 INSTALLATION

- A. Install individual wall-mounted switches and circuit breakers with tops at uniform height unless otherwise indicated.
- B. Comply with NECA 1.

3.02 IDENTIFICATION

- A. Label each enclosure with Arc-Flash and Shock Hazard Warning.

END OF SECTION 26 28 16



## SECTION 31 10 00 - SITE CLEARING

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Protecting existing vegetation to remain.
  - 2. Removing existing vegetation.
  - 3. Clearing and grubbing.

#### 1.3 DEFINITIONS

- A. Topsoil: Top layer of the soil profile consisting of existing native surface topsoil or existing in-place surface soil; the zone where plant roots grow.
- B. Vegetation: Trees, shrubs, groundcovers, grass, and other plants.

#### 1.4 MATERIAL OWNERSHIP

- A. Except for materials indicated to be stockpiled or otherwise remain Owner's property, cleared materials shall become Contractor's property and shall be removed from Project site.

#### 1.5 FIELD CONDITIONS

- A. Traffic: Minimize interference with adjoining roads, streets, walks, and other adjacent occupied or used facilities during site-clearing operations.
  - 1. Do not close or obstruct streets, walks, or other adjacent occupied or used facilities without permission from Owner and authorities having jurisdiction.
- B. Soil Stripping and Handling: Perform only when the soil is dry or slightly moist.

## **PART 2 - PRODUCTS**

NOT USED

## **PART 3 - EXECUTION**

### **3.1 PREPARATION**

- A. Verify that trees, shrubs, and other vegetation to remain have been flagged.
- B. Protect existing site improvements to remain from damage during construction.
  - 1. Restore damaged improvements to their original condition, as acceptable to Owner.

### **3.2 TEMPORARY EROSION AND SEDIMENTATION CONTROL**

- A. Provide temporary erosion- and sedimentation-control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to erosion- and sedimentation-control Drawings and requirements of authorities having jurisdiction.
- B. Verify that flows of water redirected from construction areas or generated by construction activity do not enter or cross protection zones.
- C. Inspect, maintain, and repair erosion- and sedimentation-control measures during construction until permanent vegetation has been established.
- D. Remove erosion and sedimentation controls, and restore and stabilize areas disturbed during removal.

### **3.3 TREE AND PLANT PROTECTION**

- A. Protect trees and plants remaining on-site.
- B. Repair or replace trees, shrubs, and other vegetation indicated to remain or be relocated that are damaged by construction operations.

### **3.4 EXISTING UTILITIES**

- A. Interrupting Existing Utilities: Do not interrupt utilities serving facilities occupied by Owner or others, unless permitted under the following conditions and then only after arranging to provide temporary utility services according to requirements indicated:

1. Notify Architect not less than two days in advance of proposed utility interruptions.
2. Do not proceed with utility interruptions without Architect's written permission.

### 3.5 CLEARING AND GRUBBING

- A. Remove obstructions, trees, shrubs, and other vegetation to permit installation of new construction.
  1. Do not remove trees, shrubs, and other vegetation indicated to remain.
  2. Grind down stumps and remove roots larger than 2 inches in diameter, obstructions, and debris to a depth of 18 inches below exposed subgrade.
  3. Chip removed tree branches and dispose of off-site.
- B. Fill depressions caused by clearing and grubbing operations with satisfactory soil material unless further excavation or earthwork is indicated.
  1. Place fill material in horizontal layers not exceeding a loose depth of 8 inches, and compact each layer to a density equal to adjacent original ground.

### 3.6 TOPSOIL STRIPPING

- A. Remove sod and grass before stripping topsoil.
- B. Strip topsoil to depth of 6 inches in a manner to prevent intermingling with underlying subsoil or other waste materials.

### 3.7 SITE IMPROVEMENTS

- A. Remove existing above- and below-grade improvements as indicated and necessary to facilitate new construction.
- B. Remove slabs, paving, curbs, gutters, and aggregate base as indicated.
  1. Unless existing full-depth joints coincide with line of demolition, neatly saw-cut along line of existing pavement to remain before removing adjacent existing pavement. Saw-cut faces vertically.

### 3.8 DISPOSAL OF SURPLUS AND WASTE MATERIALS

- A. Remove soil material, obstructions, demolished materials, and waste materials including trash and debris, and legally dispose of them off Owner's property.

END OF SECTION 31 10 00



## SECTION 32 31 13 - CHAIN LINK FENCES

### PART 1 - GENERAL

#### 1.1 SUMMARY

- A. Section includes chain-link fences and swing gates.
- B. Related Requirements:
  - 1. Section 03 30 53 "Miscellaneous Cast-in-Place Concrete" for cast-in-place concrete post footings.

#### 1.2 SUBMITTALS

- A. Product Data: For each type of product indicated
  - 1. Include construction details, material descriptions, dimensions of individual components and profiles, and finishes for the following:
    - a. Fence posts, rails, and fittings.
    - b. Chain-link fabric, reinforcements, and attachments.
- B. Shop Drawings: For each type of fence and gate assembly.
  - 1. Include plans, elevations, sections, details, and attachments to other work.
  - 2. Include accessories, hardware, and operational clearances.
- C. Product Certificates: For each type of chain-link fence.
- D. Product Test Reports: For framework strength according to ASTM F 1043, for tests performed by manufacturer and witnessed by a qualified testing agency or a qualified testing agency.

#### 1.3 WARRANTY

- A. Special Warranty: Manufacturer's standard form in which manufacturer agrees to repair or replace components of chain-link fences that fail in materials or workmanship within specified warranty period.
  - 1. Failures include, but are not limited to, deterioration of metals, metal finishes, and other materials beyond normal weathering.
  - 2. Warranty Period: Five years from date of Substantial Completion.

## **PART 2 - PRODUCTS**

### **2.1 CHAIN-LINK FENCE FABRIC**

- A. General: Provide fabric in one-piece heights measured between top and bottom of outer edge of selvage knuckle or twist. Comply with CLFMI Product Manual and with requirements indicated below:
  - 1. Fabric Height: 84 inches.
  - 2. Steel Wire Fabric: Wire with a diameter of 0.113 inch.
    - a. Mesh Size: 2-1/8 inches.
    - b. Zinc-Coated Fabric: ASTM A 3921, Type II, Class 1, 1.2 oz./sq. ft. with zinc coating applied after weaving.
  - 3. Selvage: Twisted top and knuckled bottom.

### **2.2 FENCE FRAMING**

- A. Posts and Rails: Comply with ASTM F 1043 for framing, including rails, braces, and line; terminal; and corner posts. Provide members with minimum dimensions and wall thickness according to ASTM F 1043 based on the following:
  - 1. Fence Height: 84 inches.
  - 2. Light Industrial Strength: Material Group IC-L, round steel pipe, electric-resistance-welded pipe
    - a. Line Post: 2.375 inches in diameter.
    - b. End, Corner and Pull Post: 2.875 inches in diameter.
  - 3. Horizontal Framework Members: Top rails complying with ASTM F 1043.
    - a. Top Rail: 1.66 inches in diameter.
  - 4. Brace Rails: ASTM F1043.
  - 5. Metallic Coating for Steel Framework:
    - a. Type A: Not less than minimum 2.0-oz./sq. ft. average zinc coating according to ASTM A 123/A 123M.

### **2.3 TENSION WIRE**

- A. Metallic-Coated Steel Wire: 0.177-inch diameter, marcelled tension wire complying with ASTM A 817 and ASTM A 824, with the following metallic coating:
  - 1. Type II, Zinc coated galvanized) by hot-dip process, with the following minimum coating weight.
    - a. Class 4: Not less than 1.2 oz./sq. ft. of uncoated wire surface.

### **2.4 SWING GATES**

- A. General: ASTM F 900 for gate posts and single and double swing gate types.
  - 1. Gate Leaf Width: 48 inches.
  - 2. Framework Member Sizes and Strength: Based on gate fabric height of more than 72 inches.



- B. Pipe and Tubing:
  - 1. Zinc-Coated Steel: ASTM F 1043 and ASTM F 1083; protective coating and finish to match fence framework.
  - 2. Gate Posts: Round tubular steel.
  - 3. Gate Frames and Bracing: Round tubular steel.
- C. Frame Corner Construction: Welded.
- D. Hardware:
  - 1. Hinges: 180-degree outward swing.
  - 2. Latch: Permitting operation from both sides of gate with provision for padlocking accessible from both sides of gate.
  - 3. Padlocks: Provide one padlock for each fence enclosure indicated on the drawings. Master key new padlocks to match existing padlocks installed during Phase 1.
    - a. Provide five master keys.
    - b. Provide ten additional padlocks as attic stock.

## 2.5 FITTINGS

- A. General: Comply with ASTM F 626.
- B. Finish:
  - 1. Metallic Coating for Pressed Steel or Cast Iron: Not less than 1.2 oz. /sq. ft. Zinc.

## PART 3 - EXECUTION

### 3.1 INSTALLATION

- A. Examine areas and conditions, with Installer present, for compliance with requirements for a certified survey of property lines and legal boundaries, site clearing, earthwork, pavement work, and other conditions affecting performance of the Work.
  - 1. Do not begin installation before final grading is completed unless otherwise permitted by Architect.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

### 3.2 PREPARATION

- A. Stake locations of fence lines and terminal posts.

### 3.3 CHAIN-LINK FENCE INSTALLATION

- A. Install chain-link fencing to comply with ASTM F 567 and more stringent requirements indicated.
- B. Post Excavation: Drill or hand-excavate holes for posts to diameters and spacings indicated, in firm, undisturbed soil.
- C. Post Setting: Set posts in concrete at indicated spacing into firm, undisturbed soil.
  - 1. Verify that posts are set plumb, aligned, and at correct height and spacing, and hold in position during setting with concrete.
  - 2. Concrete Fill: Place concrete around posts to dimensions indicated and vibrate or tamp for consolidation. Protect aboveground portion of posts from concrete splatter.
- D. Terminal Posts: Install terminal end and corner posts per ASTM F 567 and terminal pull posts at changes in horizontal or vertical alignment of 15 degrees or more.
- E. Line Posts: Space line posts uniformly.
- F. Post Bracing and Intermediate Rails: Install according to ASTM F 567, maintaining plumb position and alignment of fence posts. Diagonally brace terminal posts to adjacent line posts with truss rods and turnbuckles. Install braces at end posts and at both sides of corner and pull posts.
  - 1. Locate horizontal braces at mid-height of fabric on fences with top rail. Install so posts are plumb when diagonal rod is under proper tension.
- G. Tension Wire: Install according to ASTM F 567, maintaining plumb position and alignment of fence posts. Pull wire taut, without sags. Fasten fabric to tension wire with 0.120-inch-diameter hog rings of same material and finish as fabric wire, spaced a maximum of 24 inches o.c. Install tension wire in locations indicated before stretching fabric. Provide horizontal tension wire at the following locations:
  - 1. Extended along bottom of fence fabric. Install bottom tension wire within 2 inches of bottom of fabric and tie to each post with not less than same diameter and type of wire.
- H. Top Rail: Install according to ASTM F 567, maintaining plumb position and alignment of fence posts. Run rail continuously through line post caps, bending to radius for curved runs and terminating into rail end attached to posts or post caps fabricated to receive rail at terminal posts. Provide expansion couplings as recommended in writing by fencing manufacturer.
- A. Intermediate Rails: Secure to posts with fittings.
- B. Chain-Link Fabric: Apply fabric to outside of enclosing framework. Leave 1-inch bottom clearance between finish grade or surface and bottom selvage unless otherwise indicated. Pull fabric taut and tie to posts, rails, and tension wires. Anchor to framework so fabric remains under tension after pulling force is released.

- C. Tension or Stretcher Bars: Thread through fabric and secure to end, corner, and pull posts, with tension bands spaced not more than 15 inches o.c.
- D. Tie Wires: Use wire of proper length to firmly secure fabric to line posts and rails. Attach wire at one end to chain-link fabric, wrap wire around post a minimum of 180 degrees, and attach other end to chain-link fabric according to ASTM F 626. Bend ends of wire to minimize hazard to individuals and clothing.
  - 1. Maximum Spacing: Tie fabric to line posts at 12 inches o.c. and to braces at 24 inches o.c.

### 3.4 GATE INSTALLATION

- A. Install gates according to manufacturer's written instructions, level, plumb, and secure for full opening without interference. Attach fabric as for fencing. Attach hardware using tamper-resistant or concealed means. Install ground-set items in concrete for anchorage. Adjust hardware for smooth operation.

### 3.5 ADJUSTING

- A. Gates: Adjust gates to operate smoothly, easily, and quietly, free of binding, warp, excessive deflection, distortion, nonalignment, misplacement, disruption, or malfunction, throughout entire operational range. Confirm that latches and locks engage accurately and securely without forcing or binding.

END OF SECTION 32 31 13